Lindy 1m High Speed HDMI Cable, Black Line

Brand : Lindy

Product code: 36471

Product name : 1m High Speed HDMI Cable, Black Line

1m High Speed HDMI Cable, Black Line

Lindy 1m High Speed HDMI Cable, Black Line:

From the lines cable connectivity concept developed by Lindy, Black Line High Speed HDMI cables are fully featured, entry level high resolution connection solutions, perfect for home and small office use.

Black Line High Speed HDMI cables feature triple shielded construction with 30AWG copper coated steel conductors for premium performance and corrosion resistance. Nickel connectors and gold flashed contacts maintain signal integrity and reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 8bit are supported. Black Line HDMI cables are also capable of transmitting 32 channel audio and Dolby® True HD.

The HDMI 2.0 specification is supported for 18Gbps bandwidth capacity in cable lengths up to 15m.

Black Line HDMI cables are available in lengths from 0.5m to 15m.





Features

Cable length * Connector 1 * Connector 2 * Connector 1 gender * Connector 2 gender * Connector 1 form factor Connector 2 form factor Product colour * HDMI version Supported graphics resolutions Audio Return Channel (ARC) HDMI Ethernet channel Data transfer rate Maximum resolution AWG wire size Contact material Connector contacts plating * Connector housing material Connector material Cable material

1 m HDMI Type A (Standard) HDMI Type A (Standard) Male Male Straight Straight Black 2.0 4096 x 2160

- ۲ ۲
- 18 Gbit/s 4096 x 2160 pixels 30 Phosphor bronze Gold Polyvinyl chloride (PVC) Nickel Copper

Features Cable type Round cable Cable jacket material Polyvinyl chloride (PVC) Aluminium Shield material Bending radius (min) 6 cm Colour depth 8 bit Colour sampling 4:4:4 300kHz-825MHz 5dB, 825MHz-2.475GHz 5dB, Nominal attenuation 2.475GHz-4.125GHz 12dB, 4.125GHz-5.1GHz 20dB Certification RoHS, REACH, UL Quantity per pack * 1 pc(s) **Operational conditions** Operating temperature (T-T) -10 - 80 °C Storage temperature (T-T) -10 - 80 °C Weight & dimensions Cable diameter 6 mm Connector 1 dimensions (WxDxH) 19.2 x 34.1 x 10.6 mm Connector 2 dimensions (WxDxH) 19.2 x 34.1 x 10.6 mm Package type Polybag Logistics data 84733080 Harmonized System (HS) code



4002888364713

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.