

Lindy 1m DisplayPort 1.4 Cable, Anthra Line

Brand: Lindy Product code: 36481

Product name: 1m DisplayPort 1.4 Cable, Anthra Line

1m DisplayPort 1.4 Cable, Anthra Line

Lindy 1m DisplayPort 1.4 Cable, Anthra Line:

From the Lines cable connectivity concept developed by Lindy, Anthra Line DisplayPort cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line DisplayPort cables are premium connections that feature triple shielded with 28AWG tinned copper conductors for performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.


UHD resolutions up to 8K 7680x4320@60Hz 4:2:2 8bit, including 4K 4096x2160@144Hz 4:2:2 10bit and HDCP are supported. DisplayPort 1.4 technology and DisplayPort compliance certification ensures compatibility with all DisplayPort enabled devices.

Anthra Line DisplayPort cables are available in lengths from 0.5m to 5m.





Features		Features	
Connector 1 form factor	Straight	Contact material	Phosphor bronze
Connector 2 form factor	Straight	Connector material	Gold
Connector contacts plating	Gold	Plug and Play	✓
DisplayPort version	1.4	Bend radius (min)	5.84 cm
Maximum resolution *	7680 x 4320 pixels	Colour sampling	4:2:2
Supported graphics resolutions	4096 x 2160, 7680 x 4320	Cable type	Round cable
Maximum refresh rate Cable length *	60 Hz 1 m	Nominal attenuation	100MHz-450MHz 5.1dB, 450MHz-8100MHz 33.28dB
Connector 1 *	DisplayPort	Certification	RoHS, REACH, UL
Connector 2 *	DisplayPort	Operational conditions	
Connector 1 gender *	Male	Operating temperature (T-T)	-20 - 80 °C
Connector 2 gender *	Male	Storage temperature (T-T)	-25 - 85 °C
Product colour * Cable material	Black, Grey Tinned copper	Packaging data	
Cable shielding	Copper	Cable diameter	7.3 mm
Jacket material	Polyvinyl chloride (PVC)	Connector 1 dimensions (WxDxH)	21 x 38.9 x 13.6 mm
Connector housing material	Acrylonitrile butadiene styrene (ABS)	Connector 2 dimensions (WxDxH) Quantity per pack	21 x 38.9 x 13.6 mm 1 pc(s)
AWG wire size	28	Package type	Polybag
Data transfer rate	32.4 Gbit/s	Logistics data	
		Harmonized System (HS) code	84733080



4002888364812

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.