



Lindy 3m DisplayPort 1.2 Cable, Cromo Line

Brand : Lindy

Product code: 36303

Product name : 3m DisplayPort 1.2 Cable, Cromo Line

3m DisplayPort 1.2 Cable, Cromo Line

[Lindy 3m DisplayPort 1.2 Cable, Cromo Line:](#)

From the Lines cable connectivity concept developed by Lindy, Cromo Line DisplayPort cables are high performance, designer connections that combine premium construction materials with striking connector architecture.

Cromo Line DisplayPort Cables feature triple shielded construction with 28AWG conductors for premium performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 10bit, including stereoscopic 3D, are supported. Cromo Line DisplayPort cables are capable of delivering 4:4:4 colour spacing for the most accurate colour representation possible.

Cromo Line cables feature sleek chrome design ABS housing to complement the aesthetics of style focused commercial and home applications.

Cromo Line DisplayPort cables are available in lengths from 0.5m to 5m.



Features		Features	
Connector 1 form factor	Straight	Colour sampling	4:4:4
Connector 2 form factor	Straight	Cable type	Round cable
Connector contacts plating	Gold		300kHz-825MHz 5dB, 825MHz-2.475GHz 5dB, 2.475GHz-4.125GHz 12dB, 4.125GHz-5.1GHz 20dB
DisplayPort version	1.2	Nominal attenuation	
Maximum resolution *	4096 x 2160 pixels	Certification	RoHS, REACH, UL
Supported video modes	2160p	Operational conditions	
Maximum refresh rate	60 Hz	Operating temperature (T-T)	-20 - 80 °C
3D	✓	Storage temperature (T-T)	-25 - 85 °C
Cable length *	3 m	Packaging data	
Connector 1 *	DisplayPort	Cable diameter	7.3 mm
Connector 2 *	DisplayPort	Connector 1 dimensions (WxDxH)	19.7 x 12 x 38.9 mm
Connector 1 gender *	Male	Connector 2 dimensions (WxDxH)	19.7 x 12 x 38.9 mm
Connector 2 gender *	Male	Package type	Polybag
Product colour *	Chrome, Grey	Manual	✓
Cable material	Tinned copper	Supplier features	
Cable shielding	Copper	Product or Article Information Sheet available?	✓
Jacket material	Polyvinyl chloride (PVC)	Technical details	
Connector housing material	Acrylonitrile butadiene styrene (ABS)	Pallet net height	3.89 cm
AWG wire size	28	Compliance certificates	REACH, RoHS
Data transfer rate	21.6 Gbit/s	Logistics data	
Contact material	Phosphor bronze	Harmonized System (HS) code	84733080
Connector material	Gold		
Bend radius (min)	7.3 cm		



4002888363037

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date