



## Lindy 2m HDMI to DVI Cable, Black Line

**Brand :** Lindy

**Product code:** 36272

**Product name :** 2m HDMI to DVI Cable, Black Line

2m HDMI to DVI Cable, Black Line

[Lindy 2m HDMI to DVI Cable, Black Line:](#)

From the Lines cable connectivity concept developed by Lindy, Black Line HDMI to DVI-D cables are fully featured, entry level connection solutions, perfect for connecting PCs to monitors or projectors.

Black Line HDMI to DVI-D cables feature triple shielded construction with 30AWG tinned copper conductors for performance and corrosion resistance. Nickel connectors and 24K gold plated contacts maintain signal integrity and reliability.

The tough PVC housing incorporates an integrated finger grip for easy installation. Large thumb screws allow the connector to be tightened into place without the need for a screwdriver and a flexible strain relief prolongs cable life.

Black Line HDMI to DVI-D cables support resolutions up to 1920x1200@60Hz including HDTV resolutions up to 1080p.

Black Line HDMI to DVI-D cables are available in lengths of 0.5m to 10m.



Features		Features	
Connector 1 form factor	Straight	Connector housing material	Polyvinyl chloride (PVC)
Connector 2 form factor	Straight	Connector material	Nickel
Connector contacts plating	Gold	Contact material	Brass
Cable length *	2 m	AWG wire size	30
Connector 1 *	HDMI Type A (Standard)	Cable shielding	Aluminium braid
Connector 2 *	DVI-D	Certification	RoHS, REACH, UL
Connector 1 gender *	Male	<b>Operational conditions</b>	
Connector 2 gender *	Male	Operating temperature (T-T)	-20 - 80 °C
Dual Link DVI	✘	Storage temperature (T-T)	-25 - 85 °C
Maximum resolution	1920 x 1200 pixels	<b>Weight &amp; dimensions</b>	
Supported graphics resolutions	1920 x 1200 (WUXGA)	Cable diameter	5.5 mm
Data transfer rate	4.95 Gbit/s	Connector 1 dimensions (WxDxH)	21.4 x 34.2 x 12.7 mm
Maximum refresh rate	60 Hz	Connector 2 dimensions (WxDxH)	36.8 x 44.5 x 12.5 mm
Bend radius (min)	5.5 cm	<b>Packaging data</b>	
Product colour	Black	Quantity per pack	1 pc(s)
Conductor material	Tinned copper	Package type	Polybag
Nominal attenuation	1 €" 825Mhz 12db	<b>Logistics data</b>	
Jacket material	Polyvinyl chloride (PVC)	Harmonized System (HS) code	84733080
Cable type	Round cable		



4002888362726

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-SEP-2024. Prints or copies of Information are only valid on the printed Publication date