



Lindy 1m DisplayPort to HDMI 10.2G Cable

Brand : Lindy

Product code: 36921

Product name : 1m DisplayPort to HDMI 10.2G Cable

- Connects a DisplayPort equipped device to a 4K UHD HDMI display or projector
 - Supports resolutions up to 3840x2160@30Hz
 - Supports video mirroring and extended desktop modes
 - Audio pass-through if supported by the video source
 - 2 year warranty
- 1m DisplayPort to HDMI 10.2G Cable

Lindy 1m DisplayPort to HDMI 10.2G Cable:

The Lindy DisplayPort to HDMI Cable is ideal for connecting a DisplayPort equipped source such as a PC or laptop to an HDMI display. Supporting 4K UHD resolutions up to 3840x2160@30Hz, this cable is ideal for ensuring video is displayed in superior clarity. This cable can also be used to add another display to extend the available desktop workspace and increase productivity, great for use in residential or workplace office setups.

The DisplayPort to HDMI Cable supports uncompressed 7.1 Audio and compressed Audio such as DTS-HD Master Audio, Dolby TrueHD. Please note that audio output over HDMI is only supported when the graphics card of the laptop or desktop computer supports audio output over DisplayPort.



Features

Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
Cable length *	1 m
Connector 1 *	DisplayPort
Connector 2 *	HDMI Type A (Standard)
Connector 1 gender *	Male
Connector 2 gender *	Male
HDMI version	1.4
DisplayPort version	1.2
Maximum resolution	3840 x 2160 pixels
Supported video modes	1080p
Data transfer rate	10.2 Gbit/s
Bend radius (min)	7.3 cm
Product colour	Black
Conductor material	Tinned copper
Nominal attenuation	100MHz~450MHz -2.44~-5.099dB 450MHz~8100MHz -5.094~32.906dB
Jacket material	Polyvinyl chloride (PVC)
Cable type	Round cable
Connector housing material	Polyvinyl chloride (PVC) / Acrylonitrile butadiene styrene (ABS)

Features

Contact material	Copper
AWG wire size	28
Colour depth	8 bit
Colour sampling	4:4:4
Cable shielding	Aluminium braid
Certification	CE, UKCA, FCC, RoHS, REACH, UL, California Proposition 65

Operational conditions

Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-10 - 80 °C

Weight & dimensions

Cable diameter	7.3 mm
Connector 1 dimensions (WxDxH)	36.4 x 20.5 x 9.4 mm
Connector 2 dimensions (WxDxH)	37.5 x 20.5 x 10.5 mm

Packaging data

Quantity per pack	1 pc(s)
Package type	Polybag

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------



4002888369213

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date