



Lindy 10m Standard HDMI Cable, Anthra Line

Brand : Lindy

Product code: 36967

Product name : 10m Standard HDMI Cable, Anthra Line

10m Standard HDMI Cable, Anthra Line

[Lindy 10m Standard HDMI Cable, Anthra Line:](#)

From the Lines cable connectivity concept developed by Lindy, Anthra Line HDMI cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line HDMI cables are premium connections that feature triple shielded with 24AWG copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:2:0 8bit are supported. Anthra Line HDMI cables are also capable of transmitting 32 channel audio and Dolby® True HD.

These HDMI 2.0 cables support 10.2Gbps bandwidth capacity in cable lengths from 7.5m up to 20m.

Anthra Line HDMI cables are available in lengths from 0.3m to 20m.



Features

Cable length *	10 m
Connector 1 *	HDMI Type A (Standard)
Connector 2 *	HDMI Type A (Standard)
Connector 1 gender *	Male
Connector 2 gender *	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Product colour *	Black, Grey
HDMI version	2.0
3D	✓
Supported graphics resolutions	3840 x 2160, 4096 x 2160
Supported video modes	2160p
Dolby technologies	DTS-HD, Dolby TrueHD
Data transfer rate	10.2 Gbit/s
Maximum refresh rate	60 Hz
AWG wire size	24
Contact material	Phosphor bronze
Connector contacts plating *	Gold
Connector housing material	Polyvinyl chloride (PVC)
Connector material	Gold
Cable material	Copper
Cable type	Round cable

Features

Cable jacket material	Polyvinyl chloride (PVC)
Shield material	Aluminium
Bending radius (min)	9.8 cm
Colour sampling	4:2:0
Nominal attenuation	300kHz-825MHz --- 15dB 825MHz-2.475GHz --- 15 - 29dB 2.475GHz-4.125GHz --- 29 - 44dB 4.125GHz-5.1GHz --- 44 - 48dB
Certification	RoHS, REACH, UL
Quantity per pack *	1 pc(s)

Operational conditions

Operating temperature (T-T)	-20 - 80 °C
Storage temperature (T-T)	-25 - 85 °C

Weight & dimensions

Cable diameter	9.8 mm
Connector 1 dimensions (WxDxH)	21.4 x 41.44 x 12.7 mm
Connector 2 dimensions (WxDxH)	21.4 x 41.44 x 12.7 mm
Package type	Polybag

Technical details

Compliance certificates	RoHS
-------------------------	------

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------



4002888369671

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date