

Lindy 5m USB 2.0 Active Extension Slim

Brand: Lindy Product code: 42817

Product name: 5m USB 2.0 Active Extension Slim

- 5 metre USB 2.0 Active Extension Repeater Lead
- Supports transfer rates up to $480 \mbox{Mbps}$
- For even greater distances simply connect up to 5 cables in series
- Plug and Play
- 2 year warranty

5m USB 2.0 Active Extension Slim

Lindy 5m USB 2.0 Active Extension Slim:

The Lindy USB 2.0 Active Extension Cable Slim uses built-in active electronics to extend the cable length of a USB 2.0 device by an additional 5m whilst continuing to support data transfer rates of up to 480Mbps.

With its USB A male and USB A female connector it allows Type A devices to be connected at longer distances and ensures flexible positioning. Up to 5 extension cables can be chained together to achieve a distance of 25m.

The cable's unique and slim design allows the active electronics to fit into a standard USB connector - an advantage over other active USB leads which use bulky connectors. Compatible with all USB Type A equipped computers.





Features		Features	
USB version *	USB 2.0	Certification	CE, UKCA, FCC, RoHS & REACH
Connector 1 *	Straight 24/28	Weight & dimensions	
Connector 2 * Connector 1 gender * Connector 2 gender * Connector 1 form factor Connector 2 form factor AWG wire size Connector material		Cable length * Cable diameter Weight Bend radius (min) Connector 1 dimensions (WxDxH) Connector 2 dimensions (WxDxH)	5 m 4.8 mm 180 g 4.8 cm 15 x 40 x 6 mm 15 x 45 x 8 mm
Connector material	Nickel Brass	Packaging data	
Connector contacts plating Cable jacket material Conductor material Connector shielding Connector shield material	Gold Polyvinyl chloride (PVC) Tinned copper Aluminium Plastic 480 Mbit/s 0.48 Gbit/s Black Round cable	Package type Package width Package depth Package height Package weight	Blister 214 mm 146 mm 38 mm 200 g
Connector housing material		Packaging content	
Maximum data transfer rate Maximum data transfer rate Product colour *		Quantity per pack * Operational conditions	1 pc(s)
Cable type Plug and Play		Operating temperature (T-T) Storage temperature (T-T)	0 - 70 °C -10 - 80 °C
Transmission medium	Twisted pair	Logistics data	
Nominal attenuation	24AWG: 93.250hm/km 28AWG: 237.250hm/km	Harmonized System (HS) code	84733080





4002888428170

0066510860442



066510860442

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.