

Lindy USB 3.2 Gen 2 Type C Docking Station

Brand: Lindy Product code: 43319

Product name: USB 3.2 Gen 2 Type C Docking Station

- Connects to a tablet, MS Surface or Ultrabook via USB Type C cable
- Adds 3 USB Type A ports (2x USB 3.2 Gen 2 up to 10Gbps, 1x USB 2.0), a USB Type C port for data and Power Delivery, an HDMI and a Gigabit Ethernet port
- Conveniently attaches to your tablet/ultrabook using a streching arm design
- Supports resolutions up to 4K Ultra HD 30Hz

USB 3.2 Gen 2 Type C Mini Docking Station - HDMI, PD 3.0 100W, USB 3.2 Gen 2, Gigabit Lindy USB 3.2 Gen 2 Type C Docking Station. Connectivity technology: Wired, Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB Power Delivery up to: 100 W. Ethernet LAN data rates: 1000 Mbit/s. Product colour: Black, Data transfer rate: 0.48 Gbit/s, Maximum digital resolution: 3840 x 2160 pixels. Power source type: USB, Output voltage: 20 V, Output current: 5 A. Width: 223 mm, Depth: 32 mm, Height: 33 mm









		_	
Ports & interfaces		Power	
Connectivity technology * Host interface * USB 3.2 Gen 2 (3.1 Gen 2) Type-A	st interface * USB 3.2 Gen 1 (3.1 Gen 1) Type-C B 3.2 Gen 2 (3.1 Gen 2) Type-A rts quantity B 3.2 Gen 2 (3.1 Gen 2) Type-C rts quantity B Power Delivery B Power Delivery up to OMI ports quantity * 1	Power source type Output voltage Output current	USB 20 V 5 A
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity USB Power Delivery USB Power Delivery up to HDMI ports quantity *		Operational conditions	
		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	-20 - 70 °C -20 - 85 °C 20 - 80%
		Weight & dimensions	
HDCP HDCP version	1.4/2.2	Width Depth	223 mm 32 mm
Network		Height	33 mm
Ethernet LAN *	✓	Weight	160 g
Ethernet LAN (RJ-45) ports Ethernet LAN data rates	1 1000 Mbit/s	Packaging data Package width	280 mm
Performance		Package depth	110 mm
Data transfer rate 0.48 Gbit/s Maximum digital resolution 3840 x 2160 pixels Maximum refresh rate 30 Hz Product colour * Black Housing material Plastic Certification CE, FCC, CP65	3840 x 2160 pixels 30 Hz	Package height Package weight	45 mm 250 g
		Packaging content	
		Manual	✓
		Technical details	
		Compliance certificates	REACH, RoHS
		Logistics data	
		Harmonized System (HS) code	84733020



4002888433198

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.