

Lindy 15m USB 3.0 Active Extension

Brand: Lindy Product code: 43099

Product name: 15m USB 3.0 Active Extension

- 15 metre USB 3.0 Active Extension Repeater Lead
- Supports transfer rates up to 5Gbps
- For even greater distances simply connect 2 cables in series
- Plug and Play
- 2 year warranty

15m USB 3.0 Active Extension

Lindy 15m USB 3.0 Active Extension. Cable length: 15 m. Connector 1: USB A, Connector 2: USB A, USB version: USB 3.2 Gen 1 (3.1 Gen 1), Maximum data transfer rate: 5 Gbit/s, Connector contacts plating: Nickel, Product colour: Black





Features		Power	
USB version *	USB 3.2 Gen 1 (3.1 Gen 1)	Power note	3.5/1.35mm DC
Connector 1 *	nnector 2 * USB A nnector 1 gender * Male nnector 2 gender * Female nnector 1 form factor Straight nnector 2 form factor Straight G wire size 28/28/22 nnector material Nickel ntact material Copper	Weight & dimensions	
Connector 2 * Connector 1 gender * Connector 2 gender * Connector 1 form factor Connector 2 form factor AWG wire size Connector material		Cable length * Cable diameter Weight Bend radius (min) Connector 1 dimensions (WxDxH) Connector 2 dimensions (WxDxH) Connector 3 dimensions (WxDxH)	15 m 7 mm 1.33 kg 6 cm 16 x 49 x 9 mm 35 x 85 x 15 mm 35 x 100 x 15 mm
Contact material Connector contacts plating		Packaging data	
Cable jacket material Polyvinyl chloride (PVC) Conductor material Copper Connector shielding Connector shield material Aluminium Connector housing material Plastic	Package type Package width Package depth Package height Package weight	Polybag 300 mm 80 mm 300 mm 1.39 kg	
Maximum data transfer rate	5000 Mbit/s 5 Gbit/s Black Round cable	Packaging content	
Maximum data transfer rate Product colour * Cable type		Quantity per pack * Manual	1 pc(s) ✓
Plug and Play	✓	Operational conditions	
Transmission medium Nominal attenuation	Twisted pair 100 MHz, -1.5 dB 1.25 GHz, -5.0 dB 2.5 GHz, -7.5 dB 7.5 GHz, -25 dB CE, UKCA, FCC, RoHS, REACH	Operating temperature (T-T) Storage temperature (T-T)	0 - 55 °C -20 - 85 °C
Certification		Logistics data Harmonized System (HS) code	84733080



4002888430999

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.