

Product data sheet

Specifications



APC Smart-UPS Ultra, 3000VA 230V 1U, with Lithium-Ion Battery, with SmartConnect

SRTL3KRM1UIC

Overview

| | |
|---------------------|---|
| Presentation | Ultra high density on-line power protection with scalable runtime supported by Lithium-Ion batteries. |
| Lead time | Usually in Stock |

Main

| | |
|-------------------------------|--|
| Main Input Voltage | 230 V |
| Other Input Voltage | 230 V |
| Main Output Voltage | 230 V |
| Other Output Voltage | 230 V |
| Rated power in W | 3000 W |
| Rated power in VA | 3000 VA |
| Input Connection Type | BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P |
| Output connection type | 3 IEC 60320 C13 2 IEC 60320 C19 |
| Number of rack unit | 1U |
| Cable length | 2.44 m |
| Number of cables | 1 |
| Battery type | Li-Ion (Lithium-Ion) |
| Provided equipment | RJ45 cable USB cable Safety guide Rack mounting brackets Rack mounting support rails Wall mounting brackets Stabilization feet Screws |

Complementary

| | |
|-------------------------|---|
| Software package | SmartConnect software for remote power monitoring feature availability varies by terms of use |
|-------------------------|---|

Batteries & Runtime

| | |
|---|-------|
| Battery recharge time | 1.5 h |
| Number of battery replacement quantity | 1 |
| Battery voltage | 50 V |

| | |
|-----------------------|--|
| Battery charger power | 448 W |
| Battery design life | 8...10 year(s) |
| Battery power in VAH | 336 VAh runtime |
| Battery option | SRTL50RMBP1U-LI 1 1240 VAh SRTL50RMBP1U-LI 2 2471 VAh SRTL50RMBP1U-LI 3 3706 VAh SRTL50RMBP1U-LI 4 4944 VAh SRTL50RMBP1U-LI 5 6192 VAh |

| | |
|------------------|---|
| Extended runtime | 1 |
|------------------|---|

General

| | |
|------------------------|--------------|
| Product web sub-family | High density |
|------------------------|--------------|

| | |
|-----------|----|
| Redundant | No |
|-----------|----|

Physical

| | |
|--------|-------------|
| Colour | Silver grey |
|--------|-------------|

| | |
|--------|-------|
| Height | 43 mm |
|--------|-------|

| | |
|-------|--------|
| Width | 432 mm |
|-------|--------|

| | |
|-------|--------|
| Depth | 560 mm |
|-------|--------|

| | |
|------------|---------|
| Net weight | 15.9 kg |
|------------|---------|

| | |
|---------------------|---------------|
| Mounting preference | No preference |
|---------------------|---------------|

| | |
|---------------|---|
| Mounting mode | Rack-mounted with kit Tower-mounted with kit |
|---------------|---|

| | |
|--------------------|---|
| Two post mountable | 1 |
|--------------------|---|

| | |
|----------------|-----|
| USB compatible | Yes |
|----------------|-----|

| | |
|-------------------|------------------------|
| Mounting position | Horizontal Vertical |
|-------------------|------------------------|

Input

| | |
|-------------------|-----------------------|
| Network frequency | 50/60 Hz auto-sensing |
|-------------------|-----------------------|

| | |
|----------------------|------------------------------------|
| Input voltage limits | 160...275 V adjustable (half load) |
|----------------------|------------------------------------|

Output

| | |
|---------------------------------|--------|
| Maximum configurable power in W | 3000 W |
|---------------------------------|--------|

| | |
|------------------|---------------------------------|
| Output frequency | 50/60 Hz +/- 3 Hz sync to mains |
|------------------|---------------------------------|

| | |
|--------------|-------|
| Crest factor | 3 : 1 |
|--------------|-------|

| | |
|----------|---------|
| UPS type | On-Line |
|----------|---------|

| | |
|-----------|-----------|
| Wave type | Sine wave |
|-----------|-----------|

| | |
|-------------|--|
| Bypass type | Internal bypass (automatic and manual) |
|-------------|--|

| | |
|----------------------------------|---------|
| Maximum configurable power in VA | 3000 VA |
|----------------------------------|---------|

Conformance

| | |
|------------------------|------------|
| Product certifications | CE UKCA |
|------------------------|------------|

| | |
|---------|-----------------|
| Marking | CE Mark UKCA |
|---------|-----------------|

| | |
|-----------|----------------|
| Standards | EN/IEC 62040-1 |
|-----------|----------------|

Environmental

| | |
|---------------------------------------|-------------------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % non-condensing |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -15...45 °C |
| Storage Relative Humidity | 0...95 % non-condensing |
| Storage altitude | 0.00...15240.00 m |
| Acoustic level | 55 dB |
| IP degree of protection | IP20 |

Communications & Management

| | |
|----------------------------|--|
| Control panel | Touch screen LCD user interface |
| Alarm | Audible and visible alarms : prioritized by severity |
| Emergency power off | Yes |
| Communication port support | SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 27.8 cm |
| Package 1 Width | 56.4 cm |
| Package 1 Length | 76.4 cm |
| Package 1 Weight | 24.2 kg |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| RoHS exemption information | Yes |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 5 years repair or replace |
|----------|---------------------------|

Recommended replacement(s)