



## APC SMC2000I-2U UPS-virtalähde Linjainteraktiivinen 2 kVA 1300 W

**Tuotemerkki :** APC

**Tuotekoodi:** SMC2000I-2U

**Tuotteen nimi :** SMC2000I-2U



APC SMC2000I-2U. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 2 kVA, Lähtöteho: 1300 W. Pistorasian tyypit: C13 liitin, C19 liitin, C20 liitin. Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 5 vuosi/vuosia, Akun latausaika: 3 h. Kotelo: Telineasennettava, Näytön tyyppi: LCD, Sertifiointi: C-tick, CE, EAC, GOST, GS Mark, IRAM, SABS, VDE. Tuotteen leveys: 480 mm, Tuotteen syvyys: 470 mm, Tuotteen korkeus: 89 mm



Features		Battery	
UPS topology *	Line-Interactive	Automatic battery test	✓
Output power capacity *	2 kVA	Cold start	✓
Output power *	1300 W		
Waveform *	Sine		
Input operation voltage (min) *	180 V		
Input operation voltage (max) *	287 V		
Input frequency *	50/60 Hz		
Output operation voltage (max)	230 V		
Automatic Voltage Regulation (AVR)	✓		
Surge energy rating	300 J		
Output voltage Total Harmonic Distortion (THD)	5%		
Noise level	45 dB		
Surge protection	✓		
Audible alarm(s)	✓		
Audible alarm modes	Low battery alarm		
Auto-restart	✓		
Ports & interfaces		Design	
AC outlet types	C13 coupler, C19 coupler, C20 coupler	Form factor *	Rackmount
USB port	✓	Display type	LCD
		LED indicators	✓
		Certification	C-tick, CE, EAC, GOST, GS Mark, IRAM, SABS, VDE
Battery		Operational conditions	
Battery technology	Sealed Lead Acid (VRLA)	Operating temperature (T-T)	0 - 40 °C
Number of batteries supported	1	Storage temperature (T-T)	-5 - 45 °C
Battery life (max)	5 year(s)	Operating relative humidity (H-H)	0 - 95%
Battery recharge time	3 h	Storage relative humidity (H-H)	0 - 95%
Hot-swap battery	✓	Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Technical details	
		Compliance certificates	RoHS
		Weight & dimensions	
		Width	480 mm
		Depth	470 mm
		Height	89 mm
		Weight	26.2 kg
		Package width	590 mm
		Package depth	600 mm
		Package height	250 mm
		Package weight	30.2 kg

### Packaging data

Cables included	USB cable
Manual	✓



0731304310082



731304310082

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.