



APC SMC2000I UPS-virtalähde Linjainteraktiivinen 2 kVA 1300 W 7 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SMC2000I

Tuotteen nimi : SMC2000I

APC SMC2000I. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 2 kVA, Lähtöteho: 1300 W. Pistorasian tyypit: C13 liitin, C19 liitin, C20 liitin, Ulostulojen määrä: 7 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 499 VAh, Akun kestoikä (maks.): 5 vuosi/vuosia. Kotelo: Kompakti, Tuotteen väri: musta, Näytön tyyppi: LCD. Tuotteen leveys: 170 mm, Tuotteen syvyys: 440 mm, Tuotteen korkeus: 216 mm



Features		Battery	
UPS topology *	Line-Interactive	Hot-swap battery	✓
Output power capacity *	2 kVA	Automatic battery test	✓
Output power *	1300 W	Cold start	✓
Waveform *	Sine		
Input operation voltage (min) *	170 V		
Input operation voltage (max) *	300 V		
Input frequency *	47/63 Hz		
Output operation voltage (max)	230 V		
Automatic Voltage Regulation (AVR)	✓		
Surge energy rating	300 J		
Output voltage Total Harmonic Distortion (THD)	5%		
Noise level	45 dB		
Surge protection	✓		
Audible alarm(s)	✓		
Web-based management	✓		
Audible alarm modes	Low battery alarm		
Auto-restart	✓		
Ports & interfaces		Design	
AC outlet types	C13 coupler, C19 coupler, C20 coupler	Form factor *	Compact
AC outlets quantity	7 AC outlet(s)	Product colour *	Black
USB port	✓	Display type	LCD
		LED indicators	✓
		Certification	C-tick, CE, GOST, SABS, VDE, REACH
Battery		Operational conditions	
Battery technology	Sealed Lead Acid (VRLA)	Operating temperature (T-T)	0 - 40 °C
Battery capacity	499 VAh	Storage temperature (T-T)	-15 - 45 °C
Number of batteries supported	1	Operating relative humidity (H-H)	0 - 95%
Battery life (max)	5 year(s)	Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Technical details	
		Compliance certificates	RoHS
		Weight & dimensions	
		Width	170 mm
		Depth	440 mm
		Height	216 mm
		Weight	27.5 kg
		Package width	370 mm
		Package depth	590 mm
		Package height	330 mm

Battery

Battery recharge time 3 h

Weight & dimensions

Package weight 30 kg

Packaging data


Cables included USB cable

Resource CD ✓

Software CD ✓



0731304310075



731304310075

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.