Lenovo

Lenovo ThinkSystem ST250 V2 palvelin 0 GB Tower Intel Xeon E E-2378 2,6 GHz 32 GB DDR4-SDRAM 750 W

Tuotemerkki : Lenovo   **Tuoteperhe:** ThinkSystem   **Tuotekoodi:** 7D8FA01YEA

Tuotteen nimi : ST250 V2

Lenovo ThinkSystem ST250 V2. Suoritinperhe: Intel Xeon E, Prosessorin taajuus: 2,6 GHz, Prosessorimalli: E-2378. Sisäinen muisti: 32 GB, Sisäisen muistin tyyppi: DDR4-SDRAM, Muistin sijoittelu (paikat x koko): 1 x 32 GB. Kokonaistallennuskapasiteetti: 0 GB. Ethernet LAN, Kaapelitekniikka: 10/100/1000Base-T(X). Virtalähde: 750 W, Vikasietoisen virtalähteen tuki (RPS). Alustatyyppi: Tower

Processor

Processor manufacturer *	Intel
Processor family *	Intel Xeon E
Processor model *	E-2378
Processor frequency *	2.6 GHz
Processor boost frequency	4.8 GHz
Processor cores	8
Processor cache	16 MB
Motherboard chipset	Intel C256
Number of processors installed	1

Memory

Internal memory *	32 GB
Internal memory type *	DDR4-SDRAM
Memory slots	4x DIMM
ECC	✔
Memory layout (slots x size)	1 x 32 GB
Maximum internal memory *	128 GB

Storage

Total storage capacity *	0 GB
RAID support *	✔
RAID levels	0, 1, 5, 10
Supported RAID controllers	5350-8i
Optical drive type *	✘
Internal drive bays	8

Network

LAN controller	Broadcom BCM5720
Ethernet LAN	✔
Cabling technology	10/100/1000Base-T(X)
Ethernet interface type	Gigabit Ethernet

Ports & interfaces

Ethernet LAN (RJ-45) ports *	2
USB 2.0 ports quantity	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	4

Ports & interfaces

Serial ports quantity	1

Design

Chassis type *	Tower
Product colour	Black

Performance

Performance management	XClarity Enterprise
Noise level	27.6 dB
Trusted Platform Module (TPM)	✔
Trusted Platform Module (TPM) version	2.0

Software

Operating system installed *	✘
Compatible operating systems *	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi

Processor special features

CPU configuration (max)	1

Power

Redundant power supply (RPS) support *	✔
Power supply *	750 W
Number of redundant power supplies installed	1

Operational conditions

Operating temperature (T-T)	5 - 45 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	8 - 90%
Storage relative humidity (H-H)	8 - 90%
Operating altitude	0 - 3050 m

Weight & dimensions

Width	176 mm
Depth	578 mm
Height	444 mm
Weight	23.6 kg

Ports & interfaces

VGA (D-Sub) ports quantity   1

8032976157855