KYOCERA ECOSYS MA3500cifx Laser A4 1200 x 1200 DPI 35 ppm

Tuotemerkki: KYOCERA Tuoteperhe: ECOSYS Tuotekoodi: 1102Z33NL0

Tuotteen nimi: MA3500cifx

KYOCERA ECOSYS MA3500cifx. Tulostustekniikka: Laser, Tulostus: Väritulostus, Suurin resoluutio: 1200 x 1200 DPI, Tulostusnopeus (väri, normaalilaatu, A4/US Letter): 35 ppm. Kopiointi: Värikopiointi, Kopioinnin enimmäistarkkuus: 600 x 600 DPI. Skannaus: Väriskannaus, Optinen skannauserottelutarkkuus: 600 x 600 DPI. Faksaus: Yksittäisfaksin lähetys. Kaksipuolinen toiminto: Kopiointi, Faksi, Tulosta, Skannaus. Suurin ISO A-luokan paperikoko: A4. Suoratulostus. Tuotteen väri: musta, Valkoinen






Printing		Input & output capacity	
Duplex printing mode	Auto	Maximum input capacity	2000 sheets
Print technology *	Laser	Maximum output capacity	250 sheets
Printing *	Colour printing	Paper handling	
Duplex printing *	✓	Maximum ISO A-series paper size *	A4
Maximum resolution *	1200 x 1200 DPI	Paper tray media types *	Labels, Letterhead, Plain paper, Pre-
Print speed (black, normal quality, A4/US Letter) *	35 ppm	, , , , , , , , , , , , , , , , , , , ,	printed
Print speed (colour, normal quality,		ISO A-series sizes (A0A9) *	A4, A5, A6
A4/US Letter)	35 ppm	ISO B-series sizes (B0B9)	B5, B6
Duplex print speed (black, normal	17.5 ppm	Non-ISO print media sizes	Folio, Legal, Letter
quality, A4/US Letter)		Multi-Purpose Tray media weight	60 - 220 g/m²
Duplex print speed (colour, normal quality, A4/US Letter)	17.5 ppm	Ports & interfaces	
Warm-up time	26 s	Direct printing *	✓
Time to first page (black, normal)	5.7 s	USB port	✓
Time to first page (colour, normal)	7 s	USB 2.0 ports quantity	2
N-in-1 print function	✓	Optional connectivity	Ethernet, Wireless LAN
N-up printing	2, 4	Network	
Watermark printing	✓	Wi-Fi *	×
Economical printing	✓	Ethernet LAN *	✓
Secure printing	✓	Cabling technology	10/100/1000Base-T(X)
Poster printing function	✓	Ethernet LAN data rates	10,100,1000 Mbit/s
Borderless printing	×	Bluetooth	×
DVD/CD printing	×	Near Field Communication (NFC)	×
Copying		Security algorithms	SNMPv3, TLS
.,		Mobile printing technologies	Apple AirPrint, Mopria Print Service
Duplex copying *	Auto	Performance	
Duplex copying mode Copying *	Auto Colour copying	Maximum internal memory	3000 MB
Copyring	Colour Copyllig	· · · · · · · · · · · · · · · · · · ·	

Maximum copy secolution	Convins		Dorformance	
Meanman copy size of publick, normal quality, AM (2007 speed foliack, normal quality, AM (2007 speed foliack), normal quality, AM (2007 speed foliack), normal quality, AM (2007 speed foliack), and	Copying		Performance	-
Copy speed (cloudr, normal quality, Al) 35 c/m Multi-hi processor 4MN Cartex-A9 Copy speed (colour, normal quality, Al) 35 c/m Processor framity AMN Cartex-A9 Time to fists copy (black, normal) 1.5 c Processor frequency 1200 MHz Time to fists copy (black, normal) 7.2 c Processor croses 2 Maximum number of copies 995 copies Introduction year 2023 and 18 Nin 1 copy function (Nel) 2 - 4.00% Sound pressure level (standby) 30 d8 Nin 1 copy function (Nel) 2 - 4.00% Design Black, White Copy programming function 7 - 4.00 Product colour " Black, White Duplex scanning 7 - 4.00 Market positioning " Black, White Scanning 7 - 4.00 Colour display 7 - 7.00 Optical scanning resolution Auto Colour display 7 - 7.00 Scan speed (scolour) 1 - 4.00 Prover 499.1 W Scan speed (scolour) 1 - 4.00 Prover consumption (printing) 449.1 W Scan speed (scolour) 1 - 5.00 Prover c	• •			
May	• •	A4	•	
Copy speed (coour, normal quality) 5 pm Processor frequiry ARM Cartax-AB Time to first copy (lobur, normal) 6.1 s Processor frequency 1200 MHz Time to first copy (colour, normal) 7.2 s Processor cores 2023 Maximum number of copies 990 copies Introduction year 2023 Nin-1 copy function 7 Sound pressure level (printing) 51 dB Nin-1 copy function 7 Polesign Black, White Nin-1 copy function 7 Polesign Black, White Copy programming function 7 Display diagonal 1.7 s cm (7") Copy programming function Auto Control type Touch Copy programming function Auto Control type Touch Copy programming function Auto Colour display 7 Opplex scanning Auto Colour scanning Touch Opplex scanning Colour scanning Power consumption (printing) 459.1 W Optical scanning resolution Blated & ADE scanner Power consumption (sleep) 5.73 L	· · · · · · · · · · · · · · · · · · ·	35 cpm	•	
Time to first copy (black, normal)	Copy speed (colour, normal quality,	25 cnm	'	
Thins to first, copy (colour, normal) 7.2 s Processor cores 2	A4)	33 Cpiii	•	
Maximum number of copies 999 copies 99	• •		· -	
Sound pressure level (printing) 51 dB	• •			
N-in-1 copy function	•	•	•	
Name	'			
Copy programming function ✓ Product colour* Black, White ID card copy function ✓ Market positioning* Business Scanning ✓ Buil-in display* ✓ Duplex scanning mode Auto Control type Touch Optical scanning resolution ** 600 x 600 DPI Power Touch Scanner type ** Flatbed & ADF scanner Power consumption (printing) 449.1 W Scan technology CIS/CCD Power consumption (printing) 449.1 W Scan speed (cloulur) 50 ppm Power consumption (steep) 0.5 W Scan speed (cloulur) 50 ppm Power consumption (steep) 0.5 W Scan speed (cloulur) 100 ppm Power consumption (steep) 0.5 W Scan speed (cloulur) 100 ppm Power consumption (steep) 0.3 W Duplex scan speed (cloulur) 100 ppm Power consumption (steep) 0.3 W Duplex scan speed (cloulur) 120 ppm Power consumption (steep) 0.3 W Duplex scan speed (cloulur) 120 ppm Power consumption (steep) 0.3 W				
Darad copy function	• •	•		· · · · · · · ·
Scanning Duplex scanning mode Scanning Optical scanning mode Scanning Optical scanning resolution Scanning Optical scanning resolution Scanner type Scan technology ClS/CCD Power Scan technology ClS/CCD Scan speed (clour) Duplex scansed (clour) Duplex scan speed (clour) Scan speed (clour) Scan speed (clour) Duplex scan				
Display diagonal 17.8 cm (7°) Display diagonal 17.8 cm (7°) Display canning mode Auto Colour display ✓ Control type Touch	ID-card copy function	•	•	
Duplex scanning mode Auto Control type Touch Optical scanning mode Auto Colour scanning Colour scanning Colour scanning V Optical scanning resolution* 600 x 600 pPl Power V Scanner type * Flatbed & ADF scanner Power consumption (copying) 449.1 W Scan technology CIS/CCD Power consumption (copying) 449.1 W Scan speed (clour) 50 ppm Power consumption (steep) 0.5 W Scan speed (clour) 100 ppm Energy Star Typical Electricity 0.5 W Scan speed (clour) 100 ppm Energy Star Typical Electricity 0.3 4 kWh/week Duplex scan speed (clour) 100 ppm Energy Star Typical Electricity 0.4 4 kWh/week Duplex scan speed (clour) 100 ppm Energy Star Typical Electricity 0.3 4 kWh/week Duplex scan speed (clour) 100 ppm Energy Star Typical Electricity 0.3 6 kWh/week Duplex scan speed (clour) 100 ppm Energy Star Typical Electricity 0.3 6 kWh/week Exit Scan Star Star Star Star Star Star Star Star	Scanning		, ,	
Duplex scanning mode Auto Colour display Colour scanning Optical scanning resolution * 600 x 600 DPI Power Scannet retype * Flatbed 6 ADF scanner Power consumption (copying) 449.1 W Scan to (SCCD E-mail, FTP, SMB, USB Power consumption (standby) 18.8 W Scan speed (clour) 50 ppm Power consumption (standby) 18.8 W Scan speed (clour) 100 ppm Power consumption (standby) 18.8 W Scan speed (clour) 100 ppm Power consumption (standby) 18.8 W Scan speed (clour) 100 ppm Power consumption (standby) 18.8 W Scan speed (clour) 100 ppm Power consumption (standby) 18.8 W Scan speed (clour) 100 ppm Power consumption (standby) 1.0 University Image formats supported JPG, TIF AC input voltage 22.0 -240 V Duplex scan speed (back) JPG, TIF AC input voltage 220 -240 V Fax Power Water sequence 30.606 Hz Back page (back) JPG, TIF AC input voltage 220 -240 V <td>Duplex scanning *</td> <td>✓</td> <td>, , ,</td> <td></td>	Duplex scanning *	✓	, , ,	
Scanning ' Colour scanning or Colour Scan technology (Scan technology (SCCO Power consumption (copying) 449.1 W 479.1 W 526.1 technology (SCCO Power consumption (copying) 479.1 W 526.1 technology (SCan technology (SCCO Power consumption (copying) 479.1 W 526.1 technology (SCan technology (SCan technology) 50 ppm 60 Power consumption (steep) 0.5 W 526.1 technology (SCan speed (colour) 50 ppm 60 Power consumption (steep) 0.5 W 526.1 technology (SCCO Power Consumption (SCCO Power Power Power Consumption (SCCO Power Power Power Power Consumption (SCCO Power	Duplex scanning mode	Auto		
Scanner type* Flatbed & ADF scanner Power consumption (printing) 449.1 W Scan technology CIS/CCD Power consumption (copying) 479.1 W Scan technology CIS/CCD Power consumption (standby) 18.8 W Scan speed (colour) 50 ppm Power consumption (standby) 18.8 W Scan speed (flack) 60 ppm Power consumption (steep) 0.5 W Scan speed (flack) 100 ppm Power consumption (steep) 0.1 W Duplex scan speed (foliuch) 100 ppm Energy Star Typical Electricity 0.34 kWh/week Consumption (TEC) 220 - 240 V Consumption (TEC) 220 - 240 V Consumption (TEC) 50/60 Hz Fax System requirements Fax Windows operating systems V Supported Mac operating systems supported Mac operating systems V Supported Mac operating systems supported Mac operating systems V Supported Mac operating systems supported Mac operating systems V Supported Mac operating systems supported Mac operating systems V Supported Mac operating systems supported Mac operating systems V Supported Mac operating systems supported Mac operating systems supported Mac operating systems V Supported Mac operating systems supported Mac operating systems V Supported Mac operating systems supported Mac operating systems V Supported Mac operating systems supported Mac operating systems V Supported Mac operating systems V Supported Mac operating syste	· -	Colour scanning	Colour display	•
Scan technology CIS/CCD Power consumption (copying) 479.1 W Scan to E-mail, FTP, SMB, USB Power consumption (standby) 18.8 W Scan speed (cloul) 50 ppm Power consumption (steich) 0.5 W Scan speed (cloul) 100 ppm Power consumption (off) 0.1 W Duplex scan speed (cloul) 100 ppm Consumption (TEC) 0.34 kWh/week Duplex scan speed (cloul) 120 ppm Consumption (TEC) 0.34 kWh/week Duplex scan speed (cloul) 120 ppm Consumption (TEC) 0.34 kWh/week Duplex scan speed (cloul) 120 ppm Consumption (TEC) 0.34 kWh/week Duplex facing JEG, TIF AC input requency 50/60 Hz Fax Windows operating systems V Fax Windows operating systems supported Mac OS X 10.9 Mavericks, Mac OS X 11.0 Mavericks, Mac OS X 11.0 Mavericks, Mac OS X 11.0 Mavericks, Mac OS X 12.0 Mavericks, Mac OS X	Optical scanning resolution *	600 x 600 DPI	Power	
Scan speed (clour) E-mail, FTP, SMB, USB Power consumption (standby) 18.8 W Scan speed (black) 60 ppm Power consumption (sleep) 0.5 W Scan speed (black) 60 ppm Power consumption (off) 0.1 W Duplex scan speed (clour) 100 ppm Energy Star Typical Electricity 0.34 kWh/week Image formats supported JPG, TIF AC input woltage 220 - 240 V Document formats supported JPG, TIF AC input woltage 220 - 240 V Document formats supported JPG, TIF AC input woltage 220 - 240 V Fax System 50/60 Hz Fax Systems 50/60 Hz Faxing ** Mono faxing Mac operating systems supported Amac OS X 10.9 Mavericks, Mac OS X 12.0 Montrey, Mac OS X 12.0 Montr	Scanner type *	Flatbed & ADF scanner	Power consumption (printing)	449.1 W
Scan speed (clour) 50 ppm Power consumption (sleep) 0.5 W Scan speed (black) 60 ppm Power consumption (off) 0.1 W Duplex scan speed (clolack) 120 ppm Energy Star Typical Electricity 0.34 kWh/week Duplex scan speed (black) 120 ppm AC input voltage 220 - 240 V Document formats supported PDF, XPS AC input requency 50/60 Hz System requirements Fax System requirements Windows operating systems supported Mac OS X 10.9 Mavericks, Mac OS X 12.0 Fax fransmission speed 2.5 sec/page Mac operating systems supported Mac OS X 10.9 Mavericks, Mac OS X 12.0 Fax transmission speed 3.56 kbit/s Operational conditions Mac OS X 10.9 Mavericks, Mac OS X 12.0 Fax transmission speed 3.56 kbit/s Operating relative humidity (H-H) 10 - 80% Auto-redialing Y Storage relative humidity (H-H) 10 - 80% Auto-redialing Y Storage relative humidity (H-H) 10 - 80% Fax forwarding Y Storage relative humidity (H-H) 10 -	Scan technology	CIS/CCD	Power consumption (copying)	479.1 W
Scan speed (black) 60 ppm Power consumption (off) 0.1 W Duplex scan speed (colour) 100 ppm Energy Star Typical Electricity 0.34 kWh/week Duplex scan speed (black) 120 ppm Ac input voltage 220 - 240 V Document formats supported PDF, XPS Ac input voltage 220 - 240 V Document formats supported PDF, XPS Ac input requency 50/60 Hz System requirements Windows operating systems Fax franking* Mono faxing Mac operating systems supported Mac OS X 10.9 Mavericks, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura Fax transmission speed 35.6 kbli/s Operating systems supported Mac OS X 10.9 Mavericks, Mac OS X 13.0 Ventura Fax transmission speed 35.6 kbli/s Operating systems supported Mac OS X 13.0 Ventura Fax transmission speed 35.6 kbli/s Operating systems supported 10.0 Big Sur, Mac OS X 13.0 Ventura Fax transmission speed 35.6 kbli/s Operating systems supported 11.0 Big Sur, Mac OS X 13.0 Ventura Fax transmission speed 35.6 kbli/s Operating structure (T-T) 10.0 80% Fax	Scan to	E-mail, FTP, SMB, USB	Power consumption (standby)	18.8 W
Duplex scan speed (clolur) 100 ppm Energy Star Typical Electricity 0.34 kWh/week Duplex scan speed (black) 120 ppm Consumption (TEC) 220 - 240 V Image formats supported PDF, XPS AC input votage 220 - 240 V Fax System requirements Fax Windows operating systems supported Y Faxing* Mono faxing Mac OS X 10.9 Mavericks, Mac OS X 11.0 Monterey, Mac OS X 12.0 Monterey, Mac OS X 12.0 Monterey, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura Modem speed 33.6 Kbit/s Operating active humidity (H-H) 10 - 80% Fax memory 256 pages Operating relative humidity (H-H) 10 - 80% Auto-redialing Y Storage temperature (T-T) 20 - 40 °C Speed dialling Y Operating relative humidity (H-H) 10 - 32.5 °C Fax forwarding Y Operating attitude 0 - 3500 m Features Sustainability compliance Y Recommended duty cycle 1000 - 3500 pages per month Sustainability compliance Y Maximum duty cycle* 10000 - 3500 pages per month Sustainability certificates Blue	Scan speed (colour)	50 ppm	• • • • •	0.5 W
Duplex scan speed (black) Image formats supported JPG, TIF AC input voltage AC input trequency AC input trequency AC input frequency AC in put frequency AC in Big Sur, Mac OS X 13.0 Put in Mac OS X 13.0 Put in Ac A in a put in a pu	•	• •	• • • •	0.1 W
Image formats supported JPG, TIF AC input voltage 220 - 240 V So/60 Hz Fax	·	• •		0.34 kWh/week
Document formats supported PDF, XPS AC input frequency 50/60 Hz Fax Document formats supported PDF, XPS AC input frequency 50/60 Hz Fax Duplex faxing	·	• •	•	220 - 240 V
Fax Pax Pax Pax Pax Pax Pax Pax Pax Pax P			· -	
Duplex faxing Faxing* Mono faxing Fax resolution (black) 400 x 400 DPI Fax transmission speed 2.5 sec/page Mac operating systems supported Mac operating syst		PDF, AP3		
Faxing Mono faxing Mono faxing Mac operating systems supported 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 12.0 Monterey Monterey, Mac OS X 12.0 Monterey, Mac OS X 12.0 Monterey, Mac OS X 12.0 Monterey Monterey, Mac OS	Fax			
Fax resolution (black) Fax memory 256 pages Operational conditions Operating relative humidity (H-H) Operating relative humidity (H-H) 10 - 80% Auto-redialing ✓ Operating temperature (T-T) Fax forwarding Fax delayed sending ✓ Operating elative humidity (H-H) Operating temperature (T-T) 10 - 30.5 °C Fax delayed sending ✓ Operating altitude Operating between the midity (H-H) 10 - 90% Operating temperature (T-T) 10 - 30.5 °C Fax delayed sending ✓ Operating altitude Operating between the midity (H-H) 10 - 90% Operating temperature (T-T) 10 - 30.5 °C Fax forwarding Fax delayed sending ✓ Operating altitude Operating between the midity (H-H) 10 - 90% Operating between the midity (H-H) 10 - 90% Operating temperature (T-T) 10 - 32.5 °C Fax forwarding Fax forwarding Fax forwarding ✓ Operating relative humidity (H-H) 10 - 80% Formation Fax forwarding ✓ Operating relative humidity (H-H) 10 - 80% Formation Fax forwarding temperature (T-T) 10 - 32.5 °C Fax forwarding temperature (T-T) 10 - 30.5 °C Fax forwarding temperature (T-T) 10 - 20 - 40 °C Operating elative humidity (H-H) 10 - 80% Eavity temperature (T-T) 10 - 20 - 40 °C Operating elative humidity (H-H) 10 - 80% Eavity temperature (T-T) 10 - 30.5 °C Fax forwarding temperature (T-T) 10 - 20 - 40 °C 10 - 20 - 40 °	Duplex faxing	✓		✓
Fax transmission speed 33.6 Kbit/s Operational conditions Fax memory 256 pages Operating relative humidity (H-H) 10 - 80% Auto-redialing	Faxing *	Mono faxing		Mac OS X 10.9 Mavericks, Mac OS X
Modem speed 33.6 kbit/s Operational conditions Fax memory 256 pages Operating relative humidity (H-H) 10 - 80% Auto-redialing			Mac operating systems supported	
Fax memory 256 pages Operating relative humidity (H-H) 10 - 80% Auto-redialing	· ·	· -		Monterey, Mac OS X 13.0 Ventura
Auto-redialing V Storage temperature (T-T) Speed dialling V Operating temperature (T-T) 10 - 32.5 °C Fax forwarding V Operating temperature (T-T) Fax forwarding V Operating temperature (T-T) Fax delayed sending V Operating altitude O - 3500 m Sustainability Sustainability compliance Maximum duty cycle Maximum duty cycle Maximum duty cycle Maximum duty cycle Operating temperature (T-T) Operating altitude O - 3500 m Sustainability Operating altitude V Sustainability compliance V Weight & dimensions Fax delayed sending PCL Sc, PCL 6, PCL XL, PCLm, PDF, PostScript 3, XPS Post Script 3, XPS Post Script 3, XPS Post Script 3, XPS Nouther of origin Nouth & output capacity Neight & output capacity Package depth Package depth Package depth Package depth Package weight Total number of input trays 250 sheets Paper tray 1 input capacity Nulti-Purpose tray Post Script 3, SPS Nulti-Purpose tray Post Script 3, SPS Nouth Script 3, SPS Post Script 3, SPS Packaging content Cartridge(s) included Post Spon pages Included cartridge capacity (MXX) Post Spon pages Included cartridge capacity (MXX) Post Spon pages	'		Operational conditions	
Speed dialling Fex forwarding Fex forwarding Fex delayed sending Features Recommended duty cycle Maximum duty cycle* 10000 pages per month Duplex functions * Copy, Fax, Print, Scan Digital sender Ink tank system Number of print cartridges * Printing colours * Black, Cyan, Magenta, Yellow ProstScript 3, XPS Country of origin Replacement cartridges TK-5370 Input & output capacity Total number of input trays * Total number of input trays * Total output capacity Total output capacity Total output capacity Nulti-Purpose tray Negle description language Textory of pages per month Depth Packaging content Cartridge(s) included Cartridge capacity (ISM) Sustainability certificates Sustainability certificates Sustainability certificates Blue Angel, ENERGY STAR, EPEAT Gold Weight & dimensions Wietham Height Width 480 mm Popth Height Weight We	•		Operating relative humidity (H-H)	10 - 80%
Fax forwarding	ū	•	• • • • • • • • • • • • • • • • • • • •	-20 - 40 °C
Features Recommended duty cycle 1000 - 3500 pages per month 20000 pages per month 30000 pages per month 3000 pages per month 30000		•		
Features Recommended duty cycle 1000 - 3500 pages per month Maximum duty cycle 100000 pages per month Duplex functions 100000 pages per month Digital sender Name of print cartridges 1	Fax forwarding	✓	•	
Recommended duty cycle 1000 - 3500 pages per month Maximum duty cycle * 100000 pages per month Copy, Fax, Print, Scan Uplex functions * Copy, Fax, Print, Scan Uplex functions * Veight & dimensions Uplex functions * Veight & dimensions Uplex functions * Veight & dimensions Veight & dime	Fax delayed sending	✓	Operating altitude	0 - 3500 m
Maximum duty cycle * 100000 pages per month Duplex functions * Copy, Fax, Print, Scan Digital sender Ink tank system Number of print cartridges * 4 Printing colours * Black, Cyan, Magenta, Yellow Page description languages Country of origin Replacement cartridges TK-5370 Input & output capacity Total number of input trays * 2 Total input capacity * Total output capacity * Total output capacity * Pager tray 1 input capacity Multi-Purpose tray Inouton 100000 pages per month Sustainability certificates Weight & dimensions Width A80 mm A80 mm Poepth 577.5 mm Height 575 mm Weight 90 yeight 9	Features		Sustainability	
Maximum duty cycle * Duplex functions * Copy, Fax, Print, ScanSustainability certificatesBlue Angel, ENERGY STAR, EPEAT GoldDigital senderVWeight & dimensionsInk tank systemXWidth480 mmNumber of print cartridges *4Depth577.5 mmPrinting colours *Black, Cyan, Magenta, YellowHeight575 mmPage description languagesPCL 5c, PCL 6, PCL XL, PCLm, PDF, PostScript 3, XPSWeight39 kgCountry of originVietnamPackaging dataReplacement cartridgesTK-5370Package width623 mmInput & output capacity728 mmTotal number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity250 sheetsPackaging contentMulti-Purpose tray250 sheetsCartridge (s) includedVMulti-Purpose trayIncluded cartridge capacity (black) Included cartridge capacity (Dlack)3500 pages	Recommended duty cycle	1000 - 3500 pages per month	Sustainability compliance	✓
Duplex functions * Copy, Fax, Print, Scan Digital sender Ink tank system Number of print cartridges * 4 Printing colours * Black, Cyan, Magenta, Yellow Page description languages Country of origin Replacement cartridges TK-5370 Input & output capacity Total number of input trays * 2 Total input capacity * 250 sheets Paper tray 1 input capacity Multi-Purpose tray Weight & dimensions Width Weight & dimensions Width 480 mm Height 577.5 mm Weight 575 mm Weight Weight 9 Ackaging data Packaging data Package width Package width Package depth Package depth Package height 728 mm 789 mm Total output capacity * 51 kg Total output capacity * 250 sheets Paper tray 1 input capacity Multi-Purpose tray Packaging content Cartridge (apacity (black)) Included cartridge capacity (black) Packages Packaging content Cartridge capacity (CMX) Packages Packaging content Cartridge capacity (CMX) Packages Packaging content Cartridge capacity (CMX) Packages Packaging capacity (CMX) Pack	, ,	· - ·	Sustainability cortificator	Blue Angel, ENERGY STAR, EPEAT
Ink tank system X Width 480 mm Number of print cartridges * 4 Depth 577.5 mm Printing colours * Black, Cyan, Magenta, Yellow Height 575 mm Page description languages PCL 5c, PCL 6, PCL XL, PCLm, PDF, PostScript 3, XPS Country of origin Vietnam Package width Package width Package depth 728 mm Input & output capacity Package weight 789 mm Total number of input trays * 2 Total input capacity * 350 sheets Total output capacity * 250 sheets Packaging content Cartridge(s) included cartridge capacity (black) 3500 pages Included cartridge capacity (CMX) 2500 pages		Copy, Fax, Print, Scan	Sustainability Certificates	Gold
Number of print cartridges * 4 Depth 577.5 mm Printing colours * Black, Cyan, Magenta, Yellow Height 575 mm Page description languages PCL 5c, PCL 6, PCL XL, PCLm, PDF, PostScript 3, XPS Country of origin Vietnam Package width Package width Package depth 728 mm Package depth 789 mm Total number of input trays * 2 Package weight 51 kg Total input capacity * 350 sheets Total output capacity * 250 sheets Pager tray 1 input capacity	Digital sender	✓	Weight & dimensions	
Number of print cartridges * 4 Depth 577.5 mm Printing colours * Black, Cyan, Magenta, Yellow Height 575 mm Page description languages PCL 5c, PCL 6, PCL XL, PCLm, PDF, PostScript 3, XPS Country of origin Vietnam Package width Package width Package depth 728 mm Package depth 789 mm Total number of input trays * 2 Package weight 51 kg Total input capacity * 350 sheets Total output capacity * 250 sheets Pager tray 1 input capacity	Ink tank system	×	Width	480 mm
Printing colours * Page description languages PCL 5c, PCL 6, PCL XL, PCLm, PDF, PostScript 3, XPS Country of origin Replacement cartridges TK-5370 Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Total output capacity * Total output capacity * Package width Package weight Total output capacity * Packaging content Cartridge(s) included Included cartridge capacity (CMX) P500 pages	•		Depth	
Page description languages PostScript 3, XPS Country of origin Replacement cartridges TK-5370 Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Package weight Package weight Package weight Package weight Total output capacity * Total output capacity * Packaging content Cartridge(s) included Included cartridge capacity (DMX) Total puppose tray Packaging content Cartridge capacity (DMX) Total puppose tray Packaging content Cartridge capacity (CMX) Total puppose tray Package weight Total puppose tray Total puppose tray Package depth Total puppose tray Package depth Total puppose tray Package depth Total puppose tray Package weight Total puppose tray Total puppose tray Total puppose tray Package weight Total puppose tray Total puppose tray Total puppose tray Total puppose tray Package weight Total puppose tray Total p	,	Black, Cyan, Magenta, Yellow	Height	575 mm
Country of origin Replacement cartridges TK-5370 Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Package weight Total output capacity * Package weight Package weight Package weight Package weight Following content Cartridge(s) included Included cartridge capacity (DMX) Total provided cartridge capacity (CMX) Total output capacity * Packaging data Package width Package width Package weight Package weight Following content Cartridge(s) included Included cartridge capacity (black) Total output capacity Packaging content Cartridge capacity (DMX) Total output capacity Packaging content Cartridge capacity (CMX) Total output capacity (CMX) Package weight Package	Page description languages		Weight	39 kg
Country of origin Replacement cartridges TK-5370 Package width Package depth Package depth Package height Package height Package weight Total number of input trays * Total input capacity * Total output capacity * Total output capacity * Packaging content Cartridge(s) included Multi-Purpose tray Package width Package width Package weight Package meight Package weight Fackaging content Cartridge(s) included Included cartridge capacity (black) Included cartridge capacity (CMX) Package width Package width Package width Package width Package width Package weight Package we		·	Packaging data	
Input & output capacity Total number of input trays * 2 Total input capacity * 350 sheets Total output capacity * 250 sheets Paper tray 1 input capacity	· ·			623 mm
Input & output capacity Package height 789 mm Total number of input trays * 2 Package weight 51 kg Total input capacity * 350 sheets Packaging content Total output capacity * 250 sheets Cartridge(s) included ✓ Paper tray 1 input capacity 250 sheets Included cartridge capacity (black) 3500 pages Multi-Purpose tray Included cartridge capacity (CMY) 2500 pages		IK-33/U	-	
Total number of input trays * 2 Package weight 51 kg Total input capacity * 350 sheets Total output capacity * 250 sheets Paper tray 1 input capacity Multi-Purpose tray ✓ Included cartridge capacity (CMX) 2500 pages	Input & output capacity			789 mm
Total output capacity * 250 sheets Paper tray 1 input capacity Multi-Purpose tray Z50 sheets Cartridge(s) included Included cartridge capacity (black) Included cartridge capacity (CMY) Z500 pages	Total number of input trays *	2		51 kg
Total output capacity * 250 sheets Paper tray 1 input capacity 250 sheets Multi-Purpose tray Included cartridge capacity (black) 3500 pages		350 sheets	Packaging content	
Multi-Purpose tray Included cartridge capacity (black) 3500 pages Included cartridge capacity (CMY) 2500 pages				1
Included cartridge capacity (CMV) 2500 pages			-	
Multi-Purpose tray input capacity 100 sheets				, -
	Multi-Purpose tray input capacity	100 sheets		

Input & output capacity		Packaging content	
Maximum number of input trays	5	Imaging unit included Cables included	✓ AC
		Technical details	
		Compliance certificates	CE, REACH, RoHS, cTUVus, WEEE





632983071847

0632983071847

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.