KYOCERA ECOSYS PA4000cx Väri 1200 x 1200 DPI A4

**Tuotemerkki :** KYOCERA   **Tuoteperhe:** ECOSYS   **Tuotekoodi:** 1102Z03NL0

Tuotteen nimi : ECOSYS PA4000cx

KYOCERA ECOSYS PA4000cx. Tulostustekniikka: Laser, Väri. Värikasettien määrä: 4, Suurin toimintajakso: 100000 sivua kuukaudessa. Suurin resoluutio: 1200 x 1200 DPI. Suurin ISO A-luokan paperikoko: A4. Tulostusnopeus (musta, normaalilaatu, A4/US Letter): 40 ppm, Kaksipuolinen tulostus. Näyttö: LCD, Tuotteen väri: musta, Valkoinen

Printing

Duplex printing mode	Auto
Print speed (colour, normal quality, A4/US Letter)	40 ppm
Colour *	✔
Print technology *	Laser
Duplex printing *	✔
Maximum resolution *	1200 x 1200 DPI
Print speed (black, normal quality, A4/US Letter) *	40 ppm
Duplex print speed (black, normal quality, A4/US Letter)	33 ppm
Duplex print speed (colour, normal quality, A4/US Letter)	33 ppm
Warm-up time	23 s
Time to first page (black, normal)	5.4 s
Time to first page (colour, normal)	7 s
Economical printing	✔

Features

Maximum duty cycle *	100000 pages per month
Recommended duty cycle	1000 - 5000 pages per month
Printing colours *	Black, Cyan, Magenta, Yellow
Number of print cartridges *	4
Page description languages *	PCL 6, PCLm, PDF, PostScript 3, URF, XPS
Introduction month	july
Introduction year	2023
Country of origin	Vietnam
Replacement cartridges	TK-5380

Network

Near Field Communication (NFC)	✘
Bluetooth	✘
Security algorithms	SNMPv3, TLS
Mobile printing technologies	Apple AirPrint, Kyocera Mobile Print, Mopria Print Service

Performance

Internal memory *	1024 MB
Maximum internal memory	3072 MB
Memory slots	1
Built-in processor	✔
Sound pressure level (printing)	53 dB
Sound power level (standby)	30 dB

Design

Market positioning *	Business
Product colour *	Black, White
Built-in display *	✔
Display	LCD
Colour display	✔
Control type	Buttons

Power

Power consumption (printing) *	466 W
Power consumption (ready)	56 W
AC input voltage	220 - 240 V
AC input frequency	50/60 Hz

System requirements

Windows operating systems supported	✔

Input & output capacity

Total number of input trays *	2
Total input capacity *	650 sheets
Total output capacity *	250 sheets
Paper tray 1 input capacity	550 sheets
Multi-Purpose tray	✔
Multi-Purpose tray input capacity	100 sheets
Maximum number of input trays	5
Maximum input capacity	2300 sheets
Maximum output capacity	250 sheets

Paper handling

Maximum ISO A-series paper size *	A4
Paper tray media types *	Banner, Labels, Letterhead, Plain paper, Pre-printed
ISO A-series sizes (A0...A9) *	A4, A5, A6
ISO B-series sizes (B0...B9)	B5, B6
Non-ISO print media sizes	Folio, Legal, Letter
Paper tray media weight	60 - 220 g/m²

Ports & interfaces

Direct printing *	✔
USB port *	✔
USB 2.0 ports quantity	1
Optional connectivity	Ethernet, Wireless LAN

Network

Wi-Fi *	✘
Ethernet LAN *	✔
Cabling technology	10/100/1000Base-T(X)
Ethernet LAN data rates	10,100,1000 Mbit/s

System requirements

Mac operating systems supported	Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Linux operating systems supported	✔

Operational conditions

Operating temperature (T-T)	10 - 32.5 °C
Storage temperature (T-T)	-20 - 40 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	10 - 90%
Operating altitude	0 - 3500 m

Sustainability

Sustainability compliance	✔
Sustainability certificates	Blue Angel, ENERGY STAR, EPEAT Gold

Weight & dimensions

Width	394 mm
Depth	533 mm
Height	455 mm
Weight	34 kg

Packaging data

Package width	702 mm
Package depth	567 mm
Package height	561 mm
Package weight	41 kg

Packaging content

Cartridge(s) included	✔
Included cartridge capacity (black)	6000 pages
Included cartridge capacity (CMY)	5000 pages
Cables included	AC

Technical details

Compliance certificates	REACH, cTUVus, WEEE

0632983071755

632983071755