

## Targus DOCK460EUZ laptop dock/port replicator Wired USB4 Black

**Brand :** Targus

**Product code:** DOCK460EUZ

**Product name :** DOCK460EUZ



- Supports up to single 8K @60Hz, dual 8K@30Hz, or triple 4K@60Hz monitors with a USB4 host via one HDMI 2.1 and two DisplayPort™ 1.4 ports
  - Power Delivery 3.0 up to 100W for USB-C® hosts
  - 1x USB 3.2 Gen 2 Type-C port (10Gbps and powered to 7.5W)
  - 2x USB 3.2 Gen 2 Type-A ports (10Gbps), 1 fast charging
  - 2x USB 3.2 Gen 1 Type-A ports (5Gbps)
  - 2.5G Ethernet port
  - 1x 3.5mm combo Audio In/Out port for mics, speakers, and headphones
  - Integrated lock slot accommodates standard security locks to safeguard equipment
  - 1m screw-in USB4 host connector supports 40Gbps USB4 and is Thunderbolt™ 4 and 3 compatible
  - Compatible with Targus VESA® Mounting Bracket (ACX003GLZ, sold separately)
  - Works with Windows®, macOS®, Android™, Chrome OS™, and Ubuntu®
- USB4, Triple Video Docking Station, 100W, USB-C, 2.5G Ethernet, black

Ports & interfaces		Performance	
Connectivity technology *	Wired	Number of displays supported	3
Host interface *	USB4	Cable lock slot	✓
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2	Cable lock slot type	Kensington
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2	Product colour *	Black
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1	Plug and Play	✓
USB4 ports quantity	1	Country of origin	Taiwan
USB Power Delivery (USB PD)	✓	<b>Power</b>	
USB Power Delivery revision	3.0	Power source type	DC
USB Power Delivery up to	100 W	<b>Software</b>	
HDMI ports quantity *	1	Windows operating systems supported	✓
HDMI version	2.1	Mac operating systems supported	✓
DisplayPorts quantity	2	Linux operating systems supported	✓
DisplayPort version	1.4	Mobile operating systems supported	iPadOS
Microphone in *	✓	Other operating systems supported	ChromeOS
Combo headphone/mic port	✓	<b>Weight &amp; dimensions</b>	
Headphone outputs *	1	Width	92 mm
Headphone connectivity	3.5 mm	Depth	195 mm
DC-in jack	✓	Height	37 mm
<b>Network</b>		Weight	1.35 kg
Ethernet LAN *	✓	<b>Packaging data</b>	
Ethernet LAN (RJ-45) ports	1	Quantity per pack	1 pc(s)
Ethernet LAN data rates	2500 Mbit/s	<b>Packaging content</b>	
<b>Performance</b>		Cables included	USB Type-C
Card reader integrated *	✗	AC adapter included	✓
Data transfer rate	40 Gbit/s	Quick start guide	✓

**Performance**

HD type

8K Ultra HD



5051794042702

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-DEC-2024. Prints or copies of Information are only valid on the printed Publication date