

DELL P7524QT Interaktiivinen litteä paneeli 189,3 cm (74.5") LCD 350 cd/m² 4K Ultra HD musta Kosketusnäyttö

Tuotemerkki : DELL Tuotekoodi: DELL-P7524QT

Tuotteen nimi: P7524QT

DELL P7524QT. Tuotteen muotoilu: Interaktiivinen litteä paneeli. Näytön halkaisija: 189,3 cm (74.5"), Näytön teknologia: LCD, Näytön erottelutarkkuus: 3840 x 2160 pikseliä, Näytön kirkkaus: 350 cd/m², HD-

tyyppi: 4K Ultra HD, Kosketusnäyttö. Tuotteen väri: musta





Display		Performance	
Panel type	IPS	Purpose *	Corporate
LED backlight	✓	On Screen Display (OSD)	✓
Display diagonal *	189.3 cm (74.5")	HID support	1
Display technology *	LCD	Power	
Display resolution *	3840 x 2160 pixels	Power consumption (typical) *	140 W
Display brightness *	350 cd/m ²	Power consumption (standby) *	0.5 W
HD type *	4K Ultra HD	Power consumption (off)	0.3 W
Touchscreen *	✓	Power consumption (max)	290 W
Number of simultaneous touchpoints	20	Energy efficiency class (SDR)	G G
Multi-touch	✓	Energy efficiency class (HDR)	Not available
Native aspect ratio	16:9	Energy consumption (SDR) per 1000 hours	140 kWh
Response time	8 ms	AC input voltage	100 - 240 V
Contrast ratio (typical)	1200:1	AC input frequency	50/60 Hz
Viewing angle, horizontal	178°	Heat dissipation	477.7 BTU/h
Viewing angle, vertical	178°	Energy efficiency scale	A to G
Display number of colours	1.07 billion colours	Computer system	
Pixel pitch	0.429 x 0.429 mm	• •	
Display diagonal (metric)	189.273 cm	Windows operating systems supported	Windows 7 Professional, Windows 7 Ultimate, Windows 8, Windows 8.1
Horizontal scan range Vertical scan range	30 - 140 kHz 24 - 75 Hz	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160	Linux operating systems supported	✓
		Weight & dimensions	
		Display width	1735 mm
Supported video modes	480p, 576p, 720p, 1080i, 1080p, 2160p	Display depth	79.1 mm
		Display height	1017.4 mm
Hardness	9H	Display weight	64 kg

Display Fackaging data 7.6 kg RGB colour space MTSC Packaging content Colour gamut 72% Remote control included ✓ Ports & Interfaces Stylus pen ✓ HDMI ports quantity* 3 Acabes included AC, DisplayPort, HDMI, USB, VGA DVI port* X Operational conditions AC, DisplayPort, HDMI, USB, VGA VGA (D-Sub) input ports 1 Operational conditions 0.0 USB port* ✓ Operating temperature (T-T) 0.0 80% USB port squantity 7 Storage relative humidity (H+H) 0.0 80% USB ports quantity 7 Storage relative humidity (H+H) 5.0 90% USB ports quantity 7 Storage relative humidity (H+H) 5.0 90% USB ports quantity 7 Features 0.0 900 m USB 2.0 Type-B ports quantity 8 Features 0.0 900 m USB 2.2 Gen 1 (3.1 Gen 1) Type-A 6 Features 0.0 900 m USB 2.2 Gen 1 (3.1 Gen 1) Type-A 6 Features 0.0 900 m US				
RGB colour space NTSC Colour gamut Packaging content Colour gamut 72% Remote control included ✓ Ports & Interfaces Stylus pen ✓ HDMI ports quantity* 3 Number of stylus pens 2 HDMI version 2.0 Cables included AC, DisplayPort, HDMI, USB, VGA VGA (D-Sub) input ports 1 Operational conditions VSB ports quantity* 1 Operating relative humidity (HH) 10 - 80% USB ports quantity 7 Storage temperature (T-T) 20 - 60 °C USB ports quantity 7 Storage temperature (T-T) 20 - 60 °C USB connector type Mini-USB A Operating altitude 0 - 200 °C USB 2.0 Trype-B ports quantity 3 Features 0 - 2000 °C USB 2.2 Cen 1 (3.1 Gen 1) Type-A Persisted Versisted deal USB 179c-C DisplayPort Alternate Mode Features Resistantification (max) 989.52 BTU/h USB 179c-C DisplayPort Alternate Mode Yes Storage relative humidity (HH) Are Report No. Protect	Display		Packaging data	
Colour gamuit 72% Packaging Content Ports & Interfaces Remote control included 4 HDMI ports quantity* 3 Number of stylus pens 2 DVI port* X Operational Conditions 4C, DisplayPort, HDMI, USB, VGA DVI port* X Operational Conditions VCA (C5-bub) input ports 1 0 (C7-bub) conditions VCA (C5-bub) conditions VCA			Package weight	76.6 kg
Ports & interfaces Remote control included ✓ HDMI ports quantity* 3 Number of stylus pens 2 HDMI version 2.0 Cables included AC, DisplayPort, HDMI, USB, VGA DVI port* X Operational conditions VGA (D-Sub) input ports 1 0perating temperature (T-T) 0 - 40 °C USB ports quantity 1 0perating relative humidity (H-H) 10 - 80% USB ports quantity 7 Storage temperature (T-T) -20 - 60 °C USB connector type Mini-USB A Operating altitude 0 - 5000 m USB 2.0 Type-B ports quantity 3 Peatures 0 - 5000 m USB 2.0 Type-B ports quantity 4 Features 0 - 5000 m USB 2.0 Type-B ports quantity 4 Features 0 - 5000 m USB 2.0 Type-B ports quantity 7 Features 0 - 5000 m USB 2.0 Type-B ports quantity 7 Features 0 - 5000 m USB 2.0 Type-B ports quantity 7 Features 1 - 12 m USB 2.0 Type-B ports quantity 7 Technical d	·		Packaging content	
No	Colour gamut	72%	Remote control included	✓
HOMI ports quantity* 3 Number of stylus pens 2 HOMI version 2.0 Cables included AC, DisplayPort, HDMI, USB, VGA DVI port* X Operational conditions VGA (D-Sub) input ports 1 Operating temperature (T-T) 0-40 °C USB ports quantity 7 Storage temperature (T-T) 20 - 60 °C USB ports quantity 7 Storage temperature (T-T) 20 - 60 °C USB connector type Mini-USB a Non-operating altitude 0 - 5000 m USB connector type Mini-USB a Non-operating altitude 0 - 5000 m USB 2.0 Type-B ports quantity 3 Features - 90% USB 2.3 Ceen 1 (3.1 Gen 1) Type-A USB and US	Ports & interfaces		Stylus pen	1
HOMI version 2.0 Cables included AC, DisplayPort, HDMI, USB, VGA DVI port * X Operational conditions V VGA (D-Sub) input ports 1 Operating relative (T-T) 0 -40 °C USB port * ✓ Operating relative humidity (H-H) 10 - 80% USB ports quantity 7 Storage temperature (T-T) -20 - 60 °C USB version 2.0/3.2 Gen 1 (3.1 Gen 1) Operating altitude 0 - 5000 m USB 2.0 Type-B ports quantity 3 Features 0 - 12192 m USB 2.0 Type-B ports quantity 3 Features	HDMI ports quantity *	3	• •	2
VGA (D-Sub) input ports 1 DisplayPorts quantity* 1 Operating temperature (T-T) 0-40 °C USB port* V Operating relative humidity (H-H) 10-80% USB ports quantity 7 Storage temperature (T-T) -20-60 °C USB version 2.0/3.2 Gen 1 (3.1 Gen 1) Operating altitude 0-5000 m USB 2.0 Type-B ports quantity 3 Peatures 0-12192 m USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity 4 Features USB Type-C DisplayPort Alternate Mode ** Technical details Wi-Fi* X Sustainability certificates ENERGY STAR Wi-Fi* X Doesn't contain Arsenic, Mercury, PVC/BFR Rudio (L/R) in 1 Compliance certificates RoHS RS-222 interface * Quick start guide * Built-in speaker(s)* * LED indicators * Built-in speaker(s)* * LED indicators * RWF sted power 40 W Viewable size diagonal 18.9 cm Power subject design* <td< td=""><td>HDMI version</td><td>2.0</td><td>• •</td><td>AC, DisplayPort, HDMI, USB, VGA</td></td<>	HDMI version	2.0	• •	AC, DisplayPort, HDMI, USB, VGA
VGA (US-bul) input ports 1 USB port * / Operating telative humidity (H-H) 10 - 80% USB ports quantity 7 Storage temperature (T-T) -20 - 60 °C USB version 2.0/3.2 Gen 1 (3.1 Gen 1) Storage relative humidity (H-H) 5 - 90% USB connector type Mini-USB A Non-operating altitude 0 - 5000 m USB 2.0 Type-B ports quantity 4 Features USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity 4 Features USB Type-C DisplayPort Alternate Mode * Features USB Type-C DisplayPort Alternate Mode * Sustainability compliance * Wi-Fi* X Desent contain Arsenic, Mercury, PVC/BFR Audio (L/R) in 1 Sustainability certificates ENERGY STAR Audio (L/R) out 1 Other features RS-232 interface * Quick start guide * Audio * * Built-in speaker(s)* * LED indicators * Number of built-in speakers 2 On/off switch * <	DVI port *	×	Operational conditions	
Display-Fort Squantity	VGA (D-Sub) input ports			0.40 °C
USB ports quantity 7 Storage temperature (T-T) -20 - 60 °C USB ports quantity 2.0/3.2 Gen 1 (3.1 Gen 1) Storage relative humidity (H-H) 5 - 90% USB connector type Mini-USB A Non-operating altitude 0 - 5000 m USB 2.0 Type-B ports quantity 3 Features USB 1.3 Gen 1 (3.1 Gen 1) Type-A ports quantity 4 Features USB Type-C DisplayPort Alternate Mode Features Heat dissipation (max) 989.52 BTU/h Ethernet LAN * * Sustainability compliance * Ethernet LAN (RJ-45) ports 1 Sustainability certificates ENERGY STAR Wi-Fi * X Dosen't contain Arsenic, Mercury, PVC/BFR Audio (L/R) in 1 Compliance certificates ROHS Audio (L/R) out 1 Other features RS-232 interface * Quick start guide * Audio * * LED indicators * Built-in speaker(s) * * LED indicators * Number of built-in speakers 40 W Viewable size, king daponal </td <td></td> <td>1</td> <td>, -</td> <td></td>		1	, -	
USB ports quantity 7 USB version 2.0/3.2 Gen I (3.1 Gen 1) USB connector type Mini-USB A Von-operating altitude 0-5000 m VSB 2.0 Type-B ports quantity 3 USB 3.2 Gen I (3.1 Gen 1) Type-A the dissipation (max) 989.52 BTU/h USB Type-C DisplayPort Alternate Mode Wode Volume I AN (R)-45) ports 1 Ethernet LAN * UFB - X Ethernet LAN (R)-45) ports 1 Wi-Fi * Audio (L/R) in 1 Audio (L/R) in 1 Audio (L/R) in 1 Built-in speaker(s) * VINDER SP-232 interface Volume	USB port *			
USB connector type Wini-USB A Mini-USB A Metal dissipation (max) Metal details Ethernet LAN * Ethernet LAN (R)-45) ports I Ethernet LAN (R)-45) ports I Ethernet LAN (R)-45 ports I Etherne	USB ports quantity	7	- '	
USB 2.0 Type-B ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity USB 7.0 Type-B ports quantity USB 7.0 Type-B ports quantity USB 7.0 Type-C DisplayPort Alternate Mode Ethernet LAN* Ethernet LAN (R)-45) ports 1			• • • • • • • • • • • • • • • • • • • •	
Features USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity 4 Heat dissipation (max) 989.52 BTU/h USB Type-C DisplayPort Alternate Mode * Technical details Ethernet LAN* * Sustainability compliance * Ethernet LAN (RJ-45) ports 1 Sustainability certificates ENERGY STAR Wi-Fi* X Doesn't contain Arsenic, Mercury, PVC/BFR Audio (L/R) in 1 Other features ROHS Audio (L/R) out 1 Other features * S-232 interface * Quick start guide * RS-232 interface * Quick start guide * Buill-in speaker(s)* * Cable lock slot * Number of built-in speakers 2 On/off switch * RMS rated power 40 W Viewable size, horizontal 165 cm Product design* Interactive flat panel Viewable size, vertical 92.8 cm Placement supported* Indoor Power supply type Internal Product colour* Black Cable management * * Screen s	• •		· -	
Ports quantity USB Type-C DisplayPort Alternate Mode Fethernet LAN * Ethernet LAN (RJ-45) ports 1 Sustainability compliance Ethernet LAN (RJ-45) ports 1 Sustainability certificates ENERGY STAR Wi-Fi * X Doesn't contain Arsenic, Mercury, PVC/BFR Audio (L/R) in 1 Audio (L/R) out 1 Audio (L/R) out RS-232 interface V Quick start guide V Audio LED indicators Viewable size, horizontal Design Product design * Interactive flat panel Placement supported * Indoor Product colour * Black Screen shape Flat Response time 400 x 400 mm Bezel width (bottom) 4.28 cm Heat dissipation (max) 989.52 BTU/h Heat dissipation (max) 989.52 BTU/h Heat dissipation (max) 989.52 BTU/h Pethical details Frechnical details Flethnical details Finath Arsenic Mercury, PVC/BFR Audio (L/R) in Arsenic, Mercury, PVC/BFR Arsenic, Mercury,	,, , , ,	3	Features	
USB Type-C DisplayPort Alternate Mode * Technical details Ethernet LAN* * Sustainability compliance * Ethernet LAN (Rj-45) ports 1 Sustainability certificates ENERGY STAR Wi-Fi* * Doesn't contain Arsenic, Mercury, PVC/BFR Audio (L/R) in 1 Compliance certificates RoHS Audio (L/R) out 1 Other features RS-232 interface * Quick start guide * Audio * Cable lock slot * Built-in speaker(s)* * Cable lock slot * Number of built-in speakers 2 On/off switch * RMS rated power 40 W Viewable size diagonal 18.9 cm Product design* Interactive flat panel Viewable size, horizontal 165 cm Product design* Indoor Power supply type Internal Product colour* Black Cable management * VESA mounting* * Plug and Play * VESA mounting interface 400 x 400 mm Hug and Play * Bezel width (bottom) 4.67 cm Bezel width (totom) 4.27 cm Bezel width (totop) 4.28 cm		4		989.52 BTU/h
Ethernet LAN (RJ-45) ports 1 Sustainability certificates NERGY STAR Wi-Fi* X Doesn't contain Arsenic, Mercury, PVC/BFR Audio (L/R) in 1 Compliance certificates ROHS Audio (L/R) out 1 Other features RS-232 interface Y Quick start guide Y Audio Built-in speaker(s)* Y Cable lock slot Y Built-in speaker(s)* Y LED indicators Y RMS rated power 40 W Viewable size diagonal 18.9 cm Posign Viewable size, horizontal 165 cm Product design * Interactive flat panel Placement supported * Indoor Power supply type Internal Product colour * Black Cable management Y Screen shape Flat Response time 8 s VESA mounting * Y Plug and Play Y Panel mounting interface 400 x 400 mm Bezel width (bottom) 4.27 cm Bezel width (top) 4.28 cm		✓		
Wi-Fi * X Doesn't contain Arsenic, Mercury, PVC/BFR Audio (L/R) in 1 Compliance certificates RoHS Audio (L/R) out 1 Other features RS-232 interface	Ethernet LAN *	✓	Sustainability compliance	✓
Audio (L/R) in 1 Audio (L/R) out 1 RS-232 interface	Ethernet LAN (RJ-45) ports	1	Sustainability certificates	ENERGY STAR
Audio (L/R) out 1 Quick start guide RS-232 interface Audio	Wi-Fi *	×	Doesn't contain	Arsenic, Mercury, PVC/BFR
RS-232 interface Audio Cable lock slot Cable indicators Cable managenal Cable managenal Cable managenant Cable	Audio (L/R) in	1	Compliance certificates	RoHS
Audio Audio Cable lock slot LED indicators LED indicators Number of built-in speakers 2 On/off switch Viewable size diagonal Product design * Interactive flat panel Placement supported * Indoor Product colour * Black Screen shape Viewable size, vertical Placement supported * Indoor Product colour * Black Screen shape Viewable size, vertical Power supply type Internal Cable management Viewable size, vertical Power supply type Internal Cable management Viewable size, vertical Power supply type Internal Cable management Viewable size, vertical Power supply type Internal Product colour * S S VESA mounting * V Viewable size, vertical Power supply type Internal Viewable size diagonal Viewable size	Audio (L/R) out	1	Other features	
AudioCable lock slot✓Built-in speaker(s) *✓LED indicators✓Number of built-in speakers2On/off switch✓RMS rated power40 WViewable size diagonal18.9 cmDesignViewable size, horizontal165 cmProduct design *Interactive flat panelViewable size, vertical92.8 cmPlacement supported *IndoorPower supply typeInternalProduct colour *BlackCable management✓Screen shapeFlatResponse time8 sVESA mounting *✓Plug and Play✓Panel mounting interface400 x 400 mmBezel width (bottom)4.67 cmBezel width (side)4.27 cmBezel width (top)4.28 cm	RS-232 interface	✓	Quick start guide	√
Built-in speaker(s) *	Audio			
Number of built-in speakers2On/off switch✓RMS rated power40 WViewable size diagonal18.9 cmDesignViewable size, horizontal165 cmProduct design *Interactive flat panelViewable size, vertical92.8 cmPlacement supported *IndoorPower supply typeInternalProduct colour *BlackCable management✓Screen shapeFlatResponse time8 sVESA mounting *✓Plug and Play✓Panel mounting interface400 x 400 mmBezel width (bottom)4.67 cmBezel width (side)4.27 cmBezel width (top)4.28 cm	Ruilt-in speaker(s) *	1		
RMS rated power 40 W Viewable size diagonal 18.9 cm Pesign Viewable size, horizontal 165 cm Product design * Interactive flat panel Placement supported * Indoor Power supply type Internal Product colour * Black Cable management Screen shape Flat Response time 8 s VESA mounting * ✓ Plug and Play ✓ Panel mounting interface 400 x 400 mm Bezel width (bottom) 4.67 cm Bezel width (side) 4.27 cm Bezel width (top) 4.28 cm	•			
New State and SeriesDesignViewable size, horizontal165 cmProduct design *Interactive flat panelViewable size, vertical92.8 cmPlacement supported *IndoorPower supply typeInternalProduct colour *BlackCable management✓Screen shapeFlatResponse time8 sVESA mounting *✓Plug and Play✓Panel mounting interface400 x 400 mmBezel width (bottom)4.67 cmBezel width (side)4.27 cmBezel width (top)4.28 cm	•		·	
Product design * Interactive flat panel Placement supported * Indoor Power supply type Internal Placement supported * Black Cable management ✓ Screen shape Flat Response time 8 s S VESA mounting * ✓ Plug and Play ✓ Panel mounting interface 400 x 400 mm Bezel width (bottom) 4.67 cm Bezel width (top) 4.28 cm	·		· ·	
Placement supported * Indoor Power supply type Internal Product colour * Black Cable management ✓ Screen shape Flat Response time 8 s VESA mounting * ✓ Panel mounting interface 400 x 400 mm Bezel width (bottom) 4.67 cm Bezel width (side) 4.27 cm Bezel width (top) 4.28 cm			, and the second	
Product colour * Black Cable management ✓ Screen shape Flat Response time 8 s VESA mounting * ✓ Panel mounting interface 400 x 400 mm Bezel width (bottom) 4.67 cm Bezel width (side) 4.27 cm Bezel width (top) 4.28 cm	•	•		
Screen shape Flat Response time Plug and Play Panel mounting interface 400 x 400 mm Bezel width (bottom) 4.67 cm Bezel width (side) 4.27 cm Bezel width (top) 4.28 cm	• • • • • • • • • • • • • • • • • • • •			/
VESA mounting *			•	8 s
Panel mounting interface 400 x 400 mm Bezel width (bottom) 4.67 cm Bezel width (side) 4.27 cm Bezel width (top) 4.28 cm	·		•	
Bezel width (bottom) 4.67 cm Bezel width (side) 4.27 cm Bezel width (top) 4.28 cm	•		3 ,	
Bezel width (side) 4.27 cm Bezel width (top) 4.28 cm	_			
Bezel width (top) 4.28 cm				
Anti-yidie Scieen	Anti-glare screen	✓		



5397184821558

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.