

DELL P6524QT Interactive flat panel 163.9 cm (64.5") LCD 350 cd/m² 4K Ultra HD Black Touchscreen

Brand : DELL

_ . .

Product code: DELL-P6524QT

Product name : P6524QT

- 64.53" 4K UHD 3840 x 2160, IPS
- 9ms, 16:9, 350cd/m², 1300:1
- USB, HDMI, DisplayPort"
64.53" 4K UHD 3840 x 2160, IPS, 16:9, 350 cd/m² 1.07 Billon, 9 ms, 178°/178°, 1300:1

DELL P6524QT Interactive flat panel 163.9 cm (64.5") LCD 350 cd/m² 4K Ultra HD Black Touchscreen:

Bring the team together, whether they are in the room or remote, with this brilliant 65" 4K UHD large format monitor with 20-point touch, palm-rejection, USB-C connectivity and built-in dual 20W speakers. DELL P6524QT. Product design: Interactive flat panel. Display diagonal: 163.9 cm (64.5"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 350 cd/m², HD type: 4K Ultra HD, Touchscreen. Product colour: Black





PaneltypeIPSBezel width (top)4.47 cmLED backlightAnt-jales creenDisplay diagonalIGODisplay technology *BA0 × 2160 pixelsPurpos *CorporateDisplay technology *350 cd/m2Display technology *At Ultra HDPower consumption (typical **)0.4 WNumber of simultaneous20Power consumption (typical **)0.4 WNumber of simultaneousPower consumption (typical **)0.4 WNumber of simultaneousPower consumption (typical **)0.4 WNuthot of simultaneousPower consumption (typical **)0.4 WNumber of simultaneousPower consumption (typical **)0.4 WNumber of simultaneousPower consumption (typical **)0.4 WNuthot of typical **Power consumption (typical **)0.4 WNithous particity particity particity particity particity particity particity particity particity	Display		Design	
Display diagonal *163.9 cm (64.5*)PerformanceDisplay technology *LCDPurpose *CorporateDisplay technology *3840 x 2160 pixelsOn Screen Display (OSD)Display brightness *350 cd/m²On Screen Display (OSD)Ditype *4K Ultra HDPower101 WTouchscreen *Power consumption (typical) *101 WNumber of simultaneous touchpoints20Power consumption (tandby) *0.4 WNuther of simultaneous touchgoints20Power consumption (max)370 WNative aspect ratio16:9Energy efficiency class (SDR)FResponse time9 msEnergy efficiency class (SDR)Not availableContrast ratio (typical)1300:1Energy efficiency class (HDR)Not availableViewing angle, vertical178°AC input voltage100 + 240 VDisplay diagonal (metric)163.90 cmEnergy efficiency class (HDR)101 kWhDisplay diagonal (metric)163.90 cmEnergy efficiency scaleA to GVertical scan range24 - 75 HzWindows operating systems supportedUltimate, Windows 8, 1Mac OS X 10.01 YoSMIHAR (NGA), 122 x 768 (KGA), 1152 x 864 (XGA+), 1228 x 1202 x 1024 1152 x 266 x 1440, 3840 x 2160Mac operating systems supportedUltimate, Windows 8, 1Display widen ondes%00, 5760, 7200, 1080, 1080 x 200, 1800 x 124 x 768 (KGA), 1152, 2560 x 1440, 3840 x 2160Mac operating systems supportedVieting accession	Panel type	IPS	Bezel width (top)	4.47 cm
Display technology*LCDPerformanceDisplay resolution *3840 x 2160 pixelsPurpose *CorporateDisplay brightness *350 cd/m²On Screen Display (OSD)HD type *4K Ultra HDPower101 WTouchscreen *Power consumption (typical) *101 WNumber of simultaneous touchpoints20Power consumption (tandby)0.4 WNutit-touchPower consumption (toff)0.3 WMulti-touchPower consumption (max)370 WNative aspect ratio16:9Energy efficiency class (SDR)FResponse time9 msEnergy efficiency class (IDR)Not availableContrast ratio (typical)1300:1Energy efficiency class (IDR)Not availableViewing angle, vertical178°AC input requency50/60 HzDisplay number of colours1.07 billion coloursAC input requency50/60 HzVietical scan range30 - 140 kHzComputer systemSupported (KGA), 1224 x 768 (KGA), 1152 x 864 (KGA), 1224 x 768 (KGA), 1152 x 500 x 1440, 3840 x 2160Mac operating systems supported 10.11 El CapitanSupported video modes2160pSiplay width1517.9 mm	LED backlight	1	Anti-glare screen	1
Display resolution3840 x 2160 pixelsPurpose *CorporateDisplay brightness *350 cd/m2On Screen Display (OSD)✓HD type *4K Ultra HDPowerPowerTouchscreen *✓Power consumption (typical) *101 WNumber of simultaneous touchpoints20Power consumption (tstandby) *0.4 WMulti-touch✓Power consumption (tmax)370 WMulti-touch✓Power consumption (max)370 WNative aspect ratio16:9Energy efficiency class (SDR)FResponse time9 msEnergy efficiency class (MDR)Not availableContrast ratio (typical)1300:1Energy consumption (SDR) per 1000101 kWhViewing angle, horizontal178°AC input voltage100 - 240 VDisplay umber of colours1.07 billion coloursAC input voltage100 - 240 VDisplay diagonal (metric)163.906 cmEnergy efficiency scaleA to GHorizontal scan range30 - 140 kHzViewing ongle, social scan rangeViet Ava 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160, 1920 x 1080, 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160Mac operating systems supportedMac operating systems supportedSupported video modes#00, 576p, 720p, 1080, 1080p, 2048 x 1152, 2560 x 1440, 3840 x 2160Jipay width1517.9 mm	Display diagonal *	163.9 cm (64.5")	Performance	
Display resolution*3840 x 2160 pixelsOn Screen Display (OSD)*Display brightness*350 c/m²On Screen Display (OSD)*HD type *4K Ultra HDPower101 WTouchscreen **Power consumption (typical) *0.4 WNumber of simultaneous touchpoints0Power consumption (standby) *0.4 WMulti-touch*Power consumption (standby) *0.4 WMulti-touch*Power consumption (max)370 WNative aspect ratio16:9Energy efficiency class (SDR)FResponse time9 msEnergy efficiency class (HDR)Not availableContrast ratio (typical)1300:1Energy efficiency class (HDR)Not availableViewing angle, horizontal1.78*AC input voltage100 - 240 VDisplay number of colours1.07 billion coloursAC input voltage100 - 240 VDisplay diagonal (metric)163.906 cmEnergy efficiency csaleA to GNerzontal scan range30 - 140 kHzVindows 7 Professional, Windows 7 To Windows 7 Professional, Unidows 8, 1152 x 864 (XGA), 1220 x 400, 800 x 150 x 1864 (XGA), 1220 x 400, 800 x 1520 x 1800 (HD 1080), 2048 x 1152 x 560 x 1440, 3840 x 2160Mac operating systems supportedWindows 7 Nordessional, Windows 8, 10.10 Yosemite, Mac OS X 10.11 El CapitanSupported wideo modes& 40p, 576p, 720p, 1080i, 1080 2160pMac operating systems supportedWindows 1517.9 mm	1 5 55		Purpose *	Corporate
Display orighness*350 cd/m²HD type *4K Ultra HDPowerTouchscreen *·Power consumption (typical) *101 WNumber of simultaneous touchpoints20Power consumption (standby) *0.4 WMulti-touch·Power consumption (max)370 WMulti-touch·Power consumption (max)370 WNative aspect ratio16:9Energy efficiency class (SDR)FResponse time9 msEnergy efficiency class (HDR)Not availableContrast ratio (typical)1300:1Energy efficiency class (HDR)Not availableViewing angle, horizontal178°AC input voltage100 - 240 VViewing angle, vertical1.07 billion coloursAC input voltage100 - 240 VDisplay diagonal (metric)163.906 cmHeat dissipation344.63 BTU/hDisplay diagonal (metric)163.906 cmEnergy efficiency claseAt o GVertical scan range24 - 75 HzWindows 17 Professional, Windows 7.1Vindows 7 Professional, Windows 8.1Mac Os X 10.10 Yosemite, Mac OS X 10.10 Yosemite, Mac OS X 10.11 El CapitanMac Os X 10.10 Yosemite, Mac OS X 10.11 El CapitanSupported video modes480p, 576p, 720p, 1080i, 1080p, 2048 x 1152, 2560 x 1440, 3840 x 2160Jisplay width1517.9 mm	1.2	I	•	•
Touchscreen *Touchscreen *Power consumption (typical) *101 WNumber of simultaneous touchpoints20Power consumption (standby) *0.4 WMulti-touchPower consumption (off)0.3 WMulti-touchPower consumption (max)370 WNative aspect ratio16:9Energy efficiency class (SDR)FResponse time9 msEnergy efficiency class (MDR)Not availableContrast ratio (typical)1300:1Energy consumption (SDR) per 1000101 kWhViewing angle, vertical178 *AC input voltage100 - 240 VDisplay number of colours1.07 billion coloursAC input voltage100 - 240 VDisplay qiagonal (metric)163.906 cmEnergy efficiency scaleA to GHorizontal scan range24 - 75 HzWindows operating systemsWindows 7 Professional, Windows 7Supported graphics resolutions1152 x 864 (XGA+), 1280 x 1024 (XGA), 1280 x 1040, 1280 x 1024, 1152 x 864 (XGA+), 1280 x 1024, 1152 x 864 (XG	, , ,			
Number of simultaneous touchpoints 20 Power consumption (standby)* 0.4 W Power consumption (off) 0.3 W Multi-touch ICPS Consumption (off) 0.3 W Power consumption (max) 370 W Native aspect ratio 16:9 Energy efficiency class (SDR) F Response time 9 ms Energy efficiency class (HDR) Not available Contrast ratio (typical) 1300:1 Energy consumption (SDR) per 1000 Viewing angle, vertical 178° Viewing angle, vertical 178° Viewing angle, vertical 178° Viewing angle, vertical 178° Viewing angle, vertical 10.7 billion colours AC input voltage 100 - 240 V Display number of colours 0.372 x 0.372 mm Heat dissipation 344.63 BTU/h Display diagonal (metric) 163.906 cm Energy efficiency scale A to G Horizontal scan range 24 - 75 Hz 640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1224 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 x 600 (SVGA), 1224 x 768 (XGA), Supported graphics resolutions 480, 576, 720, 1080, 1600 x 1200, 1252 x 0.376, 720, 1080, 1080, 2060 x Supported video modes 480, 576, 720, 1080, 1080, 2060 x Supported video modes 480, 576, 720, 1080, 1080, 2060 x 1152 x 867, 720, 720, 1080, 1080, 2060 x 1152 x 867, 720, 720, 1080, 1080, 720 x 1152 x 1080 x 100, 1080, 2048 x 1152 x 1080 x 100, 1080, 2048 x 1152 x 1080 x 100, 1080, 2048 x 1152 x 1080 x 100, 1080, 1080, 2060 x 1152 x 1080 (FD 1080, 2048 x 1152 x 1080 x 100, 1080, 1080, 1080 x 1152 x 1080 x 100, 1080 x 1152 x 1080 x 1080 x 1152 x 1080 x 1080 x 1152 x 1080 x 1080 x 115	51		Power	
touchpoints20Power consumption (off)0.3 WMulti-touch✓Power consumption (off)0.3 WMulti-touch✓Power consumption (off)370 WNative aspect ratio16:9Energy efficiency class (SDR)FResponse time9 msEnergy efficiency class (SDR)Not availableContrast ratio (typical)1300:1Energy consumption (SDR) per 1000Not availableViewing angle, horizontal178°AC input voltage100 - 240 VViewing angle, vertical1.07 billion coloursAC input voltage50/60 HzDisplay number of colours1.07 billion coloursAC input voltage344.63 BTU/hDisplay diagonal (metric)163.906 cmEnergy efficiency scaleA to GHorizontal scan range24 - 75 HzWindows operating systems 600 (SYGA), 1224 x 768 (XGA), 1220 x 400, 800 x 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1152 x 2560 x 1440, 3840 x 2160Windows and operating systems supportedWindows 8, Windows 8, 1 0.11 El CapitanSupported video modes480p, 576p, 720p, 1080i, 1080 w 2160pMac operating systems supportedWindigenerating widthSupported video modes480p, 576p, 720p, 1080i, 1080 w 2160pMacing systems supportedWindigenerating widthSupported video modes480p, 576p, 720p, 1080i, 1080 w 2160pJispay widthJispay width	Touchscreen *	1	Power consumption (typical) *	101 W
Multi-buch✓Power consumption (bit)0.5 WNative aspect ratio16:9Power consumption (max)370 WNative aspect ratio9 msEnergy efficiency class (SDR)FResponse time9 msEnergy efficiency class (MDR)Not availableContrast ratio (typical)1300:1Energy consumption (SDR) per 1000 hours101 kWhViewing angle, horizontal178°AC input voltage100 - 240 VDisplay number of colours1.07 billion coloursAC input frequency50/60 HzDisplay diagonal (metric)163.906 cmHeat dissipation344.63 BTU/hHorizontal scan range24 - 75 Hz 600 (SVGA), 1224 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 1800, 1600 x 1200, 1152 x 1540 (KGA+), 1280 x 1024, (SXGA), 1280 x 1840, 1280 x 1024, (SXGA), 1280 x 1840, 1600 x 1200, 1152 x 1540 (KGA+), 1280 x 1024, (SXGA), 1280 x 1840, 1600 x 1200, 1152 x 566 x 1440, 3840 x 2100, (SXGA), 1280 x 1840, 1600 x 1200, 1152 x 1640 (HD 1080), 2088 x, 1152 x 566 x 1440, 3840 x 2100, (SXGA), 1280 x 1840, 1600 x 1200, 1152 x 1640 (HD 1080), 2088 x, 1152 x 566 x 1440, 3840 x 2100, (SXGA), 1280 x 1840, 1600 x 1200, 1152 x 1640 (HD 1080), 2088 x, 1152 x 566 x 1440, 3840 x 2100, (SXGA), 1280 x 1840, 1600 x 1200, 1152 x 1640 (HD 1080), 2088 x, 1152 x 1640 (HD 1080), 2088 x, 11		20	Power consumption (standby) *	••••
Native aspect ratio16:9Energy efficiency class (SDR)FResponse time9 msEnergy efficiency class (SDR)FContrast ratio (typical)1300:1Energy efficiency class (HDR)Not availableViewing angle, horizontal178°Energy consumption (SDR) per 1000101 kWhViewing angle, vertical178°AC input voltage100 - 240 VDisplay number of colours1.07 billion coloursAC input voltage100 - 240 VDisplay diagonal (metric)163.906 cmHeat dissipation344.63 BTU/hDisplay diagonal (metric)163.906 cmEnergy efficiency scaleA to GHorizontal scan range30 - 140 kHzComputer systemWindows operating systemsWindows 7 Professional, Windows 7Vertical scan range24 - 75 HzKui A & 80 (VGA), 122 x 468 (XGA+), 1280 x 1024Mac operating systems supportedMac OS X 10.10 Yosemite, Mac OS X 10.11 Vosemite, Mac OS X 10.11 Prosemite, Mac OS X 10.11 Prosemite, Mac OS X 10.11 El CapitanSupported video modes480p, 576p, 720p, 1080i, 1080p, 2160pDisplay width1517.9 mm	•		• • •	
Response time9 msEnergy efficiency class (HDR)Not availableContrast ratio (typical)1300:1Energy consumption (SDR) per 1000 hours101 kWhViewing angle, horizontal178°AC input voltage100 - 240 VDisplay number of colours1.07 billion coloursAC input frequency50/60 HzPixel pitch0.372 x 0.372 mmHeat dissipation344.63 BTU/hDisplay diagonal (metric)163.906 cmEnergy efficiency scaleA to GHorizontal scan range30 - 140 kHzComputer systems 600 (SVGA), 1224 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1152, 2560 x 1440, 3840 x 2160Windows operating systems supported inux operating systems supportedWindows 7 Professional, Windows 7 Notaco x 10.11 El CapitanSupported video modes480p, 576p, 720p, 1080i, 1080p, 2160p480p, 576p, 720p, 1080i, 1080p, 2160p1517.9 mm				
Contrast ratio (typical)1300:1Energy consumption (SDR) per 1000101 kWhViewing angle, horizontal178°AC input voltage100 - 240 VDisplay number of colours1.07 billion coloursAC input frequency50/60 HzPixel pitch0.372 x 0.372 mmHeat dissipation344.63 BTU/hDisplay diagonal (metric)163.906 cmEnergy efficiency scaleA to GHorizontal scan range24 - 75 HzWindows operating systemsWindows 7 Professional, Windows 7Supported graphics resolutions24 - 75 HzWindows operating systemsWindows 7 Professional, Windows 8.1Supported video modes480p, 576p, 720p, 1080i, 1080p, 2160p24 - 75 HzMac operating systems supportedMac OS X 10.10 Yosemite, Mac OS X 10.11 El CapitanSupported video modes480p, 576p, 720p, 1080i, 1080p, 2160p1517.9 mmMac Os 210.9 mm	•			
Viewing angle, horizontal178°hours101 kWhViewing angle, vertical178°AC input voltage100 - 240 VDisplay number of colours1.07 billion coloursAC input frequency50/60 HzPixel pitch0.372 x 0.372 mmHeat dissipation344.63 BTU/hDisplay diagonal (metric)163.906 cmEnergy efficiency scaleA to GHorizontal scan range24 - 75 HzWindows operating systemsWindows 7 Professional, Windows 7Supported graphics resolutions1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 1024 x 768 X(GA), 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160Windows operating systems supportedWindows 0 X 10.10 Yosemite, Mac OS X 10.11 El CapitanSupported video modes480p, 576p, 720p, 1080i, 1080p, 2160p450, 570p, 720p, 1080i, 1080p, 2160p1517.9 mm	•		5, , , ,	
Viewing angle, vertical178°AC input voltage100 - 240 VDisplay number of colours1.07 billion coloursAC input frequency50/60 HzDisplay diagonal (metric)0.372 x 0.372 mmHeat dissipation344.63 BTU/hDisplay diagonal (metric)163.906 cmEnergy efficiency scaleA to GHorizontal scan range30 - 140 kHzComputer systemWindows 7 Professional, Windows 7Vertical scan range24 - 75 HzWindows operating systemsWindows 7 Professional, Windows 8.1Supported graphics resolutions1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160Mac operating systems supportedMac OS X 10.10 Yosemite, Mac OS X 10.11 El CapitanSupported video modes480p, 576p, 720p, 1080i, 1080p, 2160pHeight & dimensionsWeight & dimensionsSupported video modes480p, 576p, 720p, 1080i, 1080p, 2160pDisplay width1517.9 mm				101 kWh
Norming ungle, vertical1/0Display number of colours1.07 billion coloursAC input frequency50/60 HzPixel pitch0.372 x 0.372 mmHeat dissipation344.63 BTU/hDisplay diagonal (metric)163.906 cmEnergy efficiency scaleA to GHorizontal scan range30 - 140 kHzComputer systemWindows 7 Professional, Windows 7Vertical scan range24 - 75 HzWindows operating systemsWindows 7 Professional, Windows 7640 x 480 (VGA), 720 x 400, 800 x600 (SVGA), 1024 x 768 (KGA),Mac operating systems supportedMac OS X 10.10 Yosemite, Mac OS XSupported graphics resolutions1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160Mac operating systems supportedMac OS X 10.10 Yosemite, Mac OS XSupported video modes480p, 576p, 720p, 1080i, 1080p, 2160pHeight & dimensionsVertical solutions1517.9 mm	0 0			100 240 \/
Display humber of colours1.07 bindirection344.63 BTU/hPixel pitch0.372 x 0.372 mmHeat dissipation344.63 BTU/hDisplay diagonal (metric)163.906 cmEnergy efficiency scaleA to GHorizontal scan range30 - 140 kHzComputer systemWindows 7 Professional, Windows 7Vertical scan range24 - 75 Hz640 x 480 (VGA), 720 x 400, 800 xWindows operating systemsWindows 7 Professional, Windows 7Supported graphics resolutions1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160Mac operating systems supportedMac OS X 10.10 Yosemite, Mac OS X 10.11 El CapitanSupported video modes480p, 576p, 720p, 1080i, 1080p, 2160pHeat dissipation1517.9 mm	5 5 7			
InstructionInstructionInstructionInstructionInstructionDisplay diagonal (metric)163.906 cmEnergy efficiency scaleA to GHorizontal scan range30 - 140 kHzComputer systemWindows 7 Professional, Windows 7Vertical scan range24 - 75 Hz640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160Windows operating systems supported (Intux operating systems supported)Mac OS X 10.10 Yosemite, Mac OS X 10.11 El CapitanSupported video modes480p, 576p, 720p, 1080i, 1080p, 2160pHord State Display widthWeight & dimensions			1 1 2	
Horizontal scan range30 - 140 kHzComputer systemVertical scan range24 - 75 HzWindows operating systemsWindows 7 Professional, Windows 7640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160Windows operating systems supportedWindows 7 Professional, Windows 7Supported video modes480p, 576p, 720p, 1080i, 1080p, 2160pWeight & dimensionsWeight & dimensionsSupported video modes480p, 576p, 720p, 1080i, 1080p, 2160pDisplay width1517.9 mm	1		•	
Vertical scan range24 - 75 HzWindows operating systems supported graphics resolutionsWindows 7 Professional, Windows 7 Ultimate, Windows 8, Windows 8, 1 Mac OS X 10.10 Yosemite, Mac OS X 1.152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160Windows operating systems supported wideo modesWindows 7 Professional, Windows 7 Ultimate, Windows 8, Windows 8, 1 Mac OS X 10.10 Yosemite, Mac OS X 10.11 El CapitanSupported video modes480p, 576p, 720p, 1080i, 1080p, 2160pWeight & dimensions Display width1517.9 mm			Energy enciency scale	A 10 G
Supported graphics resolutions640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160Windows operating systems supportedWindows / Professional, Windows / Professive /	5		Computer system	
Supported graphics resolutions1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160Mac operating systems supportedMac OS X 10.10 Tosemite, Mac OS X 10.11 El CapitanSupported video modes480p, 576p, 720p, 1080i, 1080p, 2160pMac operating systems supported✓Supported video modes480p, 576p, 720p, 1080i, 1080p, 2160pDisplay width1517.9 mm	Vertical scan range	640 x 480 (VGA), 720 x 400, 800 x		
1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160 480p, 576p, 720p, 1080i, 1080p, 2160pLinux operating systems supportedImage: Comparison of the system support of	Supported graphics resolutions	1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan
Supported video modes480p, 576p, 720p, 1080i, 1080p, 2160pWeight & dimensionsDisplay width1517.9 mm				٠
2160p Display Width 1517.9 mm	Supported video modes		Weight & dimensions	
Hardness7HDisplay depth78.7 mm	Supported video modes	2160p	Display width	1517.9 mm
	Hardness	7H	Display depth	78.7 mm

Display		Weight & dimensions	
Native refresh rate	60 Hz	Display height	892.9 mm
RGB colour space	NTSC	Display weight	45.2 kg
Colour gamut	72%	Packaging data	
Ports & interfaces		Package weight	55.3 kg
HDMI ports quantity *	3	Packaging content	
HDMI version	2.0	Remote control included	1
DVI port *	×	Stylus pen	1
DisplayPorts quantity *	1	Number of stylus pens	2
USB port *	✓	Cables included	DisplayPort, HDMI, USB, USB Type-C
USB ports quantity USB version	8 2.0/3.2 Gen 1 (3.1 Gen 1)	Operational conditions	
USB connector type	USB Type-A	Operating temperature (T-T)	0 - 40 °C
USB 2.0 Type-B ports quantity	3	Operating relative humidity (H-H)	10 - 80%
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	4	Storage temperature (T-T)	-20 - 60 °C
ports quantity	4	Storage relative humidity (H-H)	5 - 90%
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Operating altitude	0 - 5000 m
USB Power Delivery (USB PD)	<i>y</i>	Non-operating altitude	0 - 12192 m
USB Power Delivery up to	90 W	Features	
USB Type-C DisplayPort Alternate	1	Heat dissipation (max)	1262.49 BTU/h
Mode	•	Technical details	
Ethernet LAN *	✓	Sustainability compliance	1
Ethernet LAN (RJ-45) ports	1	Sustainability certificates	ENERGY STAR
Wi-Fi *	×	Doesn't contain	Arsenic, Mercury, PVC/BFR
Audio (L/R) out	1	Compliance certificates	RoHS
RS-232 interface	V	Other features	
Audio		Quick start guide	1
Built-in speaker(s) *	1	Cable lock slot	
Number of built-in speakers	2	LED indicators	
RMS rated power	40 W	On/off switch	·
Speaker impedance	8 Ω	Viewable size diagonal	16.4 cm
Speaker frequency range	120 - 20000 Hz	Viewable size, horizontal	142.8 cm
Design		Viewable size, vertical	80.3 cm
Product design *	Interactive flat panel	Power supply type	Internal
Placement supported *	Indoor	Cable management	1
Product colour *	Black	Response time	9 s
Screen shape	Flat ✓	Plug and Play	1
VESA mounting * Panel mounting interface	✔ 400 x 400 mm		
Bezel width (bottom)	400 x 400 mm 4.47 cm		
Bezel width (side)	4.47 cm		
(0.00)			



5397184821541

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.