



DELL P5524QT Interaktiivinen litteä paneeli 139,7 cm (55") LCD 350 cd/m² 4K Ultra HD musta Kosketusnäyttö

Tuotemerkki : DELL

Tuotekoodi: DELL-P5524QT

Tuotteen nimi : P5524QT



DELL P5524QT. Tuotteen muotoilu: Interaktiivinen litteä paneeli. Näytön halkaisija: 139,7 cm (55"), Näytön teknologia: LCD, Näytön erottelutarkkuus: 3840 x 2160 pikseliä, Näytön kirkkaus: 350 cd/m², HD-tyyppi: 4K Ultra HD, Kosketusnäyttö. Tuotteen väri: musta

| Display | | Design | |
|---|--|---|--|
| Panel type | IPS | Bezel width (top) | 4.47 cm |
| LED backlight | ✓ | Anti-glare screen | ✓ |
| Display diagonal * | 139.7 cm (55") | Performance | |
| Display technology * | LCD | Purpose * | Corporate |
| Display resolution * | 3840 x 2160 pixels | On Screen Display (OSD) | ✓ |
| Display brightness * | 350 cd/m ² | Power | |
| HD type * | 4K Ultra HD | Power consumption (typical) * | 77.1 W |
| Touchscreen * | ✓ | Power consumption (standby) * | 0.5 W |
| Number of simultaneous touchpoints | 20 | Power consumption (off) | 0.3 W |
| Multi-touch | ✓ | Power consumption (max) | 320 W |
| Native aspect ratio | 16:9 | Energy efficiency class (SDR) | F |
| Contrast ratio (typical) | 1300:1 | Energy efficiency class (HDR) | Not available |
| Viewing angle, horizontal | 178° | Energy consumption (SDR) per 1000 hours | 77 kWh |
| Viewing angle, vertical | 178° | AC input voltage | 100 - 240 V |
| Display number of colours | 1.07 billion colours | AC input frequency | 50/60 Hz |
| Pixel pitch | 0.315 x 0.315 mm | Heat dissipation | 263.08 BTU/h |
| Display diagonal (metric) | 138.787 cm | Energy efficiency scale | A to G |
| Horizontal scan range | 30 - 140 kHz | Computer system | |
| Vertical scan range | 24 - 75 Hz | Windows operating systems supported | Windows 7 Professional, Windows 7 Ultimate, Windows 8, Windows 8.1 |
| Supported graphics resolutions | 640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160 | Mac operating systems supported | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan |
| Supported video modes | 480p, 576p, 720p, 1080i, 1080p, 2160p | Linux operating systems supported | ✓ |
| Hardness | 3H | Weight & dimensions | |
| Native refresh rate | 60 Hz | Display width | 1299 mm |
| RGB colour space | NTSC | Display depth | 78.7 mm |
| Colour gamut | 72% | Display height | 769.8 mm |
| Ports & interfaces | | Display weight | 34.3 kg |
| HDMI ports quantity * | 3 | Packaging data | |
| HDMI version | 2.0 | Package weight | 41.9 kg |
| DVI port * | ✗ | Packaging content | |
| DisplayPorts quantity * | 1 | Remote control included | ✓ |
| USB port * | ✓ | Stylus pen | ✓ |
| USB ports quantity | 8 | Number of stylus pens | 2 |
| USB version | 2.0/3.2 Gen 1 (3.1 Gen 1) | Cables included | DisplayPort, HDMI, USB, USB Type-C |
| USB connector type | USB Type-A | Operational conditions | |
| USB 2.0 Type-B ports quantity | 3 | Operating temperature (T-T) | 0 - 40 °C |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 4 | Operating relative humidity (H-H) | 10 - 80% |

| Ports & interfaces | | Operational conditions | |
|---|------------------------|---------------------------------|---------------------------|
| USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity | 1 | Storage temperature (T-T) | -20 - 60 °C |
| USB Power Delivery (USB PD) | ✓ | Storage relative humidity (H-H) | 5 - 90% |
| USB Power Delivery up to | 90 W | Operating altitude | 0 - 5000 m |
| USB Type-C DisplayPort Alternate Mode | ✓ | Non-operating altitude | 0 - 12192 m |
| Ethernet LAN * | ✓ | Features | |
| Ethernet LAN (RJ-45) ports | 1 | Heat dissipation (max) | 1091.89 BTU/h |
| Wi-Fi * | ✗ | Technical details | |
| Audio (L/R) in | 1 | Sustainability compliance | ✓ |
| RS-232 interface | ✓ | Sustainability certificates | ENERGY STAR |
| Audio | | Doesn't contain | Arsenic, Mercury, PVC/BFR |
| Built-in speaker(s) * | ✓ | Compliance certificates | RoHS |
| Number of built-in speakers | 2 | Other features | |
| RMS rated power | 20 W | Quick start guide | ✓ |
| Speaker impedance | 8 Ω | Cable lock slot | ✓ |
| Speaker frequency range | 120 - 20000 Hz | LED indicators | ✓ |
| Design | | On/off switch | ✓ |
| Product design * | Interactive flat panel | Viewable size, horizontal | 121 cm |
| Placement supported * | Indoor | Viewable size, vertical | 68 cm |
| Product colour * | Black | Power supply type | Internal |
| Screen shape | Flat | Cable management | ✓ |
| VESA mounting * | ✓ | Response time | 9 s |
| Panel mounting interface | 300 x 400 mm | Plug and Play | ✓ |
| Bezel width (bottom) | 4.47 cm | | |
| Bezel width (side) | 4.47 cm | | |



5397184821534

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date