## **NOC**

## AOC E3 24E3QAF LED display $60.5\ cm\ (23.8")\ 1920\ x\ 1080\ pixels$ Full HD LCD Black

Brand : AOC Product family: E3 Product code: 24E3QAF

**Product name:** 24E3QAF

Screen size (inch) 23.8, Panel resolution 1920x1080, Max Refresh rate 75 Hz, Panel type IPS, HDMI HDMI  $1.4 \times 1$ , DisplayPort DisplayPort  $1.2 \times 1$ , D-SUB (VGA)  $1 \times 1$ , DVI  $1 \times 1$ 00, Sync technology (VRR) Adaptive Sync AOC E3 24E3QAF. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920  $\times 1080$  pixels, HD type: Full HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting, Height adjustment. Product colour: Black





Display		Ergonomics	
Display  Display diagonal *  Display resolution *  HD type *  Native aspect ratio *  Display technology *  Panel type *  LED backlight  Backlight type  Touchscreen *  Response time *  Anti-glare screen  Screen shape *  Contrast ratio (typical) *  Contrast ratio (dynamic)  Maximum refresh rate *  Viewing angle, horizontal  Viewing angle, vertical  Pixel pitch	60.5 cm (23.8")  1920 x 1080 pixels  Full HD  16:9  LCD  IPS  W-LED  X  4 ms  Flat  1000:1  20000000:1  75 Hz  178°  178°  0.2745 x 0.2745 mm	Cable lock slot * Cable lock slot type Height adjustment * Height adjustment Pivot Pivot angle Swivelling Swivel angle range Tilt adjustment Tilt angle range On Screen Display (OSD)  On Screen Display (OSD) languages Number of OSD languages Plug and Play	Kensington  15 cm  -90 - 90°  0 - 180°  Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish  16
Pixel density Horizontal scan range	93 ppi 30 - 85 kHz	LED indicators  Power	<b>/</b>
Vertical scan range Viewable size, horizontal Viewable size, vertical Digital horizontal frequency Digital vertical frequency Display diagonal (metric) High Dynamic Range (HDR) supported	48 - 75 Hz 52.7 cm 29.6 cm 30 - 85 kHz 48 - 75 Hz 60.47 cm	Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage AC input frequency Input current Power supply type	18 W 0.5 W 35 W 0.3 W 100 - 240 V 50/60 Hz 1.5 A
DDC/CI	✓		

Display		Operational conditions	
	2U		0 - 40 °C
Surface hardness	3H	Operating temperature (T-T)  Storage temperature (T-T)	0 - 40 °C -25 - 55 °C
Performance		Operating relative humidity (H-H)	10 - 85%
Fast charging	×	Storage relative humidity (H-H)	5 - 93%
VESA Adaptive Sync support	•	Operating altitude	0 - 5000 m
Flicker-free technology	<b>✓</b>	Non-operating altitude	0 - 12192 m
Low Blue Light technology	<b>✓</b>	Weight & dimensions	
Game mode	•	Width (with stand)	540 mm
Multimedia		Depth (with stand)	200.1 mm
Number of speakers	2	Height (with stand)	503.6 mm
Built-in speaker(s) *	✓	Weight (with stand)	4.45 kg
Built-in microphone	×	Width (without stand) Depth (without stand)	540 mm 50.7 mm
Built-in camera *	×	Height (without stand)	362.3 mm
Design		Weight (without stand)	2.63 kg
Market positioning *	Office	Packaging data	-
Product colour *	Black	Package width	613 mm
Frameless design	✓	Package depth	162 mm
Front bezel colour	Black	Package height	519 mm
Detachable stand	✓	Package weight	7.14 kg
Feet colour	Black	Packaging content	
Ports & interfaces		Stand included	1
Built-in USB hub *	×	Cables included	AC, DisplayPort, HDMI
VGA (D-Sub) ports quantity	1	Quick start guide	✓
HDMI *	✓	Sustainability	
HDMI ports quantity	1	Sustainability compliance	<b>✓</b>
HDMI version	1.4	Sustainability certificates	EPEAT Silver, TCO
DisplayPorts quantity	1 1.2	Other features	2. 2
DisplayPort version Audio input	1.2 ✓		
Headphone out *	<b>▼</b>	FPS counter	<b>V</b>
Headphone outputs	1	Dial point	•
Headphone connectivity	3.5 mm	Shadow control	VECA DO
HDCP	✓	Compatibility Exterior finish type	VESA-P2 Textured
HDCP version	1.4	Recyclable packaging material	100%
AC (power) in	<b>✓</b>	Warranty period	3 year(s)
Mobile High-Definition Link (MHL)	×		CB, CE, EAC, Federal
Ergonomics		Compliance certificates	Communications Commission (FCC), RoHS, cTUVus, WEEE
VESA mounting *	<b>✓</b>	Light effects	x
		Certification	ISO 9241-307
Panel mounting interface	100 x 100 mm	Certification	150 5241 507
Cable management	100 x 100 mm  ✓	Recycling data	150 3241 307



4038986141253

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.