

PRODUCT DATASHEET

SMART+ WIFI FLOOD Camera

SMART+ FLOOD CAMERA | Floodlight with integrated camera, speaker, motion and daylight sensor



Areas of application

- Garages
- Entrance areas
- Outdoor use (IP44)

Product benefits

- Easy and quick installation
- Increased perception of safety thanks to high brightness

Product features

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android 4.4 or iOS 9.0)
- Dimmable
- Color temperature: 3,000 K (Warm White)
- Luminous flux: 1,800 lm
- Adjustable head
- Type of protection, front side: IP44
- HD Live view camera
- Built in speaker and alarm siren



TECHNICAL DATA

Electrical data

Nominal wattage	24.00 W
Nominal voltage	220...240 V
Nominal current	114.4 mA
Mains frequency	50...60 Hz
Power factor λ	> 0.50
Operating mode	Mains voltage


Photometrical data

Light color (designation)	Warm White
Standard deviation of color matching	< 6 sdcm
Nominal luminous flux	1800 lm
Luminous flux	1800 lm
Luminous efficacy	74 lm/W
Color temperature	3000 K
Color rendering index Ra	> 80

Light technical data

Beam angle	120 °
------------	-------

Dimensions & Weight



Product weight	990.00 g
Length	163.00 mm
Width	169.00 mm
Height	250.00 mm

Lifespan

Lifespan	25000 h
----------	---------

Colors & materials

Product color	Dark gray
Housing color	Dark gray
Body material	Aluminum

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Additional product data

Mounting location	Wall
-------------------	------

Capabilities

Dimmable	Yes
Type of connection	Terminal, 3-Pole (L, N, PE)
Compatible smart home technology	Google Assistant / Amazon Alexa
LED module replaceable	Not replaceable

Certificates & Standards

Standards	CE / EAC / REACH / RoHS
Protection class	II
Type of protection	IP44



Energy labelling regulation data acc EU 2019/2015

Correlated colour temperature type	SINGLE_VALUE
EPREL ID	1086183
Model number	AC35220

EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required
- Complete mounting and connecting accessories included

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction SMART WIFI FLOOD
	Declarations of conformity SMART OUTD WIFI FLOOD CAMERA 830 DGLEDV

DOWNLOAD DATA

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075478312	Folding box 1	262 mm x 182 mm x 179 mm	1125.00 g	8.54 dm ³
4058075478329	Shipping box 4	378 mm x 276 mm x 204 mm	4961.00 g	21.28 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.