## **Product Information Sheet**

separate con-

trol gear, light-

control

ing

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	ELEGATED REGGE	2,411014 (20) 2013/2	olo with regard to energ	By labelling of light		
Supplier's name	or trade mark:	LEDVANCE				
Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany						
Model identifie	r: AC32950					
Type of light so	urce:					
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type		E27				
(or other electri	c interface)					
Mains or non-mains:		MLS	Connected light source (CLS):	Yes		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield	d:	No	Dimmable:	Yes		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
• .	nption in on- 00 h), rounded st integer	6	Energy efficiency class	E		
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone errow cone (90º)	680 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 400		
On-mode power (P <sub>on</sub> ), ex- pressed in W		6,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,50		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		0,50	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	162	Spectral power dis-	See image		
sions without	Width	64	tribution in the	in last page		

64

range 250 nm to 800

nm, at full-load

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	52		
		Chromaticity coordinates (x and y)	0,494 0,424		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	0	Survival factor	0,90		
the lumen maintenance factor	0,70				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9		

(a)'-': not applicable; (b)'-': not applicable;

