

# PRODUCT DATASHEET SMART+ Wifi Orbis Kite White 510mm TW

# Kite | Decorative ceiling luminaires with WiFi technology



#### Areas of application

- Indoor applications

- Kitchens, living rooms, children's rooms or home offices

## **Product benefits**

- Easy and quick installation

#### **Product features**

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android<sup>™</sup> 4.4 or iOS 10.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Dimmable
- Network protocol: WiFi



# **TECHNICAL DATA**

# **Electrical data**


Nominal wattage	34.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	150.000 mA
Power factor $\lambda$	> 0.90
Total harmonic distortion	< 20 %
Protection class	1
Operating mode	Mains voltage

### Photometrical data

Luminous flux	2400 lm	
Total luminous flux of contained light sources	3200 lm	
Luminous efficacy	93 lm/W	
Color temperature	30006500 K	
Light color (designation)	Tunable White	
Color rendering index Ra	> 80	
Standard deviation of color matching	< 6 sdcm	
Photobiological safety group acc. to EN62778	RG1	
Photobiological safety group acc. to EN62471	RG1	
Beam angle	126.00 °	

# **Dimensions & Weight**

Diameter	510.00 mm
Height	83.00 mm
Product weight	1284.00 g



# Materials & Colors

Product color White		
Housing color	White	
Body material	Polymethylmethacrylate (PMMA)	
Cover material	Polymethylmethacrylate (PMMA)	
Glow Wire Test according to IEC 60695-2-12	650 °C	
Mercury content	0.0 mg	

## **Application & Mounting**

Ambient temperature range	-20+40 °C	
Type of connection	Screw terminal	
Type of protection	IP20	
Dimmable	Yes	
Type of dimming	WiFi	
Mounting type	Surface	
Mounting location	Ceiling	
Application environment	Indoor	
LED module replaceable	Not replaceable	
With light source	No	

# Lifespan

Lifespan L70/B50 at 25 °C	30000 h	
Number of switching cycles	15000	

## **Certificates & Standards**

Standards	CE / EAC / REACH / RoHS
Luminaire with limited surface temperature, "D sign"	No

# Additional product data

Product remark	Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.
----------------	---

# **EQUIPMENT / ACCESSORIES**

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required

### **DOWNLOAD DATA**

	DOWNLOAD DATA
PDF	User instruction
PDF	Declarations of conformity

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075486348	Folding box 1	542 mm x 102 mm x 544 mm	1732.00 g	30.07 dm <sup>3</sup>
4058075516519	Shipping box 3	564 mm x 325 mm x 567 mm	6143.00 g	103.93 dm³
4058075486355	Shipping box 7	737 mm x 565 mm x 570 mm	13668.00 g	237.35 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.