# PRODUCT DATASHEET SMART+ BT FLEX 5M RGB + TW

SMART+ FLEX MULTICOLOR | Flexible LED strips for indoor use with Bluetooth technology



#### Areas of application

- General illumination
- Residential interiors

#### **Product benefits**

- Easy and quick installation
- Uses multi color and cold or warm white light for most flexible lighting scenes

#### **Product features**

- Flexible, self-adhesive RGBW strip with wireless smart lighting function
- Controllable via LEDVANCE SMART+ App (with minimum Android 6.0 or iOS 11.0)
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Network protocol: Bluetooth



# **TECHNICAL DATA**

#### **Electrical data**

Nominal wattage	16.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	120.000 mA
Power factor $\lambda$	> 0.50
Protection class	Ш
Operating mode	External LED driver

#### Photometrical data

Luminous flux	1200 lm	
Total luminous flux of contained light sources	1600 lm	
Luminous efficacy	75 lm/W	
Color temperature	2000 6500 K	
Light color (designation)	RGBTW	
Color rendering index Ra	> 80	
Standard deviation of color matching	≤6 sdcm	
Beam angle	110 °	

# **Dimensions & Weight**

Length	5000.00 mm
Width	10.00 mm
Height	2.60 mm
Product weight	700.00 g

#### Materials & Colors

Product color	Transparent
Body material	Silicone
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg



# **Application & Mounting**

Ambient temperature range	-20+40 °C
Type of connection	Plug type C (EU)
Type of protection	IP20
Dimmable	Yes
Type of dimming	Bluetooth
Mounting type	Surface
Mounting location	All surfaces
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	Yes

# Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

#### Certificates & Standards

Standards CE / EAC / REACH / RoHS
-----------------------------------

# **EQUIPMENT / ACCESSORIES**

- For control via LEDVANCE SMART + App Android smartphone (with Android 6.0 and later) required
- Power supply included

#### **DOWNLOAD DATA**

	DOWNLOAD DATA
PDF	User instruction
PDF	Declarations of conformity

#### **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075504844	Folding box 1	62 mm x 230 mm x 205 mm	897.00 g	2.92 dm³
4058075504851	Shipping box 4	430 mm x 245 mm x 154 mm	3914.00 g	16.22 dm³



The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.