

## AXIS T94S01P

### Outdoor protection for cabling and devices connected to Axis cameras

AXIS T94S01P Conduit Back Box is an outdoor-ready, impact resistant (IK10+) back box designed to be mounted behind a wide range of Axis network cameras. It has an ingress-protected (IP66/IP67) compartment for secure storage of connectivity devices. Examples include storing an IP-over-COAX adapter to re-use legacy cabling or a network cable coupler to bridge between rigid and flexible network cables. AXIS T94S01P enables both camera and connectivity device to be safely mounted at the same point, without need for extra cabinet installation (even directly onto junction boxes). The finished installation is both aesthetically pleasing and able to withstand challenging outdoor conditions.

- > **IP66/IP67 storage compartment for connectivity devices**
- > **Impact resistant (IK10+) against vandalism attempts**
- > **3/4" / M25 conduit interface from both side and back**
- > **Compatible with a wide range of Axis network cameras**



## AXIS T94S01P

General	
<b>Supported products</b>	AXIS P14 Network Camera Series (requires AXIS T94F01M J-Box/Gang Box Plate) AXIS P32 Network Camera Series AXIS P33 Network Camera Series AXIS Q17 Network Camera Series AXIS Q19 Thermal Network Camera Series AXIS Q35 Network Camera Series AXIS Q36 Network Camera Series
<b>Environment</b>	Indoor/outdoor
<b>Mounting</b>	Double Gang Box, Single Gang Box, 4" Octagon Junction Box, 4" Square Junction Box
<b>Casing</b>	Material: powder-coated aluminum casing, stainless steel screws (TX20) Color: white NCS S 1002-B
<b>Cable routing</b>	Back: 3 cable holes Sides: 3/4" conduit entrances Underside: 4x gaskets C M20 5–9.5 mm Top cover: 3x gaskets C M20 5–9.5 mm
<b>Maximum load</b>	2.3 kg (5 lb)
<b>Dimensions</b>	Height: 53.5 mm (2 1/8 in) ø 157 mm (6 3/16 in)
<b>Weight</b>	750 g (1.65 lb)
<b>Sustainability</b>	PVC free
<b>Approvals</b>	<b>Safety</b> IEC/EN/UL 62368–1, IEC/EN/UL 60950–22 <b>Environment</b> IEC 60068–2–6, IEC 60068–2–27, IEC/EN 60529 IP66/IP67, NEMA 250 Type 4X <b>Impact</b> IEC/EN 62262 IK10+
<b>Included accessories</b>	Installation Guide, 3x Gasket C M20 Cable 3–5 mm, 4x stainless steel screws (TX20) and washers
<b>Optional accessories</b>	AXIS T91A47 Pole Mount, AXIS T94R01B Corner Bracket, AXIS ACI Conduit Adapter 3/4" U-Shape 30 mm, AXIS ACI Conduit Adapter 3/4" NPS, Network cable coupler indoor, Network cable coupler indoor slim
<b>Warranty</b>	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>

### Environmental responsibility:

[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)