



**DELL A7067488 power distribution unit (PDU) 15 AC outlet(s) 0U Black**

Brand : DELL

Product code: A7067488

Product name : A7067488



APC Basic Rack PDU Zero U power distribution strip

DELL A7067488 power distribution unit (PDU) 15 AC outlet(s) 0U Black:

APC Switched Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and active monitoring. Remote outlet level controls allow power on/off functionality for power recycling to remotely reboot equipment and restrict unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and low profile circuit breakers. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched Rack PDUs through secure Web, SNMP, or Telnet Interfaces.



| Design                |                 |
|-----------------------|-----------------|
| PDU types *           | Basic           |
| Rack capacity *       | 0U              |
| Product colour        | Black           |
| Ports & interfaces    |                 |
| AC outlets quantity * | 15 AC outlet(s) |
| Power plug            | C20 coupler     |
| AC outlet types *     | C13 coupler     |
| Features              |                 |
| Cable length          | 2.5 m           |

| Features                          |   |
|-----------------------------------|---|
| Compatible products               | P/N: AR3100, AR3150,<br>SMX3000RMHV2UNC,<br>SU2200R3IBX120, SU2200RMI3U.1,<br>SU2200RMXLI3U,<br>SU2200RMXLI3U-1EW,<br>SU2200RMXLI3U-2EW,<br>SU2200RMXLI3U-3EW,<br>SU2200RMXLINET-1EW,<br>SU2200RMXLINET-2EW,<br>SU2200RMXLINET-3EW,<br>SU3000R3IBX120, SU3000RMINET,<br>SU3000RMINET-1EW,<br>SU3000RMINET-2EW,<br>SU3000RMINET-3EW,<br>SU3000RMTX136, SU3000RMXLI3U,<br>SU3000RMXLI3U-1EW,<br>SU3000RMXLI3U-2EW,<br>SU3000RMXLI3U-3EW,<br>SU5000R51BX120,<br>SU5000R5IBX120,<br>SU5000R5TBX135, SU5000RMI5U,<br>SU5000RMI5U-1EW,<br>SU5000RMI5U-2EW,<br>SU5000RMI5U-3EW,<br>SU5000RMXLI5U,<br>SU5000RMXLI5U-1EW,<br>SU5000RMXLI5U-2EW,<br>SU5000RMXLI5U-3EW,<br>SUA2200RMI2U-1EW,<br>SUA2200RMI2U-SLV,<br>SUA2200RMXLI3U, SUA3000I,<br>SUA3000R2IX322, SUA3000RMI,<br>SUA3000RMI2U,<br>SUA3000RMI2U-1EW,<br>SUA3000RMI2U-2EW,<br>SUA3000RMI2U-3EW,<br>SUA3000RMI2U-BRZ,<br>SUA3000RMI2U-GLD,<br>SUA3000RMI2U-SLV, SURT3000XLI,<br>SURT3000XLI/S, SURT3000XLI-BRZ,<br>SURT3000XLI-GLD, SURT3000XLI-SLV, SURT3000XLI-TU |
| Power                             |   |
| Nominal input voltage *           | 120/208/230 V   |
| AC input frequency                | 50 - 60 Hz  |
| Maximum current *                 | 16 A  |
| Output voltage                    | 120/208/230 V   |
| Certificates                      |   |
| Certification                     | UL, cUL, VDE  |
| Operational conditions            |   |
| Operating temperature (T-T)       | 0 - 45 °C   |
| Operating relative humidity (H-H) | 5 - 95%   |
| Weight & dimensions               |   |
| Width                             | 44 mm   |
| Depth                             | 44 mm   |
| Height                            | 620 mm  |
| Weight                            | 2 kg  |



5711783357193

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-APR-2025. Prints or copies of Information are only valid on the printed Publication date