



## DELL A7067488 tehonjakeluyksikkö 15 AC-pistorasia(a) 0U musta

**Tuotemerkki :** DELL

**Tuotekoodi:** A7067488

**Tuotteen nimi :** A7067488

DELL A7067488. PDU types: Perus, Telineen kapasiteetti: 0U, Tuotteen väri: musta. Ulostulojen määrä: 15 AC-pistorasia(a), Pistorasian tyypit: C13 liitin, Virtapistoke: C20 liitin. Johdon pituus: 2,5 m, Sertifiointi: UL, cUL, VDE, Yhteensopivat tuotteet: P/N: AR3100, AR3150, SMX3000RMHV2UNC, SU2200R3IBX120, SU2200RM13U.1, SU2200RMXLI3U,.... Nimellinen syöttöjännite: 120/208/230 V, Enimmäisvirta: 16 A, AC-syöttötaajuus: 50 - 60 Hz. Tuotteen leveys: 44 mm, Tuotteen syvyys: 44 mm, Tuotteen korkeus: 620 mm



### Design

PDU types *	Basic
Rack capacity *	0U
Product colour	Black

### Ports & interfaces

AC outlets quantity *	15 AC outlet(s)
Power plug	C20 coupler
AC outlet types *	C13 coupler

### Features

Cable length	2.5 m
Certification	UL, cUL, VDE

## Features

	P/N: AR3100, AR3150, SMX3000RMHV2UNC, SU2200R3IBX120, SU2200RMI3U.1, SU2200RMXLI3U, SU2200RMXLI3U-1EW, SU2200RMXLI3U-2EW, SU2200RMXLI3U-3EW, SU2200RMXLINET-1EW, SU2200RMXLINET-2EW, SU2200RMXLINET-3EW, SU3000R3IBX120, SU3000RMINET, SU3000RMINET-1EW, SU3000RMINET-2EW, SU3000RMINET-3EW, SU3000RMTX136, SU3000RMXLI3U, SU3000RMXLI3U-1EW, SU3000RMXLI3U-2EW, SU3000RMXLI3U-3EW, SU5000R51BX120, SU5000R5IBX120, SU5000R5TBX135, SU5000RMI5U, SU5000RMI5U-1EW, SU5000RMI5U-2EW, SU5000RMI5U-3EW, SU5000RMXLI5U, SU5000RMXLI5U-1EW, SU5000RMXLI5U-2EW, SU5000RMXLI5U-3EW, SUA2200RMI2U-1EW, SUA2200RMI2U-SLV, SUA2200RMXLI3U, SUA3000I, SUA3000R2IX322, SUA3000RMI, SUA3000RMI2U, SUA3000RMI2U-1EW, SUA3000RMI2U-2EW, SUA3000RMI2U-3EW, SUA3000RMI2U-BRZ, SUA3000RMI2U-GLD, SUA3000RMI2U-SLV, SURT3000XLI, SURT3000XLI/S, SURT3000XLI-BRZ, SURT3000XLI-GLD, SURT3000XLI-SLV, SURT3000XLI-TU
Compatible products	

## Power

Nominal input voltage *	120/208/230 V
AC input frequency	50 - 60 Hz
Maximum current *	16 A
Output voltage	120/208/230 V

## Weight & dimensions

Width	44 mm
Depth	44 mm
Height	620 mm
Weight	2 kg

## Operational conditions

Operating temperature (T-T)	0 - 45 °C
Operating relative humidity (H-H)	5 - 95%



5711783357193

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date