



DELL A7067488 tehonjakeluyksikkö 15 AC-pistorasia(a) 0U musta

Tuotemerkki : DELL

Tuotekoodi: A7067488

Tuotteen nimi : A7067488

DELL A7067488. PDU types: Perus, Telineen kapasiteetti: 0U, Tuotteen väri: musta. Ulostulojen määrä: 15 AC-pistorasia(a), Pistorasian tyypit: C13 liitin, Virtapistoke: C20 liitin. Johdon pituus: 2,5 m, Sertifiointi: UL, cUL, VDE, Yhteensopivat tuotteet: P/N: AR3100, AR3150, SMX3000RMHV2UNC, SU2200R3IBX120, SU2200RMI3U.1, SU2200RMXLI3U,.... Nimellinen syöttöjännite: 120/208/230 V, Enimmäisvirta: 16 A, AC-syöttötaajuus: 50 - 60 Hz. Tuotteen leveys: 44 mm, Tuotteen syvyys: 44 mm, Tuotteen korkeus: 620 mm



Suunnittelu		Ominaisuudet	
PDU types *	Perus		P/N: AR3100, AR3150, SMX3000RMHV2UNC, SU2200R3IBX120, SU2200RMI3U.1, SU2200RMXLI3U, SU2200RMXLI3U-1EW, SU2200RMXLI3U-2EW, SU2200RMXLI3U-3EW, SU2200RMXLINET-1EW, SU2200RMXLINET-2EW, SU2200RMXLINET-3EW, SU3000R3IBX120, SU3000RMINET, SU3000RMINET-1EW, SU3000RMINET-2EW, SU3000RMINET-3EW, SU3000RMTX136, SU3000RMXLI3U, SU3000RMXLI3U-1EW, SU3000RMXLI3U-2EW, SU3000RMXLI3U-3EW, SU5000R51BX120, SU5000R5IBX120, SU5000R5TBX135, SU5000RMI5U, SU5000RMI5U-1EW, SU5000RMI5U-2EW, SU5000RMI5U-3EW, SU5000RMXLI5U, SU5000RMXLI5U-1EW, SU5000RMXLI5U-2EW, SU5000RMXLI5U-3EW, SUA2200RMI2U-1EW, SUA2200RMI2U-SLV, SUA2200RMXLI3U, SUA3000I, SUA3000R2IX322, SUA3000RMI, SUA3000RMI2U, SUA3000RMI2U-1EW, SUA3000RMI2U-2EW, SUA3000RMI2U-3EW, SUA3000RMI2U-BRZ, SUA3000RMI2U-GLD, SUA3000RMI2U-SLV, SURT3000XLI, SURT3000XLI/S, SURT3000XLI-BRZ, SURT3000XLI-GLD, SURT3000XLI-SLV, SURT3000XLI-TU
Telineen kapasiteetti *	0U		
Tuotteen väri	musta		
Liitettävyys			
Ulostulojen määrä *	15 AC-pistorasia(a)		
Virtapistoke	C20 liitin		
Pistorasian tyypit *	C13 liitin		
Ominaisuudet			
Johdon pituus	2,5 m		
Sertifiointi	UL, cUL, VDE		
		Yhteensopivat tuotteet	

Virranhallinta

Nimellinen syöttöjännite *	120/208/230 V
AC-syöttötaajuus	50 - 60 Hz
Enimmäisvirta *	16 A
Ulostulojännite	120/208/230 V

Paino ja mitat

Tuotteen leveys	44 mm
Tuotteen syvyys	44 mm
Tuotteen korkeus	620 mm
Paino	2 kg

Ympäristöolosuhteet

Käyttölämpötila (T-T)	0 - 45 °C
Käytön suhteellinen kosteus (H-H)	5 - 95%



5711783357193

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-NOV-2024. Prints or copies of Information are only valid on the printed Publication date