



## APC NetShelter Rack PDU Advanced tehonjakeluksikkö 42 AC-pistorasia(a) 0U musta

**Tuotemerkki :** APC

**Tuotekoodi:** APDU10250SW

**Tuotteen nimi :** NetShelter Rack PDU Advanced

APC NetShelter Rack PDU Advanced. PDU types: Kytkimellinen, Telineen kapasiteetti: 0U, Malli: Kolmivaiheinen. Ulostulojen määrä: 42 AC-pistorasia(a), Pistorasian tyypit: C13 liitin, C15 liitin, C19 liitin, C21 liitin, Virtapistoke: IEC 60309. LED-merkkivalot: Toiminta/Seikkailu, Verkko, Teho, Johdon pituus: 1,8 m, Tietoturva-algoritmit: 128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SNMP, SNMPv2, SNMPv3. Seuranta: Virta, Ilmankosteus, Teho, Lämpötila, Jännite, Outlet-ohjaus: Esto, Kierrätys, Sammutus, Käynnistys, Laiteohjelmiston päivitys (kautta): Verkko, USB. Nimellinen syöttöjännite: 400 V, Enimmäisvirta: 16 A, AC-syöttötaajuus: 50 - 60 Hz



Design		Power	
PDU types *	Switched	AC input frequency	50 - 60 Hz
Type	Three-phase	Maximum current *	16 A
Form factor	Rackmount	Nominal output voltage	230 V
Rack capacity *	0U	Output voltage	230 V
Mounting	Vertical	Load capacity	11500 VA
Product colour	Black	Number of phases	3
Display	LCD	Maximum total current draw per phase	16 A
On/off switch	✓	Power protection features	Overload
Regulatory Approvals	CE, CSA C22.2 No 62368-1, EN 62368-1, FCC part 15 subpart B, UKCA, UL 62368-1	Maximum power	11500 W
		Surge protection	✓
Ports & interfaces		Weight & dimensions	
AC outlets quantity *	42 AC outlet(s)	Width	56 mm
Power plug	IEC 60309	Depth	75 mm
AC outlet types *	C13 coupler, C15 coupler, C19 coupler, C21 coupler	Height	1490 mm
Ethernet LAN (RJ-45) ports	2	Weight	7.2 kg
USB ports quantity	1		
Features		Packaging data	
Daisy chain	✓	Package weight	9.2 kg
Reset button	✓	Package width	208 mm
LED indicators	Activity, Network, Power	Package depth	116 mm
Colour-coded outlets	✓	Package height	1720 mm
Cable length	1.8 m		
Security algorithms	128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SNMP, SNMPv2, SNMPv3	Operational conditions	
Password protection	✓	Operating temperature (T-T)	-5 - 60 °C
		Storage temperature (T-T)	-25 - 65 °C
		Operating relative humidity (H-H)	5 - 95%
		Storage relative humidity (H-H)	5 - 95%
		Operating altitude	0 - 3048 m
		Non-operating altitude	0 - 15240 m

Features		Operational conditions	
Compatible products	Compatible with most NetShelter SX enclosures and third-party racks	Operating temperature (T-T)	23 - 140 °F
Management features		Technical details	
Monitoring	Current, Humidity, Power, Temperature, Voltage	Compliance certificates	RoHS
Outlet control	Lock-out, Recycle, Turn off, Turn on		
Firmware upgradeable	✓		
Firmware upgradeable via	Network, USB		
Power			
Nominal input voltage *	400 V		



0731304439691



731304439691

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.