



APC NetShelter Rack PDU Advanced, Metered Outlet, 3PH, 22.1kW 400V 32A or 17.3kW 415V 30A, 48 Outlets, IEC309

Brand : APC

Product code: APDU10350MO

Product name : NetShelter Rack PDU Advanced, Metered Outlet, 3PH, 22.1kW 400V 32A or 17.3kW 415V 30A, 48 Outlets, IEC309

- Metered Outlet, 17.3kW, 3PH
- 415V, 30A, 530P6
- 48 Outlet
- Power metering via remote access
- High Density
- Availability
- Agility
- Manageability

NetShelter Rack PDU Advanced, Metered Outlet, 3PH, 22.1kW 400V 32A or 17.3kW 415V 30A, 48 Outlets, IEC309

APC NetShelter Rack PDU Advanced, Metered Outlet, 3PH, 22.1kW 400V 32A or 17.3kW 415V 30A, 48 Outlets, IEC309. PDU types: Metered, Metered-by-outlet, Rack capacity: 0U, Type: Three-phase. AC outlets quantity: 48 AC outlet(s), AC outlet types: C13 coupler, C15 coupler, C19 coupler, C21 coupler, Power plug: IEC 60309. LED indicators: Activity, Network, Power, Cable length: 1.8 m, Security algorithms: 128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SNMP, SNMPv2, SNMPv3. Monitoring: Current, Humidity, Power, Temperature, Voltage, Outlet control: Lock-out, Recycle, Turn off, Turn on, Firmware upgradeable via: Network, USB. Nominal input voltage: 400 V, Maximum current: 32 A, AC input frequency: 50 - 60 Hz



| Design | | Power | |
|----------------------------|---|-----------------------------------|-------------|
| PDU types * | Metered, Metered-by-outlet | Nominal input voltage * | 400 V |
| Type | Three-phase | AC input frequency | 50 - 60 Hz |
| Form factor | Rackmount | Maximum current * | 32 A |
| Rack capacity * | 0U | Nominal output voltage | 230 V |
| Mounting | Vertical | Load capacity | 22100 VA |
| Product colour | Black | Number of phases | 3 |
| Display | LCD | Power protection features | Overload |
| On/off switch | ✓ | Maximum power | 22100 W |
| Regulatory Approvals | CE, CSA C22.2 No 62368-1, EN 62368-1, FCC part 15 subpart B, UKCA, UL 62368-1 | Surge protection | ✓ |
| Ports & interfaces | | Weight & dimensions | |
| AC outlets quantity * | 48 AC outlet(s) | Width | 56 mm |
| Power plug | IEC 60309 | Depth | 75 mm |
| AC outlet types * | C13 coupler, C15 coupler, C19 coupler, C21 coupler | Height | 1780 mm |
| Ethernet LAN (RJ-45) ports | 2 | Weight | 9.6 kg |
| USB ports quantity | 1 | Packaging data | |
| Features | | Package weight | 12.6 kg |
| Daisy chain | ✓ | Package width | 262 mm |
| Reset button | ✓ | Package depth | 132 mm |
| LED indicators | Activity, Network, Power | Package height | 1980 mm |
| Colour-coded outlets | ✓ | Operational conditions | |
| Cable length | 1.8 m | Operating temperature (T-T) | -5 - 60 °C |
| Security algorithms | 128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SNMP, SNMPv2, SNMPv3 | Storage temperature (T-T) | -25 - 65 °C |
| Password protection | ✓ | Operating relative humidity (H-H) | 5 - 95% |
| Compatible products | Compatible with most NetShelter SX enclosures and third-party racks | Storage relative humidity (H-H) | 5 - 95% |
| | | Operating altitude | 0 - 3048 m |
| | | Non-operating altitude | 0 - 15240 m |
| | | Operating temperature (T-T) | 23 - 140 °F |

Management features**Technical details**

| | | | |
|--------------------------|--|-------------------------|------|
| Monitoring | Current, Humidity, Power, Temperature, Voltage | Compliance certificates | RoHS |
| Outlet control | Lock-out, Recycle, Turn off, Turn on | | |
| Firmware upgradeable | ✓ | | |
| Firmware upgradeable via | Network, USB | | |



0731304439738



731304439738

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.