



APC NetShelter Rack PDU Advanced, Metered, 3Phase, 22.1kW 400V 32A or 17.3kW 415V 30A, 48 Outlets, IEC309

Brand : APC

Product code: APDU10350ME

Product name : NetShelter Rack PDU Advanced, Metered, 3Phase, 22.1kW 400V 32A or 17.3kW 415V 30A, 48 Outlets, IEC309

- Metered, 17.3kW, 3PH
- 415V, 30A, 530P6
- 48 Outlet
- Power metering via remote access
- High Density
- Availability
- Agility
- Manageability


NetShelter Rack PDU Advanced, Metered, 3Phase, 22.1kW 400V 32A or 17.3kW 415V 30A, 48 Outlets, IEC309

APC NetShelter Rack PDU Advanced, Metered, 3Phase, 22.1kW 400V 32A or 17.3kW 415V 30A, 48 Outlets, IEC309. PDU types: Metered, Rack capacity: 0U, Type: Three-phase. AC outlets quantity: 48 AC outlet(s), AC outlet types: C13 coupler, C15 coupler, C19 coupler, C21 coupler, Power plug: IEC 60309. LED indicators: Activity, Network, Power, Cable length: 1.8 m, Security algorithms: 128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SNMP, SNMPv2, SNMPv3. Monitoring: Current, Humidity, Power, Temperature, Voltage, Outlet control: Lock-out, Recycle, Turn off, Turn on, Firmware upgradeable via: Network, USB. Nominal input voltage: 400 V, Maximum current: 32 A, AC input frequency: 50 - 60 Hz



Design		Power	
PDU types *	Metered	AC input frequency	50 - 60 Hz
Type	Three-phase	Maximum current *	32 A
Form factor	Rackmount	Nominal output voltage	230 V
Rack capacity *	0U	Output voltage	230 V
Mounting	Vertical	Load capacity	22100 VA
Product colour	Black	Number of phases	3
Display	LCD	Maximum total current draw per phase	32 A
On/off switch	✓	Power protection features	Overload
Regulatory Approvals	CE, CSA C22.2 No 62368-1, EN 62368-1, FCC part 15 subpart B, UKCA, UL 62368-1	Maximum power	22000 W
		Surge protection	✓
Ports & interfaces		Weight & dimensions	
AC outlets quantity *	48 AC outlet(s)	Width	56 mm
Power plug	IEC 60309	Depth	75 mm
AC outlet types *	C13 coupler, C15 coupler, C19 coupler, C21 coupler	Height	1780 mm
Ethernet LAN (RJ-45) ports	2	Weight	8.4 kg
USB ports quantity	1	Packaging data	
		Package weight	11.4 kg
		Package width	262 mm
		Package depth	132 mm
		Package height	1980 mm
Features		Operational conditions	
Daisy chain	✓	Operating temperature (T-T)	-5 - 60 °C
Reset button	✓	Storage temperature (T-T)	-25 - 65 °C
LED indicators	Activity, Network, Power	Operating relative humidity (H-H)	5 - 95%
Colour-coded outlets	✓	Storage relative humidity (H-H)	5 - 95%
Cable length	1.8 m	Operating altitude	0 - 3048 m
Security algorithms	128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SNMP, SNMPv2, SNMPv3	Non-operating altitude	0 - 15240 m
Password protection	✓		

Features		Operational conditions	
Compatible products	Compatible with most NetShelter SX enclosures and third-party racks	Operating temperature (T-T)	23 - 140 °F
Management features		Technical details	
Monitoring	Current, Humidity, Power, Temperature, Voltage	Compliance certificates	RoHS
Outlet control	Lock-out, Recycle, Turn off, Turn on		
Firmware upgradeable	✓		
Firmware upgradeable via	Network, USB		
Power			
Nominal input voltage *	400 V		



0731304439714



731304439714

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.