

GDPSP2

# 2-Port DisplayPort 1.2 Cinema 4K Splitter & Multi-Monitor MST Hub



- Connect 2 independent displays from a single DisplayPort 1.2 video output
- Mirror or extend a desktop across 2 displays from a computer with 1 DisplayPort output
- Enjoy Cinema 4K video resolutions up to 4096 x 2160 @ 60HZ

## 2-Port DisplayPort Cinema 4K Splitter and MST Hub


Connect two displays from a single DisplayPort 1.2-enabled computer with the IOGEAR 2-Port DisplayPort Splitter/MST Hub. Increase productivity and workflow by expanding the amount of usable screen space on two independent screens for multi-document viewing, media streaming, and content/web browsing, or mirror your computer's display across two monitors to allow remote viewing applications such as monitoring equipment diagnostics or the status of a remote server.

## Cinema 4K Video Support

IOGEAR's 2-Port DisplayPort 1.2 Splitter and MST Hub supports Cinema 4K resolutions up to 4096 x 2160 @ 60Hz and is ideal for use with applications such as medical imaging, graphic design, gaming, and more.

- Connect 2 independent displays from a single DisplayPort 1.2 video output
- Mirror or extend a desktop across 2 displays from a computer with 1 DisplayPort output
- Enjoy Cinema 4K video resolutions up to 4096 x 2160 @ 60HZ
- With DisplayPort 1.2 Graphic Cards:
  - 2 Monitors: Up to 4K 4096 x 2160 (DisplayPort/HDMI)
- Supports 7.1 digital audio surround sound
- Push-button toggle between Single Stream Transport (SST) and Multi-Stream Transport (MST)
- DPCP and HDCP compliant
- No driver or software installation needed
- Supports DisplayPort 1.2a; HDCP 1.3





### Requirements

- **Hardware:**
- Computer with DisplayPort 1.2 compatible graphics card
- 2 Monitors with DisplayPort ports
- 
- **Optional:**
- G2LDPDP02 DisplayPort to DisplayPort Cable

### Package Contents

- 1 x GDPSP2 2-Port DisplayPort Splitter / MST Hub
- 1 x Power Adapter
- 1 x Quick Start Guide
- 1 x Warranty Card

## Specifications

| Function                 | GDPSP2                     | Dimensions                     | GDPSP2         |
|--------------------------|----------------------------|--------------------------------|----------------|
| <b>Cable Connections</b> |                            | <b>Unit Dimensions</b>         |                |
| Input                    | DisplayPort 1.2            | Height                         | 1" (2.5 cm)    |
| Output                   | DisplayPort                | Depth                          | 4.4" (11.1 cm) |
| <b>Connectors</b>        |                            | Length                         |                |
| Video Input              | 1 x DisplayPort Female     | 3" (7.6 cm)                    |                |
| Video Output             | 2 x DisplayPort Female     | <b>Unit Package Dimensions</b> |                |
| <b>Data Rate</b>         |                            | Width                          |                |
| Up to 5.4Gbps            |                            | 9.4" (23.8 cm)                 |                |
| <b>Environment</b>       |                            | Height                         |                |
| Humidity                 | 20~90% RH (Non Condensing) | 2.32" (5.9 cm)                 |                |
| Operation Temperature    | 32°F~104°F (0°C~40°C)      | Depth                          |                |
| Storage Temperature      | -4°F~140°F (-20°C~60°C)    | 6.3" (16 cm)                   |                |
| <b>Housing</b>           |                            | <b>Master Carton</b>           |                |
| Case                     | Metal                      | Width                          |                |
| <b>LEDs</b>              |                            | 14.89" (37.8 cm)               |                |
| Input                    | 1                          | Height                         |                |
| Output                   | 2                          | 10.04" (25.5 cm)               |                |
| <b>Power</b>             |                            | Depth                          |                |
| Amps                     | 2A                         | 7.17" (18.2 cm)                |                |
| Voltage                  | DC 5V                      | Master Carton Qty.             |                |
| <b>Video Resolution</b>  |                            | 6                              |                |
| Up to 4K@60Hz            |                            | <b>Weight</b>                  |                |
| <b>Audio</b>             |                            | Master Carton Wt.              |                |
| Codec                    | 2-Ch LPCM / AC3 / DTS      | 8.95 lb                        |                |
| Sample Rate              | 32-192kHz                  | Unit Pack Wt.                  |                |
|                          |                            | 1.3 lb (0.6 kg)                |                |
|                          |                            | Unit Wt.                       |                |
|                          |                            | 0.45 lb (0.2 kg)               |                |