

# **Technical Specifications**

### **MOBOTIX Visage Technologies Face Recognition App**

#### **Face Recognition for Access Control**

The app compares and recognizes faces based on encrypted image data stored in the camera (face descriptors, not real image files). The application has a 97 % hit probability for access applications. The app can be tested free of charge for 30 days and can be activated for a period of either 12 or 24 months. The app is ideally suited for the following industries: Utilities, Energy & Mining; Industry & Production; Government; Traffic & Transportation; Retail; Healthcare; Education & Education.

- App works as an extended security level for access controls, login terminals, transactions, etc.
- Works with camera online and offline
- Delivers quick and reliable results
- Configuration of the app also via MxManagementCenter(free Advanced Config license required)
- Can be used with all cameras of the MOBOTIX 7 system platform





Beyond Human Vision

## **Technical Specifications**

#### **Product Information**

**Product Features** 

Product Name	Visage Technologies Face Recognition App	
Order Code	Mx-APP-VIS-FR-1 (one-year license) Mx-APP-VIS-FR-2 (two-year license)	
Supported MOBOTIX Cameras	Mx-M73A, Mx-S74A	
Minimum Camera Firmware V7.0.4.x		
MxManagementCenter Integration	<ul> <li>min.MxMC v2.2</li> <li>Advanced Config license required</li> <li>Smart Data Interface (Recognition Log)</li> </ul>	

Flouder Features	
App Features	<ul> <li>Completely edge processed</li> <li>Face Detection &amp; Recognition optimized for access control scenarios</li> <li>MOBOTIX events via MxMessageSystem</li> <li>White- and blacklisting</li> <li>Recognition log</li> </ul>
Maximum number of simultaneously detected / recognized faces	4
Maximum number of enrolled faces	1000
Meta Data / Statistic formats	JSON
Trial License	30-day trial license pre-installed
MxMessageSystem supported	Yes
Interfaces	compare supported camera's interfaces

#### Technical Specifications MOBOTIX Visage Technologies Face Recognition App

MOBOTIX Events	Yes
ONVIF Events	Yes (Generic Message event)

#### **Scene Requirements**

Minimum face height	1/10 of live image resolution (e.g. 30px @ VGA)
Recommended installation height (camera)	165 – 210 cm
Maximum Horizontal Angle	10°
Maximum Tilt Angle	5°

#### **Technical App Specifications**

Synchronous / Asynchronous App	Asynchronous
Accuracy	Typ. 97% (considering scene & technical requirements)
Processed number of frames per second	Typ. 2 fps
Recognition time	< 1 s
Detection time	Typ. 80 ms
Size of individual face data set	1 kB



EN\_02/22 MOBOTIX AG • Kaiserstrasse • D-67722 Langmeil • Tel.: +49 6302 9816-103 • sales@mobotix.com • www.mobotix.com MOBOTIX is a trademark of MOBOTIX AG registered in the European Union, the U.S.A., and in other countries. Subject to change without notice. MOBOTIX do not assume any liability for technical or editorial errors or omissions contained herein. All rights reserved. © MOBOTIX