

SilverNet BASE 500-90 Network bridge 500 Mbit/s White

Brand : SilverNet

Product code: SIL BASE 500-90

Product name : BASE 500-90

500Mbps, IEEE 802.11ac/a/n, 26dBm, 5.1-5.8 GHz, 2x2 MIMO, 26dBm, 90° Sector Antenna, 1G RJ-45, PoE

[SilverNet BASE 500-90 Network bridge 500 Mbit/s White:](#)

The BASE 500 90 is a highly secure long range Multipoint transmission system with a built in 90 degree sector antenna. Enhanced features include MIMO spatial multiplexing and ultrafast radio speed, giving the BASE 500 90 unparalleled data throughput capabilities, available 500Mbps full duplex.

Works with the MICRO Single radio as a remote transmitter.

The PRO Range is class leading, offering a wireless outdoor bridge that has been optimised for long transmission distances which has been designed to be extremely compact and rugged. Our FREE SilverView network monitoring software built in as standard ensures you have an outstanding feature packed solution.



Data transmission		Features	
Maximum data transfer rate *	500 Mbit/s	International Protection (IP) code	IP67
Maximum transfer distance	6000 m	Surge protection	✓
Supported data transfer rates	500Mbps	Quality of Service (QoS) support	✓
Antenna		Network Time Protocol (NTP) client	✓
Antenna design	Internal	Mean time between failures (MTBF)	60000 h
Antenna gain level (max)	13 dBi	System requirements	
Pan/tilt-axis range	180°	Minimum system requirements	Internet Explorer, Google Chrome, Mozilla Firefox
Antennas quantity	1	Compatible operating systems	Microsoft Windows, Mac OS, Linux Distributions
Wireless LAN features		Power	
Wi-Fi	✓	Power source type	PoE
Wi-Fi band	Single-band (5 GHz)	AC input voltage	100-240 V
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)	Power supply	15.4 W
WLAN data transfer rate (max)	867 Mbit/s	DC input voltage	24 - 48 V
Frequency band	5.1 - 5.8 GHz	Power consumption (typical)	6 W
Transmission gain	0 - 13 dB	Power consumption (max)	16 W
Signal strength	-40 dBm	Power over Ethernet (PoE)	✓
Channels quantity	25 channels	Power over Ethernet (PoE) voltage	48 V
Modulation	16-QAM, 64-QAM, 256-QAM, BPSK, QPSK	Power plug type	Type G
Receiver sensitivity	-82dBm@54Mbps, -74dBm@300Mbps, -68dBm@1.3Gbps	Operational conditions	
Output power (dBm)	26	Operating temperature (T-T)	-20 - 70 °C
Indoor range	6000m	Operating temperature (T-T)	-4 - 158 °F
Outdoor range	6000m	Operating relative humidity (H-H)	0 - 95%
Network		Storage temperature (T-T)	-40 - 90 °C
Ethernet LAN	✓	Storage relative humidity (H-H)	0 - 95%
Ethernet LAN interface type	Gigabit Ethernet	Certificates	
Ethernet LAN data rates	10,100,1000 Mbit/s	Certification	CE, FCC
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11i, IEEE 802.11n, IEEE 802.1Q, IEEE 802.1x, IEEE 802.3af	Weight & dimensions	
Cabling technology	10/100/1000Base-T(X)	Antenna diameter	48 cm
		Width	450 mm

Network		Weight & dimensions	
Full duplex	✓	Depth	170 mm
Auto MDI/MDI-X	✓	Height	65 mm
Static IP	✓	Weight	2.3 kg
Dynamic IP	✓	Packaging content	
Ports & interfaces		Packaging content	Includes 1 x radio, 1 x PoE injector PSU and 1 x Tilt and Swivel 3 Axis mounting bracket.
Connectivity technology	Wired & Wireless	Grounding	✓
Ethernet LAN (RJ-45) ports	1	PoE+ Injector(s)	✓
Security		Mounting bracket(s) included	✓
Security algorithms	256-bit AES, SNMP, SNMPv2, SSH	Power supply included	✓
Security features	802.1x, 802.11i, 802.1Q	Antenna included	✓
MAC address filtering	✓	Quick installation guide	✓
Authentication method	WPA2 AES	Packaging data	
Management features		Package width	215 mm
Management platform	SNMP V2	Package depth	605 mm
Web-based management	✓	Package height	140 mm
DHCP client	✓	Package weight	2.91 kg
Features		Package type	Box
Product type *	Network bridge	Quantity per pack	1 pc(s)
Product colour	White	Logistics data	
Remote control function	✓	UK Trade Tariff code	85176200
LED indicators	LAN, Signal strength	Country of origin	United Kingdom
Automatic Transmit Power Control (ATPC)	✓		
Wall mountable	✓		
Reset button	✓		



5060693980213

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 10-NOV-2024. Prints or copies of Information are only valid on the printed Publication date