

SilverNet FDD 801G-30-PCP Network bridge 1000 Mbit/s White

Brand : SilverNet

Product code: SIL FDD 801G-30-PCP

Product name : FDD 801G-30-PCP

- Point-to-Point Up to 2KM
 - Up to 1 Gbps throughput
 - Channel bandwidth from 250 to 1.000 MHz
 - 4/16/64 QAM Modulation schemes
 - Adaptive Coding and Modulation
 - Power Over Ethernet
 - Gigabit Ethernet or STM-1 interfaces
 - Layer1,2,3,4 Header Compression (upto + 200% throughput increase)
 - "Fiber Mode" operation for 2x Gigabit Ethernet transparent wire speed connections
 - Packet Fragmentation to minimize latency
 - MEF Carrier Ethernet Services
 - WRED support for congestion avoidance
 - Flexible QoS definition based on VLAN, IPv4, IPv6, MPLS exp bits
 - VLAN management and rewrite
 - Jumbo Frames up to 10Kbytes
- 80 GHz, 1 Gbps 30 cm Dish full duplex capacity link, up to 2 km



Data transmission		Features	
Maximum data transfer rate *	1000 Mbit/s	Quality of Service (QoS) support	✓
Maximum transfer distance	2000 m	Network Time Protocol (NTP) client	✓
Antenna		Flow control support	✓
Antenna design	External	RMON Statistics	✓
Antennas quantity	2	Link Loss Forwarding (LLF)	✓
Wireless LAN features		Link aggregation	✓
WLAN data transfer rate (max)	1000 Mbit/s	Power	
Frequency band	80GHz (71 - 76GHz, 81 - 86GHz)	Power source type	PoE
Modulation	8-QAM, 16-QAM, 32-QAM, 64-QAM, 128-QAM, 256-QAM, BPSK	AC input voltage	100-240 V
Receiver sensitivity	See Datasheet	Power consumption (typical)	32 W
Output power (dBm)	See Datasheet	Power consumption (max)	53 W
Frequency stability	5 ppm	Power over Ethernet (PoE)	✓
Outdoor range	2000	Power over Ethernet (PoE) voltage	55 V
Network		Power plug type	Type G
Ethernet LAN	✓	Operational conditions	
Ethernet LAN interface type	Gigabit Ethernet	Operating temperature (T-T)	-35 - 55 °C
Ethernet LAN data rates	10,100,1000 Mbit/s	Certificates	
Networking standards	IEEE 1588v2, IEEE 802.1ad, IEEE 802.1ag, IEEE 802.1p, IEEE 802.3ad, IEEE 802.3x	Certification	ETSI EN 302 217 / FCC CFR 47, Part 101 and Part 15
Cabling technology	10/100/1000Base-T(X)	Weight & dimensions	
Full duplex	✓	Antenna diameter	30 cm
Auto MDI/MDI-X	✓	Width	290 mm
Static IP	✓	Depth	302.5 mm
Dynamic IP	✓	Height	117.6 mm
		Weight	12.5 kg
Ports & interfaces		Packaging content	
Connectivity technology	Wired & Wireless	Grounding	✓
Ethernet LAN (RJ-45) ports	2	PoE+ Injector(s)	✓
Security		Mounting bracket(s) included	✓
Security algorithms	128-bit AES, 256-bit AES	Power supply included	✓
MAC address filtering	✓	Cables included	LAN (RJ-45)
Access Control List (ACL)	✓	Antenna included	✓
		Manual	✓
		Quick installation guide	✓

Management features		Other features	
Management protocols	SNMP v1/v2c/v3, HTTPs, SSH, SFTP, RADIUS,	Warranty period	2 year(s)
Web-based management	✓	Packaging data	
Features		Package width	400 mm
Product type *	Network bridge	Package depth	400 mm
Mounting type	Pole/Wall	Package height	500 mm
Product colour	White	Package weight	1.55 kg
Power LED	✓	Package type	Box
Real-Time Parameter Control (RTPC)	✓	Quantity per pack	1 pc(s)
Automatic Transmit Power Control (ATPC)	✓	Logistics data	
International Protection (IP) code	IP65	UK Trade Tariff code	85176200
Surge protection	✓		



5060693980831

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-NOV-2024. Prints or copies of Information are only valid on the printed Publication date