

## SilverNet LITE 95 Verkkosilta 95 Mbit/s Valkoinen

**Tuotemerkki :** SilverNet

**Tuotekoodi:** SIL LITE 95

**Tuotteen nimi :** LITE 95

SilverNet LITE 95. Tiedonsiirron enimmäisnopeus: 95 Mbit/s, Suurin siirtoetäisyys: 6000 m, Tuettu tiedonsiirtonopeus: 95Mbps. Antennin muotoilu: Sisäinen, Antennin vahvistustaso (maks.): 18 dBi, Panoroinnin/kallistusakselin alue: 180°. Wi-Fi-taajuus: Yksikaistainen (5 GHz), Wi-Fi-standardi: Wi-Fi 5 (802.11ac), WLAN-tiedonsiirtonopeus (maks.): 1300 Mbit/s. Ethernet LAN -käyttöliittymän tyyppi: Gigabit Ethernet, Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, Verkkostandardit: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11i, IEEE 802.11n, IEEE 802.1Q, IEEE 802.1x. Yhteysteknologia: Langallinen & langaton



Data transmission		Features	
Maximum data transfer rate *	95 Mbit/s	International Protection (IP) code	IP67
Maximum transfer distance	6000 m	Surge protection	✓
Supported data transfer rates	95Mbps	Quality of Service (QoS) support	✓
Antenna		Network Time Protocol (NTP) client	✓
Antenna design	Internal	Mean time between failures (MTBF)	60000 h
Antenna gain level (max)	18 dBi	System requirements	
Pan/tilt-axis range	180°	Minimum system requirements	Internet Explorer, Google Chrome, Mozilla Firefox
Antennas quantity	1	Compatible operating systems	Microsoft Windows, Mac OS, Linux Distributions
Wireless LAN features		Power	
Wi-Fi	✓	Power source type	DC, PoE
Wi-Fi band	Single-band (5 GHz)	AC input voltage	100-240 V
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)	Power supply	15.4 W
WLAN data transfer rate (max)	1300 Mbit/s	DC input voltage	24-48/48-56 V
Frequency band	5.1 - 5.8 GHz	Power consumption (typical)	6 W
Transmission gain	0 - 18 dB	Power consumption (max)	16 W
Signal strength	-40 dBm	Power over Ethernet (PoE)	✓
Channels quantity	25 channels	Power over Ethernet (PoE) voltage	48 V
Modulation	16-QAM, 64-QAM, 256-QAM, BPSK, QPSK	Power plug type	Type G
Receiver sensitivity	-82dBm@54Mbps, -74dBm@300Mbps, -68dBm@1.3Gbps	Operational conditions	
Output power (dBm)	26	Operating temperature (T-T)	-20 - 70 °C
Indoor range	6000m	Operating temperature (T-T)	-4 - 158 °F
Outdoor range	6000m	Operating relative humidity (H-H)	0 - 95%
Network		Storage temperature (T-T)	-40 - 90 °C
Ethernet LAN	✓	Storage relative humidity (H-H)	0 - 95%
Ethernet LAN interface type	Gigabit Ethernet		

Network		Certificates	
Ethernet LAN data rates	10,100,1000 Mbit/s	Certification	CE, FCC
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11i, IEEE 802.11n, IEEE 802.1Q, IEEE 802.1x	Weight & dimensions	
Cabling technology	10/100/1000Base-T(X)	Antenna diameter	30 cm
Full duplex	✓	Width	215 mm
Auto MDI/MDI-X	✓	Depth	215 mm
Static IP	✓	Height	77 mm
Dynamic IP	✓	Weight	1.6 kg
Ports & interfaces		Packaging content	
Connectivity technology	Wired & Wireless	Grounding	✓
Ethernet LAN (RJ-45) ports	1	PoE+ Injector(s)	✓
Security		Mounting bracket(s) included	✓
Security algorithms	256-bit AES, 802.1x RADIUS, SNMPv2, SSH	Power supply included	✓
MAC address filtering	✓	Antenna included	✓
Authentication method	WPA2 AES	Quick installation guide	✓
Management features		Packaging data	
Management protocols	SNMP V2	Package width	400 mm
Web-based management	✓	Package depth	310 mm
DHCP client	✓	Package height	100 mm
Features		Package weight	2.74 kg
Product type *	Network bridge	Package type	Box
Product colour	White	Quantity per pack	1 pc(s)
Remote control function	✓	Logistics data	
LED indicators	LAN, Signal strength	UK Trade Tariff code	85176200
Automatic Transmit Power Control (ATPC)	✓	Country of origin	United Kingdom
Wall mountable	✓		
Reset button	✓		



5706998408440



5060693980046

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.