

SilverNet MICRO 95 Network bridge 95 Mbit/s Black, White

Brand : SilverNet

Product code: SIL MICRO 95-PCP

Product name : MICRO 95

- Point-to-Point Outdoor Wireless Bridge Up to 2KM
- Point-to-MultiPoint Client
- Integrated 14dBi Antenna
- Designed for Outdoor applications
- SNMP
- AES Encryption up to 256bit
- MIMO with spatial multiplexing
- DFS (Dynamic Frequency Selection)
- TPC (Transmit Power Control)
- PoE 802.3af

95Mbps, MIMO, 5.1-5.8 GHz, 26 dBm, 14 dBi, RJ-45, PoE, 179x120x45mm, pre-configured SilverNet MICRO 95. Maximum data transfer rate: 95 Mbit/s, Maximum transfer distance: 2000 m, Supported data transfer rates: 95Mbps. Antenna design: Internal, Antenna gain level (max): 14 dBi. Wi-Fi band: Single-band (5 GHz), Top Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN data transfer rate (max): 1300 Mbit/s. Ethernet LAN interface type: Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s, Networking standards: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11i, IEEE 802.11n, IEEE 802.1Q, IEEE 802.1x, IEEE 802.3af. Connectivity technology: Wired & Wireless



Data transmission		Features	
Maximum data transfer rate *	95 Mbit/s	International Protection (IP) code	IP66
Maximum transfer distance	2000 m	Surge protection	✓
Supported data transfer rates	95Mbps	Quality of Service (QoS) support	✓
Antenna		Network Time Protocol (NTP) client	✓
Antenna design	Internal	Mean time between failures (MTBF)	60000 h
Antenna gain level (max)	14 dBi	System requirements	
Antennas quantity	1	Minimum system requirements	Internet Explorer, Google Chrome, Mozilla Firefox
Wireless LAN features		Compatible operating systems	Microsoft Windows, Mac OS, Linux Distributions
Wi-Fi	✓	Power	
Wi-Fi band	Single-band (5 GHz)	Power source type	DC, PoE
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)	AC input voltage	100-240 V
WLAN data transfer rate (max)	1300 Mbit/s	Power supply	15.4 W
Frequency band	5.1 - 5.8 GHz	DC input voltage	24-48/48-56 V
Transmission gain	0 - 14 dB	Power consumption (typical)	6 W
Signal strength	-40 dBm	Power consumption (max)	16 W
Channels quantity	25 channels	Power over Ethernet (PoE)	✓
Modulation	16-QAM, 64-QAM, 256-QAM, BPSK, QPSK	Power over Ethernet (PoE) voltage	48 V
Receiver sensitivity	-82dBm@54Mbps, -74dBm@300Mbps, -68dBm@1.3Gbps	Power plug type	Type G
Output power (dBm)	26	Operational conditions	
Indoor range	2000m	Operating temperature (T-T)	-20 - 70 °C
Outdoor range	2000m	Operating temperature (T-T)	-4 - 158 °F
Network		Operating relative humidity (H-H)	0 - 95%
Ethernet LAN	✓	Storage temperature (T-T)	-40 - 90 °C
Ethernet LAN interface type	Gigabit Ethernet	Storage relative humidity (H-H)	0 - 95%
Ethernet LAN data rates	10,100,1000 Mbit/s		

Network		Certificates	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11i, IEEE 802.11n, IEEE 802.1Q, IEEE 802.1x, IEEE 802.3af	Certification	CE, FCC
Cabling technology	10/100/1000Base-T(X)	Weight & dimensions	
Full duplex	✓	Antenna diameter	20.5 cm
Auto MDI/MDI-X	✓	Width	179 mm
Static IP	✓	Depth	120 mm
Dynamic IP	✓	Height	45 mm
		Weight	500 g
Ports & interfaces		Packaging content	
Connectivity technology	Wired & Wireless	PoE+ Injector(s)	✓
Ethernet LAN (RJ-45) ports	1	Mounting bracket(s) included	✓
		Power supply included	✓
Security		Antenna included	✓
Security algorithms	256-bit AES, 802.1x RADIUS, SNMP, SNMPv2	Quick installation guide	✓
MAC address filtering	✓	Packaging data	
Authentication method	WPA2 AES	Package width	290 mm
		Package depth	115 mm
Management features		Package height	320 mm
Management protocols	SNMP V2	Package weight	3.12 kg
Web-based management	✓	Package type	Box
DHCP client	✓	Quantity per pack	2 pc(s)
Features		Logistics data	
Product type *	Network bridge	UK Trade Tariff code	85176200
Product colour	Black, White	Country of origin	United Kingdom
Remote control function	✓		
LED indicators	LAN, Signal strength		
Automatic Transmit Power Control (ATPC)	✓		
Wall mountable	✓		
Reset button	✓		



5060693980039

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date