SilverNet TDD602-PCP Network bridge 200 Mbit/s White

Brand : SilverNet Product code: SIL TDD602-PCP

Product name: TDD602-PCP

- Interference Free Ethernet connectivity
- Point-to-Point up to 500m
- Up to 1Gbps throughput
- Designed for outdoor applications with rugged case design
- Small Form Factor
- 16 QAM to 64 QAM Modulations
- Gigabit Ethernet
- Power over Ethernet (PoE)
- WEB Management
- IP67 Rated

200Mbps, 3x RJ-45, 60 GHz, IP67, PoE+, 36 dBi, 165x165x100 mm

SilverNet TDD602-PCP. Maximum data transfer rate: 200 Mbit/s, Maximum transfer distance: 500 m. Antenna design: Internal, Antenna gain level (max): 36 dBi. Modulation: 16-QAM, 64-QAM, QPSK. Ethernet LAN data rates: 1000 Mbit/s, Networking standards: IEEE 802.1D, IEEE 802.1ag, IEEE 802.3ad, IEEE 802.3ah, IEEE 802.3at. Security algorithms: 128-bit AES, 256-bit AES, SNMPv2, SNMPv3



Data transmission		Features	
Maximum data transfer rate * Maximum transfer distance	200 Mbit/s 500 m	Product colour International Protection (IP) code	White IP67
Antenna		Power	
Antenna design	Internal	Power over Ethernet (PoE)	✓
Antenna gain level (max)	36 dBi	Operational conditions	
Wireless LAN features		Operating temperature (T-T)	-45 - 55 °C
Modulation	16-QAM, 64-QAM, QPSK	Certificates	
Network			ETSI EN 302 217, UK IR 2078 & IR
Ethernet LAN data rates	1000 Mbit/s IEEE 802.1D, IEEE 802.1ag, IEEE 802.3ad, IEEE 802.3ah, IEEE 802.3at	Certification	2000, USA FCC 15.255, EMC, UL60950
Networking standards		Weight & dimensions	
		Width	165 mm
Ports & interfaces		Donth	16E mm
Ports & Interfaces Ethernet LAN (RJ-45) ports	3	Depth Height	165 mm 100 mm
	3	Depth Height Weight	
Ethernet LAN (RJ-45) ports Security	128-bit AES, 256-bit AES, SNMPv2,	Height	100 mm
Ethernet LAN (RJ-45) ports		Height Weight	100 mm
Ethernet LAN (RJ-45) ports Security	128-bit AES, 256-bit AES, SNMPv2,	Height Weight Packaging data	100 mm 1.8 kg
Ethernet LAN (RJ-45) ports Security Security algorithms	128-bit AES, 256-bit AES, SNMPv2,	Height Weight Packaging data Quantity per pack	100 mm 1.8 kg
Ethernet LAN (RJ-45) ports Security Security algorithms Management features	128-bit AES, 256-bit AES, SNMPv2, SNMPv3	Height Weight Packaging data Quantity per pack Logistics data	100 mm 1.8 kg 1 pc(s)



5060693980800

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.