

SilverNet U2430-PCP Verkkosilta 500 Mbit/s Valkoinen

Tuotemerkki : SilverNet

Tuotekoodi: SIL U2430-PCP

Tuotteen nimi : U2430-PCP

SilverNet U2430-PCP. Tiedonsiirron enimmäisnopeus: 500 Mbit/s, Suurin siirtoetäisyys: 5000 m. Antennin muotoilu: Ulkoinen, Antennin vahvistustaso (maks.): 35 dBi. Taajuuskaista: 24 GHz, Modulointi: 16-QAM, 32-QAM, 64-QAM, 128-QAM, 512-QAM, 1024-QAM, Vastaanottimen herkkyys: 4 QAM (-88) 16 QAM (-81) 32 QAM (-76.5) 64 QAM (-73.5) 128 QAM (-70.5) 256 QAM (-67) 512 QAM.... Ethernet LAN -käyttöliittymän tyyppi: Gigabit Ethernet, Ethernet LAN -datanopeudet: 1000 Mbit/s, Verkkostandardit: IEEE 802.11ad, IEEE 802.1p, IEEE 802.3ad, IEEE 802.3x. Yhteysteknologia: Langallinen & langaton

Data transmission		Features	
Maximum data transfer rate *	500 Mbit/s	VoIP	✓
Maximum transfer distance	5000 m	International Protection (IP) code	IP65
Antenna		Quality of Service (QoS) support	✓
Antenna design	External	Flow control support	✓
Antenna gain level (max)	35 dBi	RMON Statistics	✓
Antennas quantity	2	Link Loss Forwarding (LLF)	✓
Wireless LAN features		Link aggregation	✓
Frequency band	24 GHz	Power	
Modulation	16-QAM, 32-QAM, 64-QAM, 128-QAM, 512-QAM, 1024-QAM	Power source type	PoE
Receiver sensitivity	4 QAM (-88) 16 QAM (-81) 32 QAM (-76.5) 64 QAM (-73.5) 128 QAM (-70.5) 256 QAM (-67) 512 QAM (-67.5) 1024 QAM (-60.5)	Power consumption (max)	35 W
Output power (dBm)	4 QAM (+21) 16 QAM (+19) 32 QAM (+17) 64 QAM (+17) 128 QAM (+17) 256 QAM (+17) 512 QAM (+17) 1024 QAM (+16)	Power over Ethernet (PoE)	✓
Frequency stability	5 ppm	Power over Ethernet (PoE) voltage	48 V
Network		Operational conditions	
Ethernet LAN	✓	Operating temperature (T-T)	-35 - 55 °C
Ethernet LAN interface type	Gigabit Ethernet	Certificates	
Ethernet LAN data rates	1000 Mbit/s	Certification	ETSI, FCC
Networking standards	IEEE 802.11ad, IEEE 802.1p, IEEE 802.3ad, IEEE 802.3x	Weight & dimensions	
Full duplex	✓	Antenna diameter	30 cm
Static IP	✓	Width	254 mm
Ports & interfaces		Depth	154 mm
Connectivity technology	Wired & Wireless	Height	254 mm
Ethernet LAN (RJ-45) ports	2	Weight	7 kg
Power over Ethernet plus (PoE+) ports quantity	1	Packaging content	
I/O ports	2x GE electrical	Grounding	✓
Management features		PoE+ Injector(s)	✓
Management platform	Web GUI, In Band management, SilverView NMS	Mounting bracket(s) included	✓
Web-based management	✓	Power supply included	✓
Features		Antenna included	✓
Product type *	Network bridge	Quick installation guide	✓
Product colour	White	Packaging data	
Remote control function	✓	Package width	400 mm
Power LED	✓	Package depth	400 mm
Real-Time Parameter Control (RTPC)	✓	Package height	500 mm
		Package weight	37 kg
		Package type	Box
		Quantity per pack	2 pc(s)
		Logistics data	
		UK Trade Tariff code	85176200

Features

Automatic Transmit Power Control (ATPC) ✓



5060693980749

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date