

# ASUS ROG STRIX B760-A GAMING WIFI D4 Intel B760 LGA 1700 ATX



**Tuotemerkki :** ASUS

**Tuotekoodi:** 90MB1DD0-M1EAY0

**Tuotteen nimi :** ROG STRIX B760-A GAMING WIFI D4

ASUS ROG STRIX B760-A GAMING WIFI D4. Suoritinvalmistaja: Intel, Prosessorin kanta: LGA 1700, Yhteensopivat prosessorit: Intel® Celeron®, Intel® Pentium® Gold, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9. Tuetut muistityypit: DDR4-SDRAM, Sisäinen enimmäismuisti: 128 GB, Muistipaikkojen tyyppi: DIMM. Tuetut tallennusasemaliitännät: M.2, SATA III, Tuetut tallennusasematyyppit: HDD & SSD, RAID-tasot: 0, 1, 5, 10. Ethernet-liitännän tyyppi: 2.5 Gigabit Ethernet, Wi-Fi-standardi: Wi-Fi 6E (802.11ax), Wi-Fi-standardit: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E.... Komponentti (tuotteelle): PC, Emolevyn muototekijä: ATX, Emolevyn piirisarjan perhe: Intel

| Processor                                |   | Rear panel I/O ports                              |   |
|--|---|---|---|
| Processor manufacturer *                 | Intel   | USB 2.0 ports quantity *                          | 4   |
| Processor socket *                       | LGA 1700  | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * | 2   |
| Compatible processor series *            | Intel® Celeron®, Intel® Pentium® Gold, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9 | USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity * | 1   |
| Supported processor sockets              | LGA 1700  | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity * | 1   |
| <b>Memory</b>                            |   | USB 3.2 Gen 2x2 Type-C ports quantity             | 1   |
| Supported memory types *                 | DDR4-SDRAM  | Ethernet LAN (RJ-45) ports *                      | 1   |
| Number of memory slots *                 | 4   | HDMI ports quantity *                             | 1   |
| Memory slots type                        | DIMM  | HDMI version                                      | 2.1   |
| Memory channels                          | Dual-channel  | DisplayPorts quantity                             | 1   |
| ECC compatibility                        | Non-ECC   | DisplayPort version                               | 1.4   |
| Supported memory clock speeds            | 2133,2400,2666,2800,2933,3200,3333,3400,3466,3600,3733,4000,4266,4400,4600,4800,5000,5066,5333 MHz        | Headphone outputs                                 | 1   |
| Supported memory clock speed (max)       | 5333 MHz  | Line-in   | ✓   |
| Maximum internal memory *                | 128 GB  | Microphone in                                     | ✓   |
| Unbuffered memory                        | ✓   | WiFi-AP antenna jack                              | 2   |
| <b>Storage controllers</b>               |   | <b>Network</b>                                    |   |
| Supported storage drive types            | HDD & SSD   | Ethernet LAN                                      | ✓   |
| Supported storage drive interfaces *     | M.2, SATA III   | Ethernet interface type                           | 2.5 Gigabit Ethernet  |
| Number of HDDs supported                 | 4   | Wi-Fi *   | ✓   |
| Number of storage drives supported       | 7   | Top Wi-Fi standard                                | Wi-Fi 6E (802.11ax)   |
| RAID support                             | ✓   | Wi-Fi standards                                   | 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E (802.11ax) |
| RAID levels                              | 0, 1, 5, 10   | Bluetooth   | ✓   |
| <b>Graphics</b>                          |   | Bluetooth version                                 | 5.3   |
| Parallel processing technology support * | Not supported   | <b>Features</b>                                   |   |
| <b>Internal I/O</b>                      |   | Motherboard chipset *                             | Intel B760  |
| USB 2.0 connectors *                     | 1   | Audio output channels *                           | 7.1 channels  |
| USB 3.2 Gen 1 (3.1 Gen 1) connectors *   | 1   | Component for *                                   | PC  |
| USB 3.2 Gen 2 (3.1 Gen 2) connectors *   | 1   | Motherboard form factor *                         | ATX   |
| Number of SATA III connectors *          | 4   | Motherboard chipset family *                      | Intel   |
| S/PDIF out connector                     | ✓   |   |   |
| Front panel audio connector              | ✓   |   |   |
| Front panel connector                    | ✓   |   |   |

| Internal I/O                                |   | Features                            |                            |
|---|---|-------------------------------------|----------------------------|
| ATX Power connector (24-pin)                | ✓ | Windows operating systems supported | Windows 10 x64, Windows 11 |
| CPU fan connector                           | ✓ | <b>Expansion slots</b>              |                            |
| Number of chassis fan connectors            | 4 | PCI Express x1 (Gen 3.x) slots      | 2                          |
| Peripheral (Molex) power connectors (4-pin) | 1 | PCI Express x16 (Gen 3.x) slots     | 1                          |
| EPS power connector (8-pin)                 | ✓ | PCI Express x16 (Gen 5.x) slots     | 1                          |
| Thunderbolt headers                         | 1 | Number of M.2 (M) slots             | 3                          |
| 12V power connector                         | ✓ | <b>BIOS</b>                         |                            |
| RGB LED pin header                          | ✓ | BIOS type *                         | UEFI AMI                   |
|   |   | BIOS memory size                    | 256 Mbit                   |
|   |   | <b>Weight &amp; dimensions</b>      |                            |
|   |   | Width                               | 305 mm                     |
|   |   | Depth                               | 244 mm                     |
|   |   | <b>Packaging content</b>            |                            |
|   |   | Cables included                     | SATA                       |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date