## ASUS TUF GAMING Z790-PLUS WIFI Intel Z790 LGA 1700 ATX

Tuotemerkki : ASUS Tuotekoodi: 90MB1D80-M1EAY0

Tuotteen nimi: TUF GAMING Z790-PLUS WIFI

ASUS TUF GAMING Z790-PLUS WIFI. Suoritinvalmistaja: Intel, Prosessorin kanta: LGA 1700, Yhteensopivat prosessorit: Intel® Celeron®, Intel® Pentium® Gold, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ .... Tuetut muistityypit: DDR5-SDRAM, Sisäinen enimmäismuisti: 128 GB, Muistipaikkojen tyyppi: DIMM. Tuetut tallennusasemaliitännät: M.2, SATA III, Tuetut tallennusasematyypit: HDD & SSD, RAID-tasot: 0, 1, 5, 10. Ethernet-liitännän tyyppi: 2.5 Gigabit Ethernet, Wi-Fi-standardi: Wi-Fi 6 (802.11ax), Wi-Fi-standardit: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax). Komponentti (tuotteelle): PC, Emolevyn muototekijä: ATX, Emolevyn piirisarjan perhe: Intel





| Processor   |                         |   | Rear panel I/O ports                              |  |
|---|-------------------------|---|---|--|
|   |                         |   |   |  |
| Processor manufacturer * Processor socket *       |                         | Intel<br>LGA 1700   | USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity * | 1  |
|   |                         | Intel® Celeron®, Intel® Pentium®<br>Gold, Intel® Core™ i3, Intel®                 | USB 3.2 Gen 2x2 Type-C ports quantity             | 1  |
| Compatible processor series *                     |                         | Core <sup>™</sup> i5, Intel® Core <sup>™</sup> i7, Intel®<br>Core <sup>™</sup> i9 | Ethernet LAN (RJ-45) ports *                      | 1  |
|   |                         |   | HDMI ports quantity *                             | 1  |
| Supported processor sockets                       |                         | LGA 1700  | HDMI version                                      | 2.1  |
| Memory  |                         |   | DisplayPorts quantity                             | 1  |
| Supported memory types * Number of memory slots * | DDR5-SDRAM<br>4         |   | DisplayPort version                               | 1.4  |
| Memory slots type                                 | DIMM                    |   | Headphone outputs                                 | 1  |
| Memory channels<br>ECC compatibility              | Dual-channel<br>Non-ECC |   | Line-in   | ✓  |
| Supported memory clock speeds                     | 4800,5000,5200,<br>MHz  | 5400,5600,5800,6000,6200,6400,6600,6800,7000,7200                                 | Microphone in                                     | ✓  |
| Supported memory clock speed (max)                | 7200 MHz                |   | S/PDIF out port                                   | ✓  |
| Maximum internal memory *                         | 128 GB                  |   | WiFi-AP antenna jack                              | 2  |
| Unbuffered memory                                 | 1                       |   | Network   |  |
| Storage controllers                               |                         |   |   |  |
| Supported storage drive types                     |                         | HDD & SSD   | Ethernet LAN                                      | ✓  |
| Supported storage drive interfaces                |                         | M.2, SATA III   | Ethernet interface type                           | 2.5 Gigabit Ethernet   |
| RAID support                                      |                         | 1   | Wi-Fi *   | ✓  |
| RAID levels                                       |                         | 0, 1, 5, 10   | Top Wi-Fi standard                                | Wi-Fi 6 (802.11ax)   |
| Graphics Parallel processing tech                 | nology                  |   | Wi-Fi standards                                   | 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax) |
| Parallel processing technology support *          |                         | Not supported   | Bluetooth   | <b>✓</b>   |
| Internal I/O                                      |                         |   | Bluetooth version                                 | 5.3  |
| USB 2.0 connectors *                              |                         | 2   | Features  |  |
| USB 3.2 Gen 1 (3.1 Gen 1)                         |                         | 1   | Motherboard chipset *                             | Intel Z790   |
| connectors *                                      |                         | -   | Audio chip  | Realtek S1220A   |
| USB 3.2 Gen 2 (3.1 Gen connectors *               | 2)                      | 1   | Audio output channels *                           | 7.1 channels   |

| nal I/O  |          | Features                        |                            |
|--|----------|---------------------------------|----------------------------|
| r of SATA III connectors *                         | 4        | Component for *                 | PC                         |
| t panel audio connector                            | ✓        | Motherboard form factor *       | ATX                        |
| Power connector (24-pin)                           | <b>✓</b> | Windows operating systems       | Intel                      |
| fan connector                                      | ✓        |                                 | Windows 10 x64, Windows 11 |
| ber of chassis fan connectors                      | 4        |                                 |                            |
| ower connector (8-pin)                             | ✓        |                                 |                            |
| ber of COM connectors                              | 1        | PCI Express x1 (Gen 3.x) slots  | 2                          |
| derbolt headers                                    | 1        | PCI Express x4 (Gen 4.x) slots  | 1                          |
| power connector                                    | <b>✓</b> | PCI Express x16 (Gen 4.x) slots | 1                          |
| ED pin header                                      | 1        | PCI Express x16 (Gen 5.x) slots | 1                          |
| D piii fieddei                                     |          | Number of M.2 (M) slots         | 4                          |
| panel I/O ports                                    |          | BIOS                            |                            |
| 3.2 Gen 1 (3.1 Gen 1) Type-A s quantity *          | 4        | BIOS type *                     | UEFI AMI                   |
| SB 3.2 Gen 2 (3.1 Gen 2) Type-A<br>orts quantity * | 2        | BIOS memory size                | 192 Mbit                   |
|  |          | Weight & dimensions             |                            |
|  |          | Width                           | 305 mm                     |
|  |          | Depth                           | 244 mm                     |
|  |          | Packaging content               |                            |
|  |          | Cables included                 | SATA                       |

