

## Lindy 10GBase-LR/LW SFP+ LC Module - Singlemode

Brand: Lindy Product code: 25039

Product name: 10GBase-LR/LW SFP+ LC Module -

Singlemode

10GBase-LR/LW SFP+ LC Module - Singlemode

Lindy 10GBase-LR/LW SFP+ LC Module - Singlemode:

The LINDY Transceiver Module allows a 10 Gigabit fibre optic connection to your network. Simply connect this module to your 10G Ethernet switch or to an Extender with SFP+ slot with a singlemode LC duplex cable for quick and easy connectivity.

Standard SFP+ Module for common networking systems like Cisco, HP, Dell, Ubiquiti, D-Link, Zyxel, Netgear, Arista, Juniper or for mainboards with SFP+ slots like SuperMicro, Asus, Gigabyte and Asrock.

The module is built to comply with MSA (Multi Sourcing Agreement) standards and uses the industry standard LC interface to extend your network connectivity up to 10Km. It is also is fully hot pluggable, which enables you to install it without powering down your network switch and interrupting traffic flow.

Please note: This module is only compatible with 10G switches. 1G or Fast Ethernet switches are not supported.





Performance		Operational conditions	
SFP transceiver type * Maximum data transfer rate * Interface type *	ximum data transfer rate * 10000 Mbit/s erface type * SFP+ gle-mode fiber (SMF) supported or optic connector Pransceiver standard ximum transfer distance velength  10000 Mbit/s SFP+  LC  LR, LW  10000 m  1310 nm	Maximum operating temperature Storage temperature (T-T) Operating relative humidity (H-H)	70 °C -40 - 85 °C 5 - 95%
Single-mode fiber (SMF) supported		Weight & dimensions	
Fiber optic connector  SFP transceiver standard  Maximum transfer distance  Wavelength  Ethernet LAN		Width Depth Height Weight	14.5 mm 57.4 mm 12 mm 17 g
Ethernet interface type	10 Gigabit Ethernet	Packaging data	
Duplex system	Full	Number of products included	1 pc(s)
Features		Package width	115 mm
Product colour Housing material Certification	Grey Metal UKCA, FCC, California Proposition 65	Package depth Package height Package weight	45 mm 20 mm 35 g
Power		Technical details	
Power consumption (typical)	1 W	Sustainability compliance Compliance certificates	✓ CE, REACH, RoHS



4002888250399

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.