



Lindy 70m Cat.6 4 Port HDMI 4K30 and IR Splitter Extender with Loop Out

Brand : Lindy

Product code: 38155

Product name : 70m Cat.6 4 Port HDMI 4K30 and IR Splitter Extender with Loop Out



- An advanced Splitter Extender that extends and distributes HDMI and IR signals to 4 displays at distances of up to 70m

- Supports resolutions up to 3840x2160@30Hz 4:4:4 8bit, including FullHD
- Features a loop-through HDMI output on the transmitter for local monitoring/cascading
- Supports power over Cable (PoC), only a single power supply is required for operation
- 2 year warranty

70m Cat.6 4 Port HDMI 4K30 and IR Splitter Extender with Loop Out

Lindy 70m Cat.6 4 Port HDMI 4K30 and IR Splitter Extender with Loop Out. Type: Transmitter & receiver, Connectivity technology: Wired, Maximum transfer distance: 50 m. Transmitter video port type: HDMI, Transmitter local video port type: HDMI. Receiver local video port type: HDMI. AC adapter output voltage: 12 V, AC adapter output current: 2.5 A. Transmitter width: 11.8 cm, Transmitter depth: 25 cm, Transmitter height: 3.2 cm

Features		Power	
Type *	Transmitter & receiver	AC adapter output voltage	12 V
Connectivity technology *	Wired	AC adapter output current	2.5 A
Maximum transfer distance	50 m	Weight & dimensions	
Cable types supported	Cat6	Transmitter width	11.8 cm
Maximum digital resolution	1920 x 1080 pixels	Transmitter depth	25 cm
Product colour	Black	Transmitter height	3.2 cm
LED indicators	✓	Transmitter weight	443 g
Certification	CE, FCC, RoHS, REACH	Receiver width	4.9 cm
Transmitter		Receiver depth	8.1 cm
Transmitter video port type	HDMI	Receiver height	2.5 cm
Transmitter local video port	✓	Receiver weight	131 g
Transmitter local video port type	HDMI	Packaging content	
Number of displays supported	4	AC adapter included	✓
RJ-45 ports quantity (transmitter)	4	Cables included	IR
Receiver		Manual	✓
Receiver local video port type	HDMI	Operational conditions	
RJ-45 ports quantity (receiver)	1	Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-20 - 60 °C
		Operating relative humidity (H-H)	20 - 90%
		Logistics data	
		Harmonized System (HS) code	84733080



4002888381550

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-NOV-2024. Prints or copies of Information are only valid on the printed Publication date