



Lindy 100m Cat.6 HDMI 4K60, Audio, IR and RS-232 HDBaseT KVM Extender

Brand : Lindy

Product code: 38343

Product name : 100m Cat.6 HDMI 4K60, Audio, IR and RS-232 HDBaseT KVM Extender



- Distributes HDMI resolutions up to 100m over Cat.6 network cable via HDBaseT technology
- Supports HDMI 18G resolutions up to 4K@60Hz 4:4:4, with additional support for HDR
- ARC Support as well as USB, RS-232, CEC and Ethernet pass-through and bi-directional IR for simple control
- Supports PoC (Power over cable), requiring a power supply connection from only one side of the installation
- 2 year warranty

100m Cat.6 HDMI 4K60, Audio, IR and RS-232 HDBaseT KVM Extender

Lindy 100m Cat.6 HDMI 4K60, Audio, IR and RS-232 HDBaseT KVM Extender. Type: Transmitter & receiver, Connectivity technology: Wired, Maximum transfer distance: 100 m. Transmitter video port type: HDMI. Receiver local video port type: HDMI. Transmitter width: 16.5 cm, Transmitter depth: 8.8 cm, Transmitter height: 2 cm. Package width: 265 mm, Package depth: 70 mm, Package height: 210 mm



Features		Weight & dimensions	
Type *	Transmitter & receiver	Transmitter width	16.5 cm
Connectivity technology *	Wired	Transmitter depth	8.8 cm
Maximum transfer distance	100 m	Transmitter height	2 cm
Cable types supported	Cat6	Transmitter weight	335 g
Maximum digital resolution	3840 x 2160 pixels	Receiver width	16.5 cm
Maximum refresh rate	60 Hz	Receiver depth	8.8 cm
Product colour	Black	Receiver height	2 cm
Material	Metal	Receiver weight	335 g
Certification	CE, UKCA, FCC, RoHS, REACH	Packaging data	
Transmitter		Package width	265 mm
Transmitter video port type	HDMI	Package depth	70 mm
RJ-45 ports quantity (transmitter)	1	Package height	210 mm
Receiver		Package weight	1.29 kg
Receiver local video port type	HDMI	Operational conditions	
RJ-45 ports quantity (receiver)	1	Operating temperature (T-T)	0 - 40 °C
Ports & interfaces		Storage temperature (T-T)	-20 - 60 °C
USB 2.0 ports quantity	2	Operating relative humidity (H-H)	20 - 90%
		Technical details	
		Weight	335 g
		Logistics data	
		Harmonized System (HS) code	84733080



4002888383431

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date