



Lindy 1m USB 3.2 Type A to C Cable, 10Gbps, Black Line

Brand : Lindy

Product code: 36916

Product name : 1m USB 3.2 Type A to C Cable, 10Gbps, Black Line

- Entry level USB 3.2 Gen 2 Type A to C cable for home and small office applications
- SuperSpeed USB 10Gbps - supports data transfer speeds up to 10Gbps (USB 3.1, USB 3.1 Gen 2)
- Robust PVC housing, nickel connectors, gold plated contacts
- Triple shielded cable, corrosion resistant tinned copper conductors
- 10 year warranty

1m USB 3.2 Type A to C Cable, 10Gbps, Black Line

Lindy 1m USB 3.2 Type A to C Cable, 10Gbps, Black Line. Cable length: 1 m. Connector 1: USB A, Connector 2: USB C, USB version: USB 3.2 Gen 1 (3.1 Gen 1), Maximum data transfer rate: 10 Gbit/s, Connector contacts plating: Gold, Product colour: Black



Features

USB version *	USB 3.2 Gen 1 (3.1 Gen 1)
Connector 1 *	USB A
Connector 2 *	USB C
Connector 1 gender *	Male
Connector 2 gender *	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
AWG wire size	26/30/30
Connector material	Nickel
Contact material	Phosphor bronze
Connector contacts plating	Gold
Cable jacket material	Polyvinyl chloride (PVC)
Conductor material	Tinned copper
Connector shielding	✓
Connector shield material	Aluminium
Connector housing material	Polyvinyl chloride (PVC)
Maximum data transfer rate	10000 Mbit/s
Maximum data transfer rate	10 Gbit/s
Product colour *	Black
Cable type	Round cable

Features

Plug and Play	✓
Nominal attenuation	0.5Mhz €" 15Ghz 40db

Weight & dimensions

Cable length *	1 m
Cable diameter	4.5 mm
Bend radius (min)	4.5 cm
Connector 1 dimensions (WxDxH)	15.5 x 35.1 x 7.8 mm
Connector 2 dimensions (WxDxH)	11 x 25.5 x 7.3 mm

Packaging data

Package type	Polybag
--------------	---------

Packaging content

Quantity per pack *	1 pc(s)
---------------------	---------

Operational conditions


Operating temperature (T-T)	-20 - 80 °C
Storage temperature (T-T)	-25 - 85 °C

Certificates

Certification	RoHS, REACH, UL
---------------	-----------------

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------



4002888369169

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.