



## Lindy 10 Port USB 3.0 Hub with On/Off Switches

**Brand :** Lindy

**Product code:** 43370

**Product name :** 10 Port USB 3.0 Hub with On/Off Switches



- Allows up to 10 USB 3.0 devices to be connected to a single port
- On/Off switch on each port allows users to manage power consumption of the connected devices
- SuperSpeed transfer rates up to 5Gbps, backwards compatible with USB 2.0 / 1.1
- 36W of power available for devices with large power requirements
- 2 year warranty

10 Port USB 3.0 Hub with On/Off Switches

Lindy 10 Port USB 3.0 Hub with On/Off Switches. Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-B, Hub interfaces: USB 3.2 Gen 1 (3.1 Gen 1) Type-A. Data transfer rate: 5000 Mbit/s, Product colour: Black, Housing material: Acrylonitrile butadiene styrene (ABS), Aluminium. Power supply type: AC, Input voltage: 12 V, Input current: 3 A. Width: 169.6 mm, Depth: 46.2 mm, Height: 25 mm. Quantity per pack: 1 pc(s), Package width: 205 mm, Package depth: 132 mm



Ports & interfaces		Packaging data	
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-B	Quantity per pack	1 pc(s)
Hub interfaces *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A	Package width	205 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	10	Package depth	132 mm
Ports quantity *	11	Package height	52 mm
DC-in jack	✓	Package weight	600 g
		Package type	Carton
Features		Packaging content	
Data transfer rate *	5000 Mbit/s	AC adapter included	✓
Product colour	Black	Included power plug types	AU, EU, UK, US
Housing material	Acrylonitrile butadiene styrene (ABS), Aluminium	Cables included	USB Type-A to USB Type-B
USB Power Delivery	✗	Manual	✓
Cable length	1 m	Operational conditions	
Certification	CE, FCC, RoHS & REACH, CP65	Operating temperature (T-T)	-5 - 56 °C
Power		Operating temperature (T-T)	23 - 133 °F
Power supply type	AC	Storage temperature (T-T)	-20 - 60 °C
Input voltage	12 V	Operating relative humidity (H-H)	5 - 95%
Input current	3 A	Technical details	
Weight & dimensions		Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS
Width	169.6 mm	Other features	
Depth	46.2 mm	Chipset	RTS5411
Height	25 mm		
Weight	42 g		



4002888433709

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-SEP-2024. Prints or copies of Information are only valid on the printed Publication date