

## Vertiv Avocent ACS8048MDDC-404 konsolipalvelin RJ-45

Tuotemerkki : Vertiv Tuoteperhe: Avocent Tuotekoodi:
ACS8048MDDC-404

O com

Tuotteen nimi: ACS8048MDDC-404

Vertiv Avocent ACS8048MDDC-404. Hallintaprotokolla: CLI, HTTP/ HTTPS, SNMP. Todennustapa: LOCAL,LDAP,RADIUS,TACACS+ and OneTimePasswords(OTP), Tietoturva-algoritmit: 3DES, 128-bit AES, 192-bit AES, 256-bit AES, AES, FIPS 140-2, HTTPS, IPSec, SHA-256, SNMP, SNMPv3,.... Console-portti: RJ-45, Pistorasian tyypit: C13 liitin. Käyttöjärjestelmä asennettu: Upotettu LINUX. Mitat (LxSxK): 438,2 x 241,3 x 44,5 mm, Paino: 3,4 kg



Technical details		Power	
Rack mounting Internal modem Zero Touch Provisioning (ZTP)	×	Power consumption (typical) Input current DC input voltage	14 W 0.5 A -48 V
Web-based management	·	Operational conditions	
Temperature sensor Product colour Event logging	✓ Black ✓	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-10 - 60 °C -20 - 70 °C 20 - 80% 5 - 95%
Management features		Certificates	
Management protocols  Security  Authentication method	CLI, HTTP/ HTTPS, SNMP  LOCAL,LDAP,RADIUS,TACACS+ and OneTimePasswords(OTP)  3DES, 128-bit AES, 192-bit AES, 256-bit AES, AES, FIPS 140-2, HTTPS, IPSec, SHA-256, SNMP,	Certification	FCC Class A, CE Class A (EU), ICES-003 (Canada), VCCI (Japan), RCM (Australia), Customs Union (CU), KCC (Korea), UL (USA), cUL (Canada), EN-60950 (EU), CB, Customs Union (CU)
Security algorithms		Memory	
IP address filtering One-time password (OTP)	SNMPv3, SSH, SSH-2  ✓	Flash memory RAM capacity RAM type eMMC capacity	16000 MB 1024 MB DDR3L 16 GB
Ports & interfaces	DI 45	Processor	10 00
Console port Serial ports quantity USB 2.0 ports quantity Ethernet LAN (RJ-45) ports SFP module slots quantity AC outlet types	RJ-45 48 8 2 C13 coupler	Processor family Processor architecture Processor cores Processor frequency	ARM Cortex-A9 ARM Cortex-A9 2 667 MHz
Software		Network	10DACE T 100DACE T 1000DACE T
Operating system installed	Embedded LINUX	Cable types supported	10BASE-T, 100BASE-T, 1000BASE-T Cat5, Cat5e, Cat6, Cat6+, Cat6a, Cat6e, Cat7, Fiber
Weight & dimensions	420.2 241.2 44.5	Other features	· · · ·
Dimensions (WxDxH) Weight	438.2 x 241.3 x 44.5 mm 3.4 kg	Safety	UL (USA), cUL (Canada), EN-60950 (EU), CB, Customs Union (CU)
Power			(30)
Power source type AC input frequency	DC 50 - 60 Hz		





636430086477

0636430086477

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.