

Vertiv Avocent ACS8032MDDC-400 konsolipalvelin RJ-45

Tuotemerkki : Vertiv

Tuoteperhe: Avocent

Tuotekoodi:
ACS8032MDDC-400



Tuotteen nimi :
ACS8032MDDC-400

Vertiv Avocent ACS8032MDDC-400. Hallintaprotokolla: CLI, HTTP/ HTTPS, SNMP. Todennustapa: LOCAL,LDAP,RADIUS,TACACS+ and OneTimePasswords(OTP), Tietoturva-algoritmit: 3DES, 128-bit AES, 192-bit AES, 256-bit AES, AES, FIPS 140-2, HTTPS, IPSec, SHA-256, SNMP, SNMPv3,.... Console-portti: RJ-45, Pistorasian tyyppi: C13 liitin. Käyttöjärjestelmä asennettu: Uputettu LINUX. Mitat (LxSxK): 438,2 x 241,3 x 44,5 mm, Paino: 3,4 kg

Technical details		Power	
Rack mounting	✓	Input current	0.5 A
Internal modem	✓	DC input voltage	-48 V
Zero Touch Provisioning (ZTP)	✓	Number of power supply units	2
Web-based management	✓	Operational conditions	
Temperature sensor	✓	Operating temperature (T-T)	-10 - 60 °C
Product colour	Black	Storage temperature (T-T)	-20 - 70 °C
Event logging	✓	Operating relative humidity (H-H)	20 - 80%
		Storage relative humidity (H-H)	5 - 95%
Management features		Certificates	
Management protocols	CLI, HTTP/ HTTPS, SNMP	Certification	FCC Class A, CE Class A (EU), ICES-003 (Canada), VCCI (Japan), RCM (Australia), Customs Union (CU), KCC (Korea), UL (USA), cUL (Canada), EN-60950 (EU), CB, Customs Union (CU)
Security		Memory	
Authentication method	LOCAL,LDAP,RADIUS,TACACS+ and OneTimePasswords(OTP)	Internal memory	1000 MB
Security algorithms	3DES, 128-bit AES, 192-bit AES, 256-bit AES, AES, FIPS 140-2, HTTPS, IPSec, SHA-256, SNMP, SNMPv3, SSH, SSH-2	Flash memory	16000 MB
IP address filtering	✓	RAM capacity	1024 MB
One-time password (OTP)	✓	RAM type	DDR3L
		eMMC capacity	16 GB
Ports & interfaces		Processor	
Console port	RJ-45	Processor family	ARM Cortex-A9
Serial ports quantity	32	Processor architecture	ARM Cortex-A9
USB 2.0 ports quantity	8	Processor cores	2
Ethernet LAN (RJ-45) ports	2	Processor frequency	667 MHz
SFP module slots quantity	2	Network	
AC outlet types	C13 coupler	Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T
Software		Cable types supported	Cat5, Cat5e, Cat6, Cat6+, Cat6a, Cat6e, Cat7, Fiber
Operating system installed	Embedded LINUX	Other features	
Weight & dimensions		Safety	UL (USA), cUL (Canada), EN-60950 (EU), CB, Customs Union (CU)
Dimensions (WxDxH)	438.2 x 241.3 x 44.5 mm		
Weight	3.4 kg		
Power			
Power source type	DC		
AC input frequency	50 - 60 Hz		
Power consumption (typical)	11 W		



0636430079097



636430079097

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.