

Vertiv Avocent ACS8032MDAC-404 konsolipalvelin RJ-45

Tuotemerkki : Vertiv

Tuoteperhe: Avocent

Tuotekoodi:
ACS8032MDAC-404



Tuotteen nimi :
ACS8032MDAC-404

Vertiv Avocent ACS8032MDAC-404. Hallintaprotokolla: CLI, HTTP/ HTTPS, SNMP. Todennustapa: LOCAL,LDAP,RADIUS,TACACS+ and OneTimePasswords(OTP), Tietoturva-algoritmit: 3DES, 128-bit AES, 192-bit AES, 256-bit AES, AES, FIPS 140-2, HTTPS, IPSec, SHA-256, SNMP, SNMPv3,.... Console-portti: RJ-45, Pistorasian tyypit: C13 liitin. Käyttäjärjestelmä asennettu: Upotettu LINUX. Mitat (LxSxK): 438,2 x 241,3 x 44,5 mm, Paino: 3,4 kg



Technical details		Power	
Rack mounting	✓	Power consumption (max)	35 W
Internal modem	✓	Input current	0.1 A
Zero Touch Provisioning (ZTP)	✓	Number of power supply units	2
Web-based management	✓	Operational conditions	
Temperature sensor	✓	Operating temperature (T-T)	-10 - 60 °C
Product colour	Black	Storage temperature (T-T)	-20 - 70 °C
Management features		Operating relative humidity (H-H)	20 - 80%
Management protocols	CLI, HTTP/ HTTPS, SNMP	Storage relative humidity (H-H)	5 - 95%
Security		Certificates	
Authentication method	LOCAL,LDAP,RADIUS,TACACS+ and OneTimePasswords(OTP)	Certification	FCC Class A, CE Class A (EU), ICES-003 (Canada), VCCI (Japan), RCM (Australia), Customs Union (CU), KCC (Korea), UL (USA), cUL (Canada), EN-60950 (EU), CB, Customs Union (CU)
Security algorithms	3DES, 128-bit AES, 192-bit AES, 256-bit AES, AES, FIPS 140-2, HTTPS, IPSec, SHA-256, SNMP, SNMPv3, SSH, SSH-2		
IP address filtering	✓	Memory	
One-time password (OTP)	✓	Flash memory	16000 MB
Ports & interfaces		RAM capacity	1024 MB
Console port	RJ-45	RAM type	DDR3L
Serial ports quantity	32	eMMC capacity	16 GB
USB 2.0 ports quantity	8	Processor	
Ethernet LAN (RJ-45) ports	2	Processor family	ARM Cortex-A9
SFP module slots quantity	2	Processor architecture	ARM Cortex-A9
AC outlet types	C13 coupler	Processor cores	2
Software		Processor frequency	667 MHz
Operating system installed	Embedded LINUX	Network	
Weight & dimensions		Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T
Dimensions (WxDxH)	438.2 x 241.3 x 44.5 mm	Cable types supported	Cat5, Cat5e, Cat6, Cat6+, Cat6a, Cat6e, Cat7, Fiber
Weight	3.4 kg	Other features	
Power		Safety	UL (USA), cUL (Canada), EN-60950 (EU), CB, Customs Union (CU)
Power source type	AC		

Power

AC input voltage	106 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (typical)	20 W



0636430086293



636430086293

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.