## **ATEN**

## ATEN CL1308N, RU KVM-kytkin Telineasennus musta



Tuotemerkki: ATEN Tuotekoodi: CL1308N-ATA-2XK06RG

Tuotteen nimi: CL1308N, RU

ATEN CL1308N, RU. Näppäimistöportin liitin: USB, PS/2, Hiiriportin liitin: USB, PS/2.

Enimmäiserottelutarkkuus: 1280 x 1024 pikseliä, Skannausväli: 1,255 s. Tuotteen väri: musta, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli, Muovi. Näyttö: LCD, Näytön halkaisija: 48,3 cm (19").

Tulojännite: 100-240 V, AC-syöttötaajuus: 50 - 60 Hz, Syöttöjännite: 1 A

Ports & interfaces		Power	
Number of computers controlled * Keyboard port type * Mouse port type *	8 USB, PS/2 USB, PS/2	Input voltage AC input frequency Input current	100-240 V 50 - 60 Hz 1 A
Performance		Power consumption (typical)	22 W
Maximum resolution * Scan interval DDC2B support	1280 x 1024 pixels 1,255 s ✓	System requirements Windows operating systems supported Linux operating systems supported	<i>*</i>
Hot-swap	<b>✓</b>	. 3,	
Design		Sustainability	D. 116
Rack mounting *	✓	Compliance certificates	RoHS
Rack capacity	10	Operational conditions	
		Operating temperature (T-T)	0 - 50 °C
Product colour *	Black	operating temperature (1-1)	
Product colour * Housing material	Black Metal, Plastic	Storage temperature (T-T)	-20 - 60 °C
		, , ,	
Housing material	Metal, Plastic	Storage temperature (T-T)	-20 - 60 °C
Housing material LED indicators	Metal, Plastic ✓	Storage temperature (T-T) Operating relative humidity (H-H)	-20 - 60 °C
Housing material LED indicators Push button	Metal, Plastic  ✓	Storage temperature (T-T) Operating relative humidity (H-H) Weight & dimensions	-20 - 60 °C 0 - 80%
Housing material LED indicators Push button Keyboard language	Metal, Plastic  ✓	Storage temperature (T-T) Operating relative humidity (H-H)  Weight & dimensions  Width Depth Height	-20 - 60 °C 0 - 80% 689.2 mm 483 mm 44 mm
Housing material LED indicators Push button Keyboard language Display	Metal, Plastic  ✓  ✓ Russian	Storage temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width Depth	-20 - 60 °C 0 - 80% 689.2 mm 483 mm
Housing material LED indicators Push button Keyboard language Display Built-in display *	Metal, Plastic  Russian	Storage temperature (T-T) Operating relative humidity (H-H)  Weight & dimensions  Width Depth Height	-20 - 60 °C 0 - 80% 689.2 mm 483 mm 44 mm

